

libximc  
2.3.2

Generated by Doxygen 1.8.1

Tue Sep 2 2014 20:25:38

# Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Introduction</b>                     | <b>1</b> |
| 1.1      | About                                   | 1        |
| 1.2      | System requirements                     | 1        |
| 1.2.1    | For rebuilding library                  | 1        |
| 1.2.2    | For using library                       | 2        |
| <b>2</b> | <b>How to rebuild library</b>           | <b>3</b> |
| 2.1      | Building on generic UNIX                | 3        |
| 2.2      | Building on debian-based linux systems  | 3        |
| 2.3      | Building on redhat-based linux systems  | 3        |
| 2.4      | Building on FreeBSD                     | 4        |
| 2.5      | Buliding on Mac OS X                    | 4        |
| 2.6      | Buliding on Windows                     | 4        |
| 2.7      | Source code access                      | 4        |
| <b>3</b> | <b>How to use with...</b>               | <b>5</b> |
| 3.1      | Usage with C                            | 5        |
| 3.1.1    | Visual C++                              | 5        |
| 3.1.2    | MinGW                                   | 5        |
| 3.1.3    | C++ Builder                             | 5        |
| 3.1.4    | XCode                                   | 6        |
| 3.1.5    | GCC                                     | 6        |
| 3.2      | .NET                                    | 6        |
| 3.3      | Delphi                                  | 6        |
| 3.4      | MATLAB                                  | 6        |
| <b>4</b> | <b>Data Structure Documentation</b>     | <b>7</b> |
| 4.1      | accessories_settings.t Struct Reference | 7        |
| 4.1.1    | Detailed Description                    | 7        |
| 4.1.2    | Field Documentation                     | 8        |
| 4.1.2.1  | MBRatedCurrent                          | 8        |
| 4.1.2.2  | MBRatedVoltage                          | 8        |

|          |  |    |
|----------|--|----|
| 4.1.2.3  | MBTorque                                   | 8  |
| 4.1.2.4  | TSGrad                                     | 8  |
| 4.2      | add_sync_in_action_calb.t Struct Reference | 8  |
| 4.3      | add_sync_in_action.t Struct Reference      | 8  |
| 4.3.1    | Detailed Description                       | 9  |
| 4.3.2    | Field Documentation                        | 9  |
| 4.3.2.1  | Speed                                      | 9  |
| 4.3.2.2  | uPosition                                  | 9  |
| 4.3.2.3  | uSpeed                                     | 9  |
| 4.4      | analog_data.t Struct Reference             | 9  |
| 4.4.1    | Detailed Description                       | 10 |
| 4.5      | brake_settings.t Struct Reference          | 11 |
| 4.5.1    | Detailed Description                       | 11 |
| 4.5.2    | Field Documentation                        | 11 |
| 4.5.2.1  | t1   | 11 |
| 4.5.2.2  | t2   | 11 |
| 4.5.2.3  | t3   | 11 |
| 4.5.2.4  | t4   | 11 |
| 4.6      | calibration.t Struct Reference             | 12 |
| 4.6.1    | Detailed Description                       | 12 |
| 4.7      | chart_data.t Struct Reference              | 12 |
| 4.7.1    | Detailed Description                       | 12 |
| 4.8      | control_settings_calb.t Struct Reference   | 13 |
| 4.8.1    | Field Documentation                        | 13 |
| 4.8.1.1  | MaxClickTime                               | 13 |
| 4.8.1.2  | Timeout                                    | 13 |
| 4.9      | control_settings.t Struct Reference        | 13 |
| 4.9.1    | Detailed Description                       | 14 |
| 4.9.2    | Field Documentation                        | 14 |
| 4.9.2.1  | MaxClickTime                               | 14 |
| 4.9.2.2  | MaxSpeed                                   | 14 |
| 4.9.2.3  | Timeout                                    | 14 |
| 4.9.2.4  | uDeltaPosition                             | 14 |
| 4.9.2.5  | uMaxSpeed                                  | 14 |
| 4.10     | controller_name.t Struct Reference         | 14 |
| 4.10.1   | Detailed Description                       | 15 |
| 4.10.2   | Field Documentation                        | 15 |
| 4.10.2.1 | ControllerName                             | 15 |
| 4.11     | ctp_settings.t Struct Reference            | 15 |
| 4.11.1   | Detailed Description                       | 15 |

|          |   |    |
|----------|---|----|
| 4.11.2   | Field Documentation                     | 16 |
| 4.11.2.1 | CTPMinError                             | 16 |
| 4.12     | debug_read_t Struct Reference           | 16 |
| 4.12.1   | Detailed Description                    | 16 |
| 4.13     | device_information_t Struct Reference   | 16 |
| 4.13.1   | Detailed Description                    | 16 |
| 4.14     | edges_settings_calb_t Struct Reference  | 17 |
| 4.15     | edges_settings_t Struct Reference       | 17 |
| 4.15.1   | Detailed Description                    | 17 |
| 4.15.2   | Field Documentation                     | 17 |
| 4.15.2.1 | LeftBorder                              | 17 |
| 4.15.2.2 | RightBorder                             | 18 |
| 4.15.2.3 | uLeftBorder                             | 18 |
| 4.15.2.4 | uRightBorder                            | 18 |
| 4.16     | encoder_information_t Struct Reference  | 18 |
| 4.16.1   | Detailed Description                    | 18 |
| 4.16.2   | Field Documentation                     | 18 |
| 4.16.2.1 | Manufacturer                            | 18 |
| 4.16.2.2 | PartNumber                              | 18 |
| 4.17     | encoder_settings_t Struct Reference     | 19 |
| 4.17.1   | Detailed Description                    | 19 |
| 4.17.2   | Field Documentation                     | 19 |
| 4.17.2.1 | MaxCurrentConsumption                   | 19 |
| 4.17.2.2 | MaxOperatingFrequency                   | 19 |
| 4.17.2.3 | SupplyVoltageMax                        | 19 |
| 4.17.2.4 | SupplyVoltageMin                        | 19 |
| 4.18     | engine_settings_calb_t Struct Reference | 20 |
| 4.18.1   | Field Documentation                     | 20 |
| 4.18.1.1 | Antiplay                                | 20 |
| 4.18.1.2 | NomCurrent                              | 20 |
| 4.18.1.3 | NomSpeed                                | 20 |
| 4.18.1.4 | NomVoltage                              | 20 |
| 4.18.1.5 | StepsPerRev                             | 20 |
| 4.19     | engine_settings_t Struct Reference      | 21 |
| 4.19.1   | Detailed Description                    | 21 |
| 4.19.2   | Field Documentation                     | 21 |
| 4.19.2.1 | Antiplay                                | 21 |
| 4.19.2.2 | NomCurrent                              | 21 |
| 4.19.2.3 | NomSpeed                                | 22 |
| 4.19.2.4 | NomVoltage                              | 22 |

|          |   |    |
|----------|---|----|
| 4.19.2.5 | StepsPerRev                               | 22 |
| 4.19.2.6 | uNomSpeed                                 | 22 |
| 4.20     | entype_settings_t Struct Reference        | 22 |
| 4.20.1   | Detailed Description                      | 22 |
| 4.21     | extio_settings_t Struct Reference         | 22 |
| 4.21.1   | Detailed Description                      | 23 |
| 4.22     | feedback_settings_t Struct Reference      | 23 |
| 4.22.1   | Detailed Description                      | 23 |
| 4.23     | gear_information_t Struct Reference       | 23 |
| 4.23.1   | Detailed Description                      | 24 |
| 4.23.2   | Field Documentation                       | 24 |
| 4.23.2.1 | Manufacturer                              | 24 |
| 4.23.2.2 | PartNumber                                | 24 |
| 4.24     | gear_settings_t Struct Reference          | 24 |
| 4.24.1   | Detailed Description                      | 25 |
| 4.24.2   | Field Documentation                       | 25 |
| 4.24.2.1 | Efficiency                                | 25 |
| 4.24.2.2 | InputInertia                              | 25 |
| 4.24.2.3 | MaxOutputBacklash                         | 25 |
| 4.24.2.4 | RatedInputSpeed                           | 25 |
| 4.24.2.5 | RatedInputTorque                          | 25 |
| 4.24.2.6 | ReductionIn                               | 25 |
| 4.24.2.7 | ReductionOut                              | 25 |
| 4.25     | get_position_calb_t Struct Reference      | 26 |
| 4.26     | get_position_t Struct Reference           | 26 |
| 4.26.1   | Detailed Description                      | 26 |
| 4.27     | hallsensor_information_t Struct Reference | 26 |
| 4.27.1   | Detailed Description                      | 26 |
| 4.27.2   | Field Documentation                       | 27 |
| 4.27.2.1 | Manufacturer                              | 27 |
| 4.27.2.2 | PartNumber                                | 27 |
| 4.28     | hallsensor_settings_t Struct Reference    | 27 |
| 4.28.1   | Detailed Description                      | 27 |
| 4.28.2   | Field Documentation                       | 27 |
| 4.28.2.1 | MaxCurrentConsumption                     | 27 |
| 4.28.2.2 | MaxOperatingFrequency                     | 27 |
| 4.28.2.3 | SupplyVoltageMax                          | 28 |
| 4.28.2.4 | SupplyVoltageMin                          | 28 |
| 4.29     | home_settings_calb_t Struct Reference     | 28 |
| 4.30     | home_settings_t Struct Reference          | 28 |

|  |    |
|--|----|
| 4.30.1 Detailed Description . . . . .                | 29 |
| 4.30.2 Field Documentation . . . . .                 | 29 |
| 4.30.2.1 FastHome . . . . .                          | 29 |
| 4.30.2.2 HomeDelta . . . . .                         | 29 |
| 4.30.2.3 SlowHome . . . . .                          | 29 |
| 4.30.2.4 uFastHome . . . . .                         | 29 |
| 4.30.2.5 uHomeDelta . . . . .                        | 29 |
| 4.30.2.6 uSlowHome . . . . .                         | 29 |
| 4.31 joystick_settings.t Struct Reference . . . . .  | 29 |
| 4.31.1 Detailed Description . . . . .                | 30 |
| 4.32 motor_information.t Struct Reference . . . . .  | 30 |
| 4.32.1 Detailed Description . . . . .                | 30 |
| 4.32.2 Field Documentation . . . . .                 | 31 |
| 4.32.2.1 Manufacturer . . . . .                      | 31 |
| 4.32.2.2 PartNumber . . . . .                        | 31 |
| 4.33 motor_settings.t Struct Reference . . . . .     | 31 |
| 4.33.1 Detailed Description . . . . .                | 32 |
| 4.33.2 Field Documentation . . . . .                 | 32 |
| 4.33.2.1 DetentTorque . . . . .                      | 32 |
| 4.33.2.2 MaxCurrent . . . . .                        | 32 |
| 4.33.2.3 MaxCurrentTime . . . . .                    | 32 |
| 4.33.2.4 MaxSpeed . . . . .                          | 32 |
| 4.33.2.5 MechanicalTimeConstant . . . . .            | 33 |
| 4.33.2.6 NoLoadCurrent . . . . .                     | 33 |
| 4.33.2.7 NoLoadSpeed . . . . .                       | 33 |
| 4.33.2.8 NominalCurrent . . . . .                    | 33 |
| 4.33.2.9 NominalPower . . . . .                      | 33 |
| 4.33.2.10 NominalSpeed . . . . .                     | 33 |
| 4.33.2.11 NominalTorque . . . . .                    | 33 |
| 4.33.2.12 NominalVoltage . . . . .                   | 33 |
| 4.33.2.13 RotorInertia . . . . .                     | 33 |
| 4.33.2.14 SpeedConstant . . . . .                    | 34 |
| 4.33.2.15 SpeedTorqueGradient . . . . .              | 34 |
| 4.33.2.16 StallTorque . . . . .                      | 34 |
| 4.33.2.17 TorqueConstant . . . . .                   | 34 |
| 4.33.2.18 WindingInductance . . . . .                | 34 |
| 4.33.2.19 WindingResistance . . . . .                | 34 |
| 4.34 move_settings_calb.t Struct Reference . . . . . | 34 |
| 4.35 move_settings.t Struct Reference . . . . .      | 35 |
| 4.35.1 Detailed Description . . . . .                | 35 |

|          |                                      |    |
|----------|--------------------------------------|----|
| 4.35.2   | Field Documentation                  | 35 |
| 4.35.2.1 | Accel                                | 35 |
| 4.35.2.2 | AntiplaySpeed                        | 35 |
| 4.35.2.3 | Decel                                | 35 |
| 4.35.2.4 | Speed                                | 35 |
| 4.35.2.5 | uAntiplaySpeed                       | 36 |
| 4.35.2.6 | uSpeed                               | 36 |
| 4.36     | pid_settings_t Struct Reference      | 36 |
| 4.36.1   | Detailed Description                 | 36 |
| 4.37     | power_settings_t Struct Reference    | 36 |
| 4.37.1   | Detailed Description                 | 37 |
| 4.37.2   | Field Documentation                  | 37 |
| 4.37.2.1 | CurrentSetTime                       | 37 |
| 4.37.2.2 | CurrReductDelay                      | 37 |
| 4.37.2.3 | HoldCurrent                          | 37 |
| 4.37.2.4 | PowerOffDelay                        | 37 |
| 4.38     | secure_settings_t Struct Reference   | 37 |
| 4.38.1   | Detailed Description                 | 38 |
| 4.38.2   | Field Documentation                  | 38 |
| 4.38.2.1 | Criticalpwr                          | 38 |
| 4.38.2.2 | Criticalusb                          | 38 |
| 4.38.2.3 | CriticalT                            | 38 |
| 4.38.2.4 | CriticalUpwr                         | 38 |
| 4.38.2.5 | CriticalUusb                         | 38 |
| 4.38.2.6 | LowUpwrOff                           | 39 |
| 4.38.2.7 | MinimumUusb                          | 39 |
| 4.39     | serial_number_t Struct Reference     | 39 |
| 4.39.1   | Detailed Description                 | 39 |
| 4.40     | set_position_calb_t Struct Reference | 39 |
| 4.41     | set_position_t Struct Reference      | 39 |
| 4.41.1   | Detailed Description                 | 40 |
| 4.42     | stage_information_t Struct Reference | 40 |
| 4.42.1   | Detailed Description                 | 40 |
| 4.42.2   | Field Documentation                  | 40 |
| 4.42.2.1 | Manufacturer                         | 40 |
| 4.42.2.2 | PartNumber                           | 41 |
| 4.43     | stage_name_t Struct Reference        | 41 |
| 4.43.1   | Detailed Description                 | 41 |
| 4.43.2   | Field Documentation                  | 41 |
| 4.43.2.1 | PositionerName                       | 41 |

|          |   |    |
|----------|---|----|
| 4.44     | stage_settings_t Struct Reference         | 41 |
| 4.44.1   | Detailed Description                      | 42 |
| 4.44.2   | Field Documentation                       | 42 |
| 4.44.2.1 | HorizontalLoadCapacity                    | 42 |
| 4.44.2.2 | LeadScrewPitch                            | 42 |
| 4.44.2.3 | MaxCurrentConsumption                     | 42 |
| 4.44.2.4 | MaxSpeed                                  | 42 |
| 4.44.2.5 | SupplyVoltageMax                          | 42 |
| 4.44.2.6 | SupplyVoltageMin                          | 42 |
| 4.44.2.7 | TravelRange                               | 43 |
| 4.44.2.8 | Units                                     | 43 |
| 4.44.2.9 | VerticalLoadCapacity                      | 43 |
| 4.45     | status_calb_t Struct Reference            | 43 |
| 4.46     | status_t Struct Reference                 | 44 |
| 4.46.1   | Detailed Description                      | 44 |
| 4.46.2   | Field Documentation                       | 45 |
| 4.46.2.1 | uCurPosition                              | 45 |
| 4.46.2.2 | uCurSpeed                                 | 45 |
| 4.47     | sync_in_settings_calb_t Struct Reference  | 45 |
| 4.47.1   | Field Documentation                       | 45 |
| 4.47.1.1 | ClutterTime                               | 45 |
| 4.48     | sync_in_settings_t Struct Reference       | 45 |
| 4.48.1   | Detailed Description                      | 46 |
| 4.48.2   | Field Documentation                       | 46 |
| 4.48.2.1 | ClutterTime                               | 46 |
| 4.48.2.2 | Speed                                     | 46 |
| 4.48.2.3 | uPosition                                 | 46 |
| 4.48.2.4 | uSpeed                                    | 46 |
| 4.49     | sync_out_settings_calb_t Struct Reference | 46 |
| 4.49.1   | Field Documentation                       | 47 |
| 4.49.1.1 | SyncOutPeriod                             | 47 |
| 4.49.1.2 | SyncOutPulseSteps                         | 47 |
| 4.50     | sync_out_settings_t Struct Reference      | 47 |
| 4.50.1   | Detailed Description                      | 47 |
| 4.50.2   | Field Documentation                       | 48 |
| 4.50.2.1 | Accuracy                                  | 48 |
| 4.50.2.2 | SyncOutPeriod                             | 48 |
| 4.50.2.3 | SyncOutPulseSteps                         | 48 |
| 4.50.2.4 | uAccuracy                                 | 48 |
| 4.51     | uart_settings_t Struct Reference          | 48 |



|   |           |
|---|-----------|
| 4.51.1 Detailed Description . . . . .           | 48        |
| <b>5 File Documentation . . . . .</b>           | <b>49</b> |
| 5.1 ximc.h File Reference . . . . .             | 49        |
| 5.1.1 Detailed Description . . . . .            | 69        |
| 5.1.2 Macro Definition Documentation . . . . .  | 69        |
| 5.1.2.1 BORDERS_SWAP_MISSET_DETECTION . . . . . | 69        |
| 5.1.2.2 DRIVER_TYPE_DISCRETE_FET . . . . .      | 69        |
| 5.1.2.3 ENGINE_ACCEL_ON . . . . .               | 69        |
| 5.1.2.4 ENGINE_ANTIPLAY . . . . .               | 70        |
| 5.1.2.5 ENGINE_MAX_SPEED . . . . .              | 70        |
| 5.1.2.6 ENGINE_REVERSE . . . . .                | 70        |
| 5.1.2.7 ENGINE_TYPE_TEST . . . . .              | 70        |
| 5.1.2.8 ENUMERATE_PROBE . . . . .               | 70        |
| 5.1.2.9 EXTIO_SETUP_INVERT . . . . .            | 70        |
| 5.1.2.10 HOME_DIR_FIRST . . . . .               | 70        |
| 5.1.2.11 HOME_DIR_SECOND . . . . .              | 70        |
| 5.1.2.12 JOY_REVERSE . . . . .                  | 70        |
| 5.1.2.13 MVCMD_ERROR . . . . .                  | 71        |
| 5.1.2.14 REV_SENS_INV . . . . .                 | 71        |
| 5.1.2.15 STATE_ALARM . . . . .                  | 71        |
| 5.1.2.16 SYNCIN_GOTOPOSITION . . . . .          | 71        |
| 5.1.2.17 SYNCOUT_ENABLED . . . . .              | 71        |
| 5.1.2.18 XIMC_API . . . . .                     | 71        |
| 5.1.3 Typedef Documentation . . . . .           | 71        |
| 5.1.3.1 logging_callback_t . . . . .            | 71        |
| 5.1.4 Function Documentation . . . . .          | 71        |
| 5.1.4.1 close_device . . . . .                  | 71        |
| 5.1.4.2 command_clear_fram . . . . .            | 72        |
| 5.1.4.3 command_eeread_settings . . . . .       | 72        |
| 5.1.4.4 command_eesave_settings . . . . .       | 72        |
| 5.1.4.5 command_home . . . . .                  | 72        |
| 5.1.4.6 command_left . . . . .                  | 73        |
| 5.1.4.7 command_loft . . . . .                  | 73        |
| 5.1.4.8 command_move . . . . .                  | 73        |
| 5.1.4.9 command_movr . . . . .                  | 73        |
| 5.1.4.10 command_power_off . . . . .            | 73        |
| 5.1.4.11 command_read_settings . . . . .        | 74        |
| 5.1.4.12 command_reset . . . . .                | 74        |
| 5.1.4.13 command_right . . . . .                | 74        |

|          |  |    |
|----------|--|----|
| 5.1.4.14 | <a href="#">command_save_settings</a>            | 74 |
| 5.1.4.15 | <a href="#">command_sstp</a>                     | 74 |
| 5.1.4.16 | <a href="#">command_stop</a>                     | 75 |
| 5.1.4.17 | <a href="#">command_update_firmware</a>          | 75 |
| 5.1.4.18 | <a href="#">command_zero</a>                     | 75 |
| 5.1.4.19 | <a href="#">enumerate_devices</a>                | 75 |
| 5.1.4.20 | <a href="#">free_enumerate_devices</a>           | 75 |
| 5.1.4.21 | <a href="#">get_accessories_settings</a>         | 76 |
| 5.1.4.22 | <a href="#">get_analog_data</a>                  | 76 |
| 5.1.4.23 | <a href="#">get_bootloader_version</a>           | 76 |
| 5.1.4.24 | <a href="#">get_brake_settings</a>               | 76 |
| 5.1.4.25 | <a href="#">get_chart_data</a>                   | 76 |
| 5.1.4.26 | <a href="#">get_control_settings</a>             | 77 |
| 5.1.4.27 | <a href="#">get_controller_name</a>              | 77 |
| 5.1.4.28 | <a href="#">get_ctp_settings</a>                 | 77 |
| 5.1.4.29 | <a href="#">get_debug_read</a>                   | 77 |
| 5.1.4.30 | <a href="#">get_device_count</a>                 | 78 |
| 5.1.4.31 | <a href="#">get_device_information</a>           | 78 |
| 5.1.4.32 | <a href="#">get_device_name</a>                  | 78 |
| 5.1.4.33 | <a href="#">get_edges_settings</a>               | 78 |
| 5.1.4.34 | <a href="#">get_encoder_information</a>          | 79 |
| 5.1.4.35 | <a href="#">get_encoder_settings</a>             | 79 |
| 5.1.4.36 | <a href="#">get_engine_settings</a>              | 79 |
| 5.1.4.37 | <a href="#">get_entype_settings</a>              | 79 |
| 5.1.4.38 | <a href="#">get_enumerate_device_information</a> | 80 |
| 5.1.4.39 | <a href="#">get_enumerate_device_serial</a>      | 80 |
| 5.1.4.40 | <a href="#">get_extio_settings</a>               | 80 |
| 5.1.4.41 | <a href="#">get_feedback_settings</a>            | 80 |
| 5.1.4.42 | <a href="#">get_firmware_version</a>             | 81 |
| 5.1.4.43 | <a href="#">get_gear_information</a>             | 81 |
| 5.1.4.44 | <a href="#">get_gear_settings</a>                | 81 |
| 5.1.4.45 | <a href="#">get_hallsensor_information</a>       | 81 |
| 5.1.4.46 | <a href="#">get_hallsensor_settings</a>          | 81 |
| 5.1.4.47 | <a href="#">get_home_settings</a>                | 82 |
| 5.1.4.48 | <a href="#">get_joystick_settings</a>            | 82 |
| 5.1.4.49 | <a href="#">get_motor_information</a>            | 82 |
| 5.1.4.50 | <a href="#">get_motor_settings</a>               | 82 |
| 5.1.4.51 | <a href="#">get_move_settings</a>                | 83 |
| 5.1.4.52 | <a href="#">get_pid_settings</a>                 | 83 |
| 5.1.4.53 | <a href="#">get_position</a>                     | 83 |

|          |  |    |
|----------|--|----|
| 5.1.4.54 | <a href="#">get_power_settings</a>             | 83 |
| 5.1.4.55 | <a href="#">get_secure_settings</a>            | 83 |
| 5.1.4.56 | <a href="#">get_serial_number</a>              | 84 |
| 5.1.4.57 | <a href="#">get_stage_information</a>          | 84 |
| 5.1.4.58 | <a href="#">get_stage_name</a>                 | 84 |
| 5.1.4.59 | <a href="#">get_stage_settings</a>             | 84 |
| 5.1.4.60 | <a href="#">get_status</a>                     | 84 |
| 5.1.4.61 | <a href="#">get_status_calb</a>                | 85 |
| 5.1.4.62 | <a href="#">get_sync_in_settings</a>           | 85 |
| 5.1.4.63 | <a href="#">get_sync_out_settings</a>          | 85 |
| 5.1.4.64 | <a href="#">get_uart_settings</a>              | 85 |
| 5.1.4.65 | <a href="#">goto_firmware</a>                  | 86 |
| 5.1.4.66 | <a href="#">has_firmware</a>                   | 86 |
| 5.1.4.67 | <a href="#">logging_callback_stderr_narrow</a> | 86 |
| 5.1.4.68 | <a href="#">logging_callback_stderr_wide</a>   | 86 |
| 5.1.4.69 | <a href="#">msec_sleep</a>                     | 86 |
| 5.1.4.70 | <a href="#">open_device</a>                    | 87 |
| 5.1.4.71 | <a href="#">probe_device</a>                   | 87 |
| 5.1.4.72 | <a href="#">service_command_updf</a>           | 87 |
| 5.1.4.73 | <a href="#">set_accessories_settings</a>       | 87 |
| 5.1.4.74 | <a href="#">set_add_sync_in_action</a>         | 87 |
| 5.1.4.75 | <a href="#">set_brake_settings</a>             | 88 |
| 5.1.4.76 | <a href="#">set_control_settings</a>           | 88 |
| 5.1.4.77 | <a href="#">set_controller_name</a>            | 88 |
| 5.1.4.78 | <a href="#">set_ctp_settings</a>               | 88 |
| 5.1.4.79 | <a href="#">set_edges_settings</a>             | 88 |
| 5.1.4.80 | <a href="#">set_encoder_information</a>        | 89 |
| 5.1.4.81 | <a href="#">set_encoder_settings</a>           | 89 |
| 5.1.4.82 | <a href="#">set_engine_settings</a>            | 89 |
| 5.1.4.83 | <a href="#">set_entype_settings</a>            | 89 |
| 5.1.4.84 | <a href="#">set_extio_settings</a>             | 90 |
| 5.1.4.85 | <a href="#">set_feedback_settings</a>          | 90 |
| 5.1.4.86 | <a href="#">set_gear_information</a>           | 90 |
| 5.1.4.87 | <a href="#">set_gear_settings</a>              | 90 |
| 5.1.4.88 | <a href="#">set_hallsensor_information</a>     | 91 |
| 5.1.4.89 | <a href="#">set_hallsensor_settings</a>        | 91 |
| 5.1.4.90 | <a href="#">set_home_settings</a>              | 91 |
| 5.1.4.91 | <a href="#">set_joystick_settings</a>          | 91 |
| 5.1.4.92 | <a href="#">set_logging_callback</a>           | 92 |
| 5.1.4.93 | <a href="#">set_motor_information</a>          | 92 |

|           |                                       |    |
|-----------|---------------------------------------|----|
| 5.1.4.94  | <a href="#">set_motor_settings</a>    | 92 |
| 5.1.4.95  | <a href="#">set_move_settings</a>     | 92 |
| 5.1.4.96  | <a href="#">set_pid_settings</a>      | 93 |
| 5.1.4.97  | <a href="#">set_position</a>          | 93 |
| 5.1.4.98  | <a href="#">set_power_settings</a>    | 93 |
| 5.1.4.99  | <a href="#">set_secure_settings</a>   | 93 |
| 5.1.4.100 | <a href="#">set_serial_number</a>     | 94 |
| 5.1.4.101 | <a href="#">set_stage_information</a> | 94 |
| 5.1.4.102 | <a href="#">set_stage_name</a>        | 94 |
| 5.1.4.103 | <a href="#">set_stage_settings</a>    | 94 |
| 5.1.4.104 | <a href="#">set_sync_in_settings</a>  | 94 |
| 5.1.4.105 | <a href="#">set_sync_out_settings</a> | 95 |
| 5.1.4.106 | <a href="#">set_uart_settings</a>     | 95 |
| 5.1.4.107 | <a href="#">write_key</a>             | 95 |
| 5.1.4.108 | <a href="#">ximc_fix_usbser_sys</a>   | 96 |
| 5.1.4.109 | <a href="#">ximc_version</a>          | 96 |

# Chapter 1

## Introduction

### 1.1 About

Congratulations on choosing XIMC multi-platform programming library! This document contains all information about XIMC library. It utilizes well known virtual COM-port interface, so you can use it on Windows 7, Windows Vista, Windows XP, Windows Server 2003, Windows 2000, Linux, Mac OS X. XIMC multi-platform programming library supports plug/unplug on the fly. One program can control one device. Multiple processes (programs) that control one device simultaneously are not allowed.

### 1.2 System requirements

#### 1.2.1 For rebuilding library

On Windows:

- Windows 2000 or later, 64-bit system (if compiling both architectures) or 32-bit system.
- Microsoft Visual C++ 2008 or later
- cygwin with tar, bison, flex installed

On Linux or FreeBSD:

- 64-bit or/and 32-bit system
- gcc 4 or later
- common autotools: autoconf, autoheader, aclocal, automake, autoreconf, libtool
- gmake
- doxygen - for building docs
- LaTeX distribution (TeX or texlive) - for building docs
- flex 2.5.30+
- bison
- mercurial (for building developer version from hg)

On Mac OS X:

- XCode 4

- doxygen
- mactex
- autotools
- mercurial (for building developer version from hg)

If mercurial is used, please enable 'purge' extension by adding to `~/.hgrc` following lines:

```
[extensions]
hgext.purge=
```

### 1.2.2 For using library

Supported operating systems (32 or 64 bit):

- Mac OS X 10.6
- Windows 2000 or later
- Autotools-compatible unix. Package is installed from sources.
- Linux debian-based. DEB package is built against Debian Squeeze 6
- Linux rpm-based. RPM is built against OpenSUSE 10
- FreeBSD 9. Package is provided.

Build requirements:

- Windows: Microsoft Visual C++ 2008 or mingw (currently not supported)
- UNIX: gcc 4, gmake
- Mac OS X: XCode 4

## Chapter 2

# How to rebuild library

### 2.1 Building on generic UNIX

Generic version could be built with standard autotools.

```
./build.sh lib
```

Built files (library, headers, documentation) are installed to `./dist/local` directory. It is a generic developer build. Sometimes you need to specify additional parameters to command line for your machine. Please look to following OS sections.

### 2.2 Building on debian-based linux systems

Requirement: 64-bit and 32-bit debian system, ubuntu Typical set of packages: gcc, autotools, autoconf, libtool, dpkg-dev, flex, bison, doxygen, texlive, mercurial

It's required to match library and host architecture: 64-bit library can be built only at 64-bit host, 32-bit library - only at 32-bit host.

To build library and package Invoke a script:

```
$ ./build.sh libdeb
```

Grab packages from `./dist/latest/deb` and locally installed binaries from `./dist/local`.

### 2.3 Building on redhat-based linux systems

Requirement: 64-bit redhat-based system (Fedora, Red Hat, SUSE) Typical set of packages: gcc, autotools, autoconf, libtool, flex, bison, doxygen, texlive, mercurial

It's possible to build both 32- and 64-bit libraries on 64-bit host system. 64-bit library can't be built on 32-bit system.

To build library and package invoke a script:

```
$ ./build.sh librpm
```

Grab packages from `./dist/latest/rpm` and locally installed binaries from `./dist/local`.

## 2.4 Building on FreeBSD

Requirement: 64-bit or 32-bit FreeBSD Typical set of packages: gcc, autotools, autoconf, libtool, flex, bison, doxygen, teTeX, mercurial

It's required to match library and host architecture. Also you need to fix a configure.ac to exclude SOVER from the package name (freebsd does not use linux conventions on library versioning).

Attention! It's needed to specify additional parameters for a simple build.

```
$ ./build.sh lib LEX=/usr/local/bin/flex CXXFLAGS=-I/usr/local/include/flex
```

To build a library and package invoke following command. It requires sudo privileges for port installing and specially crafted /usr/ports/local tree. Consult a script for details.

```
$ ./build.sh libfreebsd
```

Grab packages from ./dist/latest/freebsd.

## 2.5 Buliding on Mac OS X

To build and package a script invoke a script:

```
$ ./build.sh libosx
```

Built library (classical and framework), examples (classical and .app), documentation are located at ./dist/latest/mac-osx, locally installed binaries from ./dist/local.

## 2.6 Buliding on Windows

Requirements: 64-bit windows (build script builds both architectures), cygwin (must be installed to a default path), mercurial.

Invoke a script:

```
$ ./build.bat
```

Grab packages from ./dist/latest/win32 and ./dist/latest/win64

## 2.7 Source code access

XIMC source codes are given under special request.



## Chapter 3

# How to use with...

Library usage can be examined from test application testapp. Non-C languages are supported because library supports stdcall calling convention and so can be used with a variety of languages.

C test project is located at 'examples/testapp' directory, C# test project - at 'examples/testcs', VB.NET - 'examples/testvbnet', Delphi 6 - 'examples/testdelphi', sample bindings for MATLAB - 'examples/testmatlab'

### 3.1 Usage with C

#### 3.1.1 Visual C++

Testapp can be built using testapp.sln. Library must be compiled with MS Visual C++ too, mingw-library isn't supported. Make sure that Microsoft Visual C++ Redistributable Package is installed.

NOTE: Example compiled with (MS Visual C++ 2008 SP1 and needs package 9.0.307291 (provided with SDK - vc\_redist.x86 or vc\_redist.x64)

Open solution examples/testapp/testapp.sln, build and run from the IDE.

#### 3.1.2 MinGW

MinGW is a port of GCC to win32 platform. It's required to install MinGW package. Currently not supported

MinGW-compiled testapp can be built with MS Visual C++ or mingw library.

```
$ mingw32-make -f Makefile.mingw all
```

Then copy library libximc.dll to current directory and launch testapp.exe.

#### 3.1.3 C++ Builder

First of all you should create C++ Builder-style import library. Visual C++ library is not compatible with BCB. Invoke:

```
$ implib libximc.lib libximc.def
```

Then compile test application:

```
$ bcc32 -I..\..\ximc\win32 -L..\..\ximc\win32 -DWIN32 -DNDEBUG -DWINDOWS  
testapp.c libximc.lib
```

### 3.1.4 XCode

Test app should be built with XCode project testapp.xcodeproj. Library is a Mac OS X framework, and at example application it's bundled inside testapp.app

Then launch application testapp.app and check activity output in Console.app.

### 3.1.5 GCC

Make sure that libximc (rpm, deb, freebsd package or tarball) is installed at your system. Installation of package should be performed with a package manager of operating system. On OS X plain dylib library and a framework is provided.

Note that user should belong to system group which allows access to a serial port (dip or serial, for example).

Test application can be built with the installed library with the following script:

```
$ make
```

In case of cross-compilation (target architecture differs from the current system architecture) feed -m64 or -m32 flag to compiler. On OS X it's needed to use -arch flag instead to build an universal binary. Please consult a compiler documentation.

Then launch the application as:

```
$ make run
```

Note: make run on OS X copies a library to the current directory. If you want to use library from the custom directory please be sure to specify LD\_LIBRARY\_PATH or DYLD\_LIBRARY\_PATH to the directory with the library.

## 3.2 .NET

Wrapper assembly for libximc.dll is wrappers/csharp/ximcnet.dll. It is provided with two different architectures and depends on .NET 2.0.

Test .NET applications for Visual Studio 2008 is located at testcs (for C#) and testvbnet (for VB.NET) respectively. Open solutions, build and run.

## 3.3 Delphi

Wrapper for libximc.dll is a unit wrappers/delphi/ximc.pas

Console test application for is located at testdelphi. Tested with Delphi 6 and only 32-bit version.

Just compile, place DLL near the executable and run program.

## 3.4 MATLAB

Sample MATLAB program testximc.m is provided at the directory examples/testmatlab. Fix first lines with the actual location of the XIMC library and launch M-file as:

```
$ testximc
```

## Chapter 4

# Data Structure Documentation

### 4.1 accessories\_settings\_t Struct Reference

Additional accessories information.

#### Data Fields

- char [MagneticBrakeInfo](#) [25]  
*The manufacturer and the part number of magnetic brake, the maximum string length is 24 characters.*
- float [MBRatedVoltage](#)  
*Rated voltage for controlling the magnetic brake (B).*
- float [MBRatedCurrent](#)  
*Rated current for controlling the magnetic brake (A).*
- float [MBTorque](#)  
*Retention moment (mN m).*
- unsigned int [MBSettings](#)  
*Magnetic brake settings flags.*
- char [TemperatureSensorInfo](#) [25]  
*The manufacturer and the part number of the temperature sensor, the maximum string length: 24 characters.*
- float [TSMIn](#)  
*The minimum measured temperature (degrees Celsius) Data type: float.*
- float [TSMaX](#)  
*The maximum measured temperature (degrees Celsius) Data type: float.*
- float [TSGrad](#)  
*The temperature gradient (V/degrees Celsius).*
- unsigned int [TSSettings](#)  
*Temperature sensor settings flags.*
- unsigned int [LimitSwitchesSettings](#)  
*Temperature sensor settings flags.*

#### 4.1.1 Detailed Description

Additional accessories information.

See also

[set\\_accessories\\_settings](#)  
[get\\_accessories\\_settings](#)  
[get\\_accessories\\_settings](#), [set\\_accessories\\_settings](#)

### 4.1.2 Field Documentation

#### 4.1.2.1 float MBRatedCurrent

Rated current for controlling the magnetic brake (A).

Data type: float.

#### 4.1.2.2 float MBRatedVoltage

Rated voltage for controlling the magnetic brake (B).

Data type: float.

#### 4.1.2.3 float MBTorque

Retention moment (mN m).

Data type: float.

#### 4.1.2.4 float TSGrad

The temperature gradient (V/degrees Celsius).

Data type: float.

## 4.2 add\_sync\_in\_action\_calb\_t Struct Reference

### Data Fields

- float [Position](#)  
*Desired position or shift.*
- float [Speed](#)  
*Target speed.*

## 4.3 add\_sync\_in\_action\_t Struct Reference

This command adds one element of the FIFO commands.

### Data Fields

- int [Position](#)  
*Desired position or shift (whole steps)*
- int [uPosition](#)  
*The fractional part of a position or shift in microsteps (-255 .*
- unsigned int [Speed](#)  
*Target speed(for stepper motor: steps / c, for DC: rpm).*
- unsigned int [uSpeed](#)  
*Target speed in microsteps/s.*

### 4.3.1 Detailed Description

This command adds one element of the FIFO commands.

See also

[set\\_add\\_sync\\_in\\_action](#)

### 4.3.2 Field Documentation

#### 4.3.2.1 unsigned int Speed

Target speed(for stepper motor: steps / c, for DC: rpm).

Range: 0..1000000.

#### 4.3.2.2 int uPosition

The fractional part of a position or shift in microsteps (-255 . . 255)(is only used with stepper motor)

#### 4.3.2.3 unsigned int uSpeed

Target speed in microsteps/s.

Using with stepper motor only. Range: 0..255.

## 4.4 analog\_data\_t Struct Reference

Analog data.

### Data Fields

- unsigned int [A1Voltage\\_ADC](#)  
"Voltage on pin 1 winding A" raw data from ADC.
- unsigned int [A2Voltage\\_ADC](#)  
"Voltage on pin 2 winding A" raw data from ADC.
- unsigned int [B1Voltage\\_ADC](#)  
"Voltage on pin 1 winding B" raw data from ADC.
- unsigned int [B2Voltage\\_ADC](#)  
"Voltage on pin 2 winding B" raw data from ADC.
- unsigned int [SupVoltage\\_ADC](#)  
"Voltage on the top of MOSFET full bridge" raw data from ADC.
- unsigned int [ACurrent\\_ADC](#)  
"Winding A current" raw data from ADC.
- unsigned int [BCurrent\\_ADC](#)  
"Winding B current" raw data from ADC.
- unsigned int [FullCurrent\\_ADC](#)  
"Full current" raw data from ADC.
- unsigned int [Temp\\_ADC](#)  
Voltage from temperature sensor, raw data from ADC.

- unsigned int [Joy\\_ADC](#)  
*Joystick raw data from ADC.*
- unsigned int [Pot\\_ADC](#)  
*Voltage on "Potentiometer", raw data from ADC.*
- unsigned int [L5\\_ADC](#)  
*USB supply voltage after the current sense resistor, from ADC.*
- unsigned int [H5\\_ADC](#)  
*Power supply USB from ADC.*
- int [A1Voltage](#)  
*"Voltage on pin 1 winding A" calibrated data.*
- int [A2Voltage](#)  
*"Voltage on pin 2 winding A" calibrated data.*
- int [B1Voltage](#)  
*"Voltage on pin 1 winding B" calibrated data.*
- int [B2Voltage](#)  
*"Voltage on pin 2 winding B" calibrated data.*
- int [SupVoltage](#)  
*"Voltage on the top of MOSFET full bridge" calibrated data.*
- int [ACurrent](#)  
*"Winding A current" calibrated data.*
- int [BCurrent](#)  
*"Winding B current" calibrated data.*
- int [FullCurrent](#)  
*"Full current" calibrated data.*
- int [Temp](#)  
*Temperature, calibrated data.*
- int [Joy](#)  
*Joystick, calibrated data.*
- int [Pot](#)  
*Potentiometer, calibrated data.*
- int [L5](#)  
*USB supply voltage after the current sense resistor.*
- int [H5](#)  
*Power supply USB.*
- unsigned int **deprecated**
- int [R](#)  
*Motor winding resistance in mOhms(is only used with stepper motor).*
- int [L](#)  
*Motor winding pseudo inductance in uHn(is only used with stepper motor).*

#### 4.4.1 Detailed Description

Analog data.

This structure contains raw analog data from ADC embedded on board. These data used for device testing and deep recalibration by manufacturer only.

See also

[get\\_analog\\_data](#)  
[get\\_analog\\_data](#)

## 4.5 brake\_settings\_t Struct Reference

Brake settings.

### Data Fields

- unsigned int [t1](#)  
*Time in ms between turn on motor power and turn off brake.*
- unsigned int [t2](#)  
*Time in ms between turn off brake and moving readiness.*
- unsigned int [t3](#)  
*Time in ms between motor stop and turn on brake.*
- unsigned int [t4](#)  
*Time in ms between turn on brake and turn off motor power.*
- unsigned int [BrakeFlags](#)  
*Brake settings flags.*

### 4.5.1 Detailed Description

Brake settings.

This structure contains parameters of brake control.

See also

[set\\_brake\\_settings](#)  
[get\\_brake\\_settings](#)  
[get\\_brake\\_settings](#), [set\\_brake\\_settings](#)

### 4.5.2 Field Documentation

#### 4.5.2.1 unsigned int t1

Time in ms between turn on motor power and turn off brake.

Range: 0..65535.

#### 4.5.2.2 unsigned int t2

Time in ms between turn off brake and moving readiness.

All moving commands will execute after this interval. Range: 0..65535.

#### 4.5.2.3 unsigned int t3

Time in ms between motor stop and turn on brake.

Range: 0..65535.

#### 4.5.2.4 unsigned int t4

Time in ms between turn on brake and turn off motor power.

Range: 0..65535.

## 4.6 calibration\_t Struct Reference

Calibration companion structure.

### Data Fields

- double [A](#)  
*Multiplier.*
- unsigned int [MicrostepMode](#)  
*Microstep mode.*

### 4.6.1 Detailed Description

Calibration companion structure.

## 4.7 chart\_data\_t Struct Reference

Additional device state.

### Data Fields

- int [WindingVoltageA](#)  
*In the case step motor, the voltage across the winding A; in the case of a brushless, the voltage on the first coil, in the case of the only DC.*
- int [WindingVoltageB](#)  
*In the case step motor, the voltage across the winding B; in case of a brushless, the voltage on the second winding, and in the case of DC is not used.*
- int [WindingVoltageC](#)  
*In the case of a brushless, the voltage on the third winding, in the case step motor and DC is not used.*
- int [WindingCurrentA](#)  
*In the case step motor, the current in the coil A; brushless if the current in the first coil, and in the case of a single DC.*
- int [WindingCurrentB](#)  
*In the case step motor, the current in the coil B; brushless if the current in the second coil, and in the case of DC is not used.*
- int [WindingCurrentC](#)  
*In the case of a brushless, the current in the third winding, in the case step motor and DC is not used.*
- unsigned int [Pot](#)  
*Potentiometer in ten-thousandths of [0, 10000].*
- unsigned int [Joy](#)  
*The joystick to the ten-thousandths [0, 10000].*
- int [DutyCycle](#)  
*Duty cycle of PWM.*

### 4.7.1 Detailed Description

Additional device state.

This structure contains additional values such as winding's voltages, currents and temperature.

See also

[get\\_chart\\_data](#)  
[get\\_chart\\_data](#)



## 4.8 control\_settings\_calb\_t Struct Reference

### Data Fields

- float [MaxSpeed](#) [10]  
*Array of speeds using with joystick and button control.*
- unsigned int [Timeout](#) [9]  
*timeout[i] is time in ms, after that max\_speed[i+1] is applying.*
- unsigned int [MaxClickTime](#)  
*Maximum click time.*
- unsigned int [Flags](#)  
*Control flags.*
- float [DeltaPosition](#)  
*Shift (delta) of position.*

### 4.8.1 Field Documentation

#### 4.8.1.1 unsigned int MaxClickTime

Maximum click time.

Prior to the expiration of this time the first speed isn't enabled.

#### 4.8.1.2 unsigned int Timeout[9]

timeout[i] is time in ms, after that max\_speed[i+1] is applying.

It is using with buttons control only. Range: 0..65535.

## 4.9 control\_settings\_t Struct Reference

Control settings.

### Data Fields

- unsigned int [MaxSpeed](#) [10]  
*Array of speeds (full step) using with joystick and button control.*
- unsigned int [uMaxSpeed](#) [10]  
*Array of speeds (1/256 microstep) using with joystick and button control.*
- unsigned int [Timeout](#) [9]  
*timeout[i] is time in ms, after that max\_speed[i+1] is applying.*
- unsigned int [MaxClickTime](#)  
*Maximum click time.*
- unsigned int [Flags](#)  
*Control flags.*
- int [DeltaPosition](#)  
*Shift (delta) of position.*
- int [uDeltaPosition](#)  
*Fractional part of the shift in micro steps (-255 .*

### 4.9.1 Detailed Description

Control settings.

This structure contains control parameters. When choosing CTL\_MODE=1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i=0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL\_MODE=2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout[i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i+1] to acceleration, as usual. The figure above shows the sensitivity of the joystick feature on its position.

See also

[set\\_control\\_settings](#)  
[get\\_control\\_settings](#)  
[get\\_control\\_settings, set\\_control\\_settings](#)

### 4.9.2 Field Documentation

#### 4.9.2.1 unsigned int MaxClickTime

Maximum click time.

Prior to the expiration of this time the first speed isn't enabled.

#### 4.9.2.2 unsigned int MaxSpeed[10]

Array of speeds (full step) using with joystick and button control.

Range: 0..1000000.

#### 4.9.2.3 unsigned int Timeout[9]

timeout[i] is time in ms, after that max.speed[i+1] is applying.

It is using with buttons control only. Range: 0..65535.

#### 4.9.2.4 int uDeltaPosition

Fractional part of the shift in micro steps (-255 .

. 255) is only used with stepper motor

#### 4.9.2.5 unsigned int uMaxSpeed[10]

Array of speeds (1/256 microstep) using with joystick and button control.

Range: 0..255.

## 4.10 controller\_name\_t Struct Reference

Controller user name and flags of setting.

## Data Fields

- char [ControllerName](#) [17]  
*User controller name.*
- unsigned int [CtrlFlags](#)  
*Flags of internal controller settings.*

### 4.10.1 Detailed Description

Controller user name and flags of setting.

See also

[get\\_controller\\_name](#), [set\\_controller\\_name](#)

### 4.10.2 Field Documentation

#### 4.10.2.1 char ControllerName[17]

User controller name.

Can be set by user for his/her convenience. Max string length: 16 chars.

## 4.11 ctp\_settings\_t Struct Reference

Control position settings(is only used with stepper motor).

## Data Fields

- unsigned int [CTPMinError](#)  
*Minimum contrast steps from step motor encoder position, wich set STATE\_CTP\_ERROR flag.*
- unsigned int [CTPFlags](#)  
*Position control flags.*

### 4.11.1 Detailed Description

Control position settings(is only used with stepper motor).

When controlling the step motor with encoder (CTP\_BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP\_ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is greater CTPMinError, a flag STATE\_CTP\_ERROR and set ALARM state. When controlling the step motor with speed sensor (CTP\_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE\_CTP\_ERROR and set ALARM state.

See also

[set\\_ctp\\_settings](#)  
[get\\_ctp\\_settings](#)  
[get\\_ctp\\_settings](#), [set\\_ctp\\_settings](#)

### 4.11.2 Field Documentation

#### 4.11.2.1 unsigned int CTPMinError

Minimum contrast steps from step motor encoder position, wich set STATE.CTP\_ERROR flag.

Measured in steps step motor. Range: 0..255.

## 4.12 debug\_read\_t Struct Reference

Debug data.

### Data Fields

- unsigned int [DebugData](#) [128]  
*Arbitrary debug data.*

### 4.12.1 Detailed Description

Debug data.

These data are used for device debugging by manufacturer only.

See also

[get\\_debug\\_read](#)

## 4.13 device\_information\_t Struct Reference

Read command controller information.

### Data Fields

- char [Manufacturer](#) [5]  
*Manufacturer.*
- char [ManufacturerId](#) [3]  
*Manufacturer id.*
- char [ProductDescription](#) [9]  
*Product description.*

### 4.13.1 Detailed Description

Read command controller information.

The controller responds to this command in any state. Manufacturer field for all XI \*\* devices should contain the string "XIMC" (validation is performed on it) The remaining fields contain information about the device.

See also

[get\\_device\\_information](#)  
[get\\_device\\_information\\_impl](#)

## 4.14 edges\_settings\_calb\_t Struct Reference

### Data Fields

- unsigned int [BorderFlags](#)  
*Border flags.*
- unsigned int [EnderFlags](#)  
*Limit switches flags.*
- float [LeftBorder](#)  
*Left border position, used if BORDER.IS.ENCODER flag is set.*
- float [RightBorder](#)  
*Right border position, used if BORDER.IS.ENCODER flag is set.*

## 4.15 edges\_settings\_t Struct Reference

Edges settings.

### Data Fields

- unsigned int [BorderFlags](#)  
*Border flags.*
- unsigned int [EnderFlags](#)  
*Limit switches flags.*
- int [LeftBorder](#)  
*Left border position, used if BORDER.IS.ENCODER flag is set.*
- int [uLeftBorder](#)  
*Left border position in 1/256 microsteps(used with stepper motor only).*
- int [RightBorder](#)  
*Right border position, used if BORDER.IS.ENCODER flag is set.*
- int [uRightBorder](#)  
*Right border position in 1/256 microsteps.*

### 4.15.1 Detailed Description

Edges settings.

This structure contains border and limit switches settings. Please load new engine settings when you change positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See also

[set\\_edges\\_settings](#)  
[get\\_edges\\_settings](#)  
[get\\_edges\\_settings](#), [set\\_edges\\_settings](#)

### 4.15.2 Field Documentation

#### 4.15.2.1 int LeftBorder

Left border position, used if BORDER.IS.ENCODER flag is set.

Range: -2147483647..2147483647.

## 4.15.2.2 int RightBorder

Right border position, used if BORDER\_IS\_ENCODER flag is set.

Range: -2147483647..2147483647.

## 4.15.2.3 int uLeftBorder

Left border position in 1/256 microsteps(used with stepper motor only).

Range: -255..255.

## 4.15.2.4 int uRightBorder

Right border position in 1/256 microsteps.

Range: -255..255(used with stepper motor only).

## 4.16 encoder\_information\_t Struct Reference

Encoder information.

### Data Fields

- char [Manufacturer](#) [17]  
*Manufacturer.*
- char [PartNumber](#) [25]  
*Series and PartNumber.*

### 4.16.1 Detailed Description

Encoder information.

See also

[set\\_encoder\\_information](#)  
[get\\_encoder\\_information](#)  
[get\\_encoder\\_information](#), [set\\_encoder\\_information](#)

### 4.16.2 Field Documentation

## 4.16.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

## 4.16.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

## 4.17 encoder\_settings\_t Struct Reference

Encoder settings.

### Data Fields

- float [MaxOperatingFrequency](#)  
*Max operation frequency (kHz).*
- float [SupplyVoltageMin](#)  
*Minimum supply voltage (V).*
- float [SupplyVoltageMax](#)  
*Maximum supply voltage (V).*
- float [MaxCurrentConsumption](#)  
*Max current consumption (mA).*
- unsigned int [PPR](#)  
*The number of counts per revolution.*
- unsigned int [EncoderSettings](#)  
*Encoder settings flags.*

### 4.17.1 Detailed Description

Encoder settings.

See also

[set\\_encoder\\_settings](#)  
[get\\_encoder\\_settings](#)  
[get\\_encoder\\_settings](#), [set\\_encoder\\_settings](#)

### 4.17.2 Field Documentation

#### 4.17.2.1 float MaxCurrentConsumption

Max current consumption (mA).

Data type: float.

#### 4.17.2.2 float MaxOperatingFrequency

Max operation frequency (kHz).

Data type: float.

#### 4.17.2.3 float SupplyVoltageMax

Maximum supply voltage (V).

Data type: float.

#### 4.17.2.4 float SupplyVoltageMin

Minimum supply voltage (V).

Data type: float.

## 4.18 engine\_settings\_calb\_t Struct Reference

### Data Fields

- unsigned int [NomVoltage](#)  
*Rated voltage.*
- unsigned int [NomCurrent](#)  
*Rated current.*
- float [NomSpeed](#)  
*Nominal speed.*
- unsigned int [EngineFlags](#)  
*Flags of engine settings.*
- float [Antiplay](#)  
*Number of pulses or steps for backlash (play) compensation procedure.*
- unsigned int [MicrostepMode](#)  
*Flags of microstep mode.*
- unsigned int [StepsPerRev](#)  
*Number of full steps per revolution(Used with stepper motor only).*

### 4.18.1 Field Documentation

#### 4.18.1.1 float Antiplay

Number of pulses or steps for backlash (play) compensation procedure.

Used if ENGINE\_ANTIPLAY flag is set.

#### 4.18.1.2 unsigned int NomCurrent

Rated current.

Controller will keep current consumed by motor below this value if ENGINE\_LIMIT\_CURR flag is set. Range: 1..65535

#### 4.18.1.3 float NomSpeed

Nominal speed.

Controller will keep motor speed below this value if ENGINE\_LIMIT\_RPM flag is set.

#### 4.18.1.4 unsigned int NomVoltage

Rated voltage.

Controller will keep the voltage drop on motor below this value if ENGINE\_LIMIT\_VOLT flag is set(Used with DC only). Range: 1..65535

#### 4.18.1.5 unsigned int StepsPerRev

Number of full steps per revolution(Used with stepper motor only).

Range: 1..65535.



## 4.19 engine\_settings\_t Struct Reference

Engine settings.

### Data Fields

- unsigned int [NomVoltage](#)  
*Rated voltage.*
- unsigned int [NomCurrent](#)  
*Rated current.*
- unsigned int [NomSpeed](#)  
*Nominal speed (in whole steps / s or rpm for DC and stepper motor as a master encoder).*
- unsigned int [uNomSpeed](#)  
*The fractional part of a nominal speed in microsteps (is only used with stepper motor).*
- unsigned int [EngineFlags](#)  
*Flags of engine settings.*
- int [Antiplay](#)  
*Number of pulses or steps for backlash (play) compensation procedure.*
- unsigned int [MicrostepMode](#)  
*Flags of microstep mode.*
- unsigned int [StepsPerRev](#)  
*Number of full steps per revolution(Used with stepper motor only).*

### 4.19.1 Detailed Description

Engine settings.

This structure contains useful motor settings. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics. All boards are supplied with standart set of engine setting on controller's flash memory. Please load new engine settings when you change motor, encoder, positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See also

[set\\_engine\\_settings](#)  
[get\\_engine\\_settings](#)  
[get\\_engine\\_settings, set\\_engine\\_settings](#)

### 4.19.2 Field Documentation

#### 4.19.2.1 int Antiplay

Number of pulses or steps for backlash (play) compensation procedure.

Used if ENGINE\_ANTIPLAY flag is set. Range: -32768..32767

#### 4.19.2.2 unsigned int NomCurrent

Rated current.

Controller will keep current consumed by motor below this value if ENGINE\_LIMIT\_CURR flag is set. Range: 1..65535

## 4.19.2.3 unsigned int NomSpeed

Nominal speed (in whole steps / s or rpm for DC and stepper motor as a master encoder).

Controller will keep motor shaft RPM below this value if ENGINE\_LIMIT\_RPM flag is set. Range: 1..1000000.

## 4.19.2.4 unsigned int NomVoltage

Rated voltage.

Controller will keep the voltage drop on motor below this value if ENGINE\_LIMIT\_VOLT flag is set(Used with DC only). Range: 1..65535

## 4.19.2.5 unsigned int StepsPerRev

Number of full steps per revolution(Used with stepper motor only).

Range: 1..65535.

## 4.19.2.6 unsigned int uNomSpeed

The fractional part of a nominal speed in microsteps (is only used with stepper motor).

Range: 0..255

## 4.20 entype\_settings\_t Struct Reference

Engine type and driver type settings.

## Data Fields

- unsigned int [EngineType](#)  
*Flags of engine type.*
- unsigned int [DriverType](#)  
*Flags of driver type.*

## 4.20.1 Detailed Description

Engine type and driver type settings.

## Parameters

|                   |                         |
|-------------------|-------------------------|
| <i>id</i>         | an identifier of device |
| <i>EngineType</i> | engine type             |
| <i>DriverType</i> | driver type             |

See also

[get\\_entype\\_settings](#), [set\\_entype\\_settings](#)

## 4.21 extio\_settings\_t Struct Reference

EXTIO settings.

## Data Fields

- unsigned int [EXTIOSetupFlags](#)  
*External IO setup flags.*
- unsigned int [EXTIOModeFlags](#)  
*External IO mode flags.*

### 4.21.1 Detailed Description

EXTIO settings.

This structure contains all EXTIO settings. By default input event are signalled through rising front and output states are signalled by high logic state.

See also

[get\\_extio\\_settings](#)  
[set\\_extio\\_settings](#)  
[get\\_extio\\_settings](#), [set\\_extio\\_settings](#)

## 4.22 feedback\_settings\_t Struct Reference

Feedback settings.

## Data Fields

- unsigned int [IPS](#)  
*The number of measured counts per revolution encoder.*
- unsigned int [FeedbackType](#)  
*Feedback type.*
- unsigned int [FeedbackFlags](#)  
*Describes feedback flags.*
- unsigned int [HallSPR](#)  
*The number of hall steps per revolution.*
- int [HallShift](#)  
*Phase shift between output signal on BLDC engine and hall sensor input(0 - when only active the Hall sensor, the output state is a positive voltage on the winding A and a negative voltage on the winding B).*

### 4.22.1 Detailed Description

Feedback settings.

This structure contains feedback settings.

See also

[get\\_feedback\\_settings](#), [set\\_feedback\\_settings](#)

## 4.23 gear\_information\_t Struct Reference

Gear information.

## Data Fields

- char [Manufacturer](#) [17]  
*Manufacturer.*
- char [PartNumber](#) [25]  
*Series and PartNumber.*

### 4.23.1 Detailed Description

Gear information.

See also

[set\\_gear\\_information](#)  
[get\\_gear\\_information](#)  
[get\\_gear\\_information](#), [set\\_gear\\_information](#)

### 4.23.2 Field Documentation

#### 4.23.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

#### 4.23.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

## 4.24 gear\_settings\_t Struct Reference

Gear settings.

## Data Fields

- float [ReductionIn](#)  
*Input reduction coefficient.*
- float [ReductionOut](#)  
*Output reduction coefficient.*
- float [RatedInputTorque](#)  
*Max continuous torque (N m).*
- float [RatedInputSpeed](#)  
*Max speed on the input shaft (rpm).*
- float [MaxOutputBacklash](#)  
*Output backlash of the reduction gear(degree).*
- float [InputInertia](#)  
*Equivalent input gear inertia (g cm2).*
- float [Efficiency](#)  
*Reduction gear efficiency (%).*

#### 4.24.1 Detailed Description

Gear settings.

See also

[set\\_gear\\_settings](#)  
[get\\_gear\\_settings](#)  
[get\\_gear\\_settings](#), [set\\_gear\\_settings](#)

#### 4.24.2 Field Documentation

##### 4.24.2.1 float Efficiency

Reduction gear efficiency (%).

Data type: float.

##### 4.24.2.2 float InputInertia

Equivalent input gear inertia (g cm<sup>2</sup>).

Data type: float.

##### 4.24.2.3 float MaxOutputBacklash

Output backlash of the reduction gear(degree).

Data type: float.

##### 4.24.2.4 float RatedInputSpeed

Max speed on the input shaft (rpm).

Data type: float.

##### 4.24.2.5 float RatedInputTorque

Max continuous torque (N m).

Data type: float.

##### 4.24.2.6 float ReductionIn

Input reduction coefficient.

(Output = (ReductionOut / ReductionIn) \* Input) Data type: float.

##### 4.24.2.7 float ReductionOut

Output reduction coefficient.

(Output = (ReductionOut / ReductionIn) \* Input) Data type: float.

## 4.25 `get_position_calb_t` Struct Reference

### Data Fields

- float [Position](#)  
*The position in the engine.*
- long\_t [EncPosition](#)  
*Encoder position.*

## 4.26 `get_position_t` Struct Reference

Position information.

### Data Fields

- int [Position](#)  
*The position of the whole steps in the engine.*
- int [uPosition](#)  
*Microstep position is only used with stepper motors.*
- long\_t [EncPosition](#)  
*Encoder position.*

### 4.26.1 Detailed Description

Position information.

Useful structure that contains position value in steps and micro for stepper motor and encoder steps of all engines.

See also

[get\\_position](#)

## 4.27 `hallsensor_information_t` Struct Reference

Hall sensor information.

### Data Fields

- char [Manufacturer](#) [17]  
*Manufacturer.*
- char [PartNumber](#) [25]  
*Series and PartNumber.*

### 4.27.1 Detailed Description

Hall sensor information.

See also

[set\\_hallsensor\\_information](#)  
[get\\_hallsensor\\_information](#)  
[get\\_hallsensor\\_information](#), [set\\_hallsensor\\_information](#)

### 4.27.2 Field Documentation

#### 4.27.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

#### 4.27.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

## 4.28 hallsensor\_settings\_t Struct Reference

Hall sensor settings.

### Data Fields

- float [MaxOperatingFrequency](#)  
*Max operation frequency (kHz).*
- float [SupplyVoltageMin](#)  
*Minimum supply voltage (V).*
- float [SupplyVoltageMax](#)  
*Maximum supply voltage (V).*
- float [MaxCurrentConsumption](#)  
*Max current consumption (mA).*
- unsigned int [PPR](#)  
*The number of counts per revolution.*

### 4.28.1 Detailed Description

Hall sensor settings.

See also

[set\\_hallsensor\\_settings](#)  
[get\\_hallsensor\\_settings](#)  
[get\\_hallsensor\\_settings](#), [set\\_hallsensor\\_settings](#)

### 4.28.2 Field Documentation

#### 4.28.2.1 float MaxCurrentConsumption

Max current consumption (mA).

Data type: float.

#### 4.28.2.2 float MaxOperatingFrequency

Max operation frequency (kHz).

Data type: float.

## 4.28.2.3 float SupplyVoltageMax

Maximum supply voltage (V).

Data type: float.

## 4.28.2.4 float SupplyVoltageMin

Minimum supply voltage (V).

Data type: float.

## 4.29 home\_settings\_calb\_t Struct Reference

### Data Fields

- float [FastHome](#)  
*Speed used for first motion.*
- float [SlowHome](#)  
*Speed used for second motion.*
- float [HomeDelta](#)  
*Distance from break point.*
- unsigned int [HomeFlags](#)  
*Home settings flags.*

## 4.30 home\_settings\_t Struct Reference

Position calibration settings.

### Data Fields

- unsigned int [FastHome](#)  
*Speed used for first motion.*
- unsigned int [uFastHome](#)  
*Part of the speed for first motion, microsteps.*
- unsigned int [SlowHome](#)  
*Speed used for second motion.*
- unsigned int [uSlowHome](#)  
*Part of the speed for second motion, microsteps.*
- int [HomeDelta](#)  
*Distance from break point.*
- int [uHomeDelta](#)  
*Part of the delta distance, microsteps.*
- unsigned int [HomeFlags](#)  
*Home settings flags.*



#### 4.30.1 Detailed Description

Position calibration settings.

This structure contains settings used in position calibrating. It specify behaviour of calibrating position.

See also

[get\\_home\\_settings](#)  
[set\\_home\\_settings](#)  
[command\\_home](#)  
[get\\_home\\_settings](#), [set\\_home\\_settings](#)

#### 4.30.2 Field Documentation

##### 4.30.2.1 unsigned int FastHome

Speed used for first motion.

Range: 0..1000000.

##### 4.30.2.2 int HomeDelta

Distance from break point.

Range: -2147483647..2147483647.

##### 4.30.2.3 unsigned int SlowHome

Speed used for second motion.

Range: 0..1000000.

##### 4.30.2.4 unsigned int uFastHome

Part of the speed for first motion, microsteps.

Range: 0..255.

##### 4.30.2.5 int uHomeDelta

Part of the delta distance, microsteps.

Range: -255..255.

##### 4.30.2.6 unsigned int uSlowHome

Part of the speed for second motion, microsteps.

Range: 0..255.

### 4.31 joystick\_settings\_t Struct Reference

Joystick settings.

## Data Fields

- unsigned int [JoyLowEnd](#)  
*Joystick lower end position.*
- unsigned int [JoyCenter](#)  
*Joystick center position.*
- unsigned int [JoyHighEnd](#)  
*Joystick higher end position.*
- unsigned int [ExpFactor](#)  
*Exponential nonlinearity factor.*
- unsigned int [DeadZone](#)  
*Joystick dead zone.*
- unsigned int [JoyFlags](#)  
*Joystick flags.*

## 4.31.1 Detailed Description

Joystick settings.

This structure contains joystick parameters. If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy.

See also

[set\\_joystick\\_settings](#)  
[get\\_joystick\\_settings](#)  
[get\\_joystick\\_settings](#), [set\\_joystick\\_settings](#)

## 4.32 motor\_information\_t Struct Reference

motor information.

## Data Fields

- char [Manufacturer](#) [17]  
*Manufacturer.*
- char [PartNumber](#) [25]  
*Series and PartNumber.*

## 4.32.1 Detailed Description

motor information.

See also

[set\\_motor\\_information](#)  
[get\\_motor\\_information](#)  
[get\\_motor\\_information](#), [set\\_motor\\_information](#)

## 4.32.2 Field Documentation

## 4.32.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

## 4.32.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

## 4.33 motor\_settings\_t Struct Reference

motor settings.

## Data Fields

- unsigned int [MotorType](#)  
*Motor Type flags.*
- unsigned int [ReservedField](#)  
*Reserved.*
- unsigned int [Poles](#)  
*Number of pole pairs for DC or BLDC motors or number of steps per rotation for stepper motor.*
- unsigned int [Phases](#)  
*Number of phases for BLDC motors.*
- float [NominalVoltage](#)  
*Nominal voltage on winding (V).*
- float [NominalCurrent](#)  
*Maximum direct current in winding for DC and BLDC engines, nominal current in windings for stepper motor (A).*
- float [NominalSpeed](#)  
*Nominal speed(rpm).*
- float [NominalTorque](#)  
*Nominal torque(mN m).*
- float [NominalPower](#)  
*Nominal power(W).*
- float [WindingResistance](#)  
*Resistance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(Ohm).*
- float [WindingInductance](#)  
*Inductance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(mH).*
- float [RotorInertia](#)  
*Rotor inertia(g cm<sup>2</sup>).*
- float [StallTorque](#)  
*Torque hold position for a stepper motor or torque at a motionless rotor for other types of engines (mN m).*
- float [DetentTorque](#)  
*Holding torque position with un-powered coils (mN m).*
- float [TorqueConstant](#)

*Torque constant, which determines the aspect ratio of maximum moment of force from the rotor current flowing in the coil (mN m / A).*

- float [SpeedConstant](#)

*Velocity constant, which determines the value or amplitude of the induced voltage on the motion of DC or BLDC motor (rpm / V) or stepper motor (steps/s / V).*

- float [SpeedTorqueGradient](#)

*Speed torque gradient (rpm / mN m).*

- float [MechanicalTimeConstant](#)

*Mechanical time constant (ms).*

- float [MaxSpeed](#)

*The maximum speed for stepper motors (steps/s) or DC and BLDC motors (rpm).*

- float [MaxCurrent](#)

*The maximum current in the winding (A).*

- float [MaxCurrentTime](#)

*Safe duration of overcurrent in the winding (ms).*

- float [NoLoadCurrent](#)

*The current consumption in idle mode (A).*

- float [NoLoadSpeed](#)

*Idle speed (rpm).*

#### 4.33.1 Detailed Description

motor settings.

See also

[set\\_motor\\_settings](#)

[get\\_motor\\_settings](#)

[get\\_motor\\_settings](#), [set\\_motor\\_settings](#)

#### 4.33.2 Field Documentation

##### 4.33.2.1 float DetentTorque

Holding torque position with un-powered coils (mN m).

Data type: float.

##### 4.33.2.2 float MaxCurrent

The maximum current in the winding (A).

Data type: float.

##### 4.33.2.3 float MaxCurrentTime

Safe duration of overcurrent in the winding (ms).

Data type: float.

##### 4.33.2.4 float MaxSpeed

The maximum speed for stepper motors (steps/s) or DC and BLDC motors (rpm).

Data type: float.

## 4.33.2.5 float MechanicalTimeConstant

Mechanical time constant (ms).

Data type: float.

## 4.33.2.6 float NoLoadCurrent

The current consumption in idle mode (A).

Used for DC and BLDC motors. Data type: float.

## 4.33.2.7 float NoLoadSpeed

Idle speed (rpm).

Used for DC and BLDC motors. Data type: float.

## 4.33.2.8 float NominalCurrent

Maximum direct current in winding for DC and BLDC engines, nominal current in windings for stepper motor (A).

Data type: float.

## 4.33.2.9 float NominalPower

Nominal power(W).

Used for DC and BLDC engine. Data type: float.

## 4.33.2.10 float NominalSpeed

Nominal speed(rpm).

Used for DC and BLDC engine. Data type: float.

## 4.33.2.11 float NominalTorque

Nominal torque(mN m).

Used for DC and BLDC engine. Data type: float.

## 4.33.2.12 float NominalVoltage

Nominal voltage on winding (B).

Data type: float

## 4.33.2.13 float RotorInertia

Rotor inertia(g cm<sup>2</sup>).

Data type: float.

## 4.33.2.14 float SpeedConstant

Velocity constant, which determines the value or amplitude of the induced voltage on the motion of DC or BLDC motor (rpm / V) or stepper motor (steps/s / V).

Data type: float.

## 4.33.2.15 float SpeedTorqueGradient

Speed torque gradient (rpm / mN m).

Data type: float.

## 4.33.2.16 float StallTorque

Torque hold position for a stepper motor or torque at a motionless rotor for other types of engines (mN m).

Data type: float.

## 4.33.2.17 float TorqueConstant

Torque constant, which determines the aspect ratio of maximum moment of force from the rotor current flowing in the coil (mN m / A).

Used mainly for DC motors. Data type: float.

## 4.33.2.18 float WindingInductance

Inductance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(mH).

Data type: float.

## 4.33.2.19 float WindingResistance

Resistance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(Ohm).

Data type: float.

## 4.34 move\_settings\_calb\_t Struct Reference

## Data Fields

- float [Speed](#)  
*Target speed.*
- float [Accel](#)  
*Motor shaft acceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).*
- float [Decel](#)  
*Motor shaft deceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).*
- float [AntiplaySpeed](#)  
*Speed in antiplay mode.*

## 4.35 move\_settings\_t Struct Reference

Move settings.

### Data Fields

- unsigned int [Speed](#)  
*Target speed(for stepper motor: steps / c, for DC: rpm).*
- unsigned int [uSpeed](#)  
*Target speed in 1/256 microsteps/s.*
- unsigned int [Accel](#)  
*Motor shaft acceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).*
- unsigned int [Decel](#)  
*Motor shaft deceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).*
- unsigned int [AntiplaySpeed](#)  
*Speed in antiplay mode, full steps/s(stepper motor) or RPM(DC).*
- unsigned int [uAntiplaySpeed](#)  
*Speed in antiplay mode, 1/256 microsteps/s.*

### 4.35.1 Detailed Description

Move settings.

See also

[set\\_move\\_settings](#)  
[get\\_move\\_settings](#)  
[get\\_move\\_settings](#), [set\\_move\\_settings](#)

### 4.35.2 Field Documentation

#### 4.35.2.1 unsigned int Accel

Motor shaft acceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).

Range: 0..65535.

#### 4.35.2.2 unsigned int AntiplaySpeed

Speed in antiplay mode, full steps/s(stepper motor) or RPM(DC).

Range: 0..1000000.

#### 4.35.2.3 unsigned int Decel

Motor shaft deceleration, steps/s<sup>2</sup>(stepper motor) or RPM/s(DC).

Range: 0..65535.

#### 4.35.2.4 unsigned int Speed

Target speed(for stepper motor: steps / c, for DC: rpm).

Range: 0..1000000.

## 4.35.2.5 unsigned int uAntiplaySpeed

Speed in antiplay mode, 1/256 microsteps/s.

Used with stepper motor only. Range: 0..255.

## 4.35.2.6 unsigned int uSpeed

Target speed in 1/256 microsteps/s.

Using with stepper motor only. Range: 0..255.

## 4.36 pid\_settings\_t Struct Reference

PID settings.

### Data Fields

- unsigned int [KpU](#)  
*Proportional gain for voltage PID routine.*
- unsigned int [KiU](#)  
*Integral gain for voltage PID routine.*
- unsigned int [KdU](#)  
*Differential gain for voltage PID routine.*

### 4.36.1 Detailed Description

PID settings.

This structure contains factors for PID routine. Range: 0..65535. It specify behaviour of PID routine for voltage. These factors are slightly different for different positioners. All boards are supplied with standart set of PID setting on controller's flash memory. Please load new PID settings when you change positioner. Please note that wrong PID settings lead to device malfunction.

See also

[set\\_pid\\_settings](#)  
[get\\_pid\\_settings](#)  
[get\\_pid\\_settings](#), [set\\_pid\\_settings](#)

## 4.37 power\_settings\_t Struct Reference

Step motor power settings.

### Data Fields

- unsigned int [HoldCurrent](#)  
*Current in holding regime, percent of nominal.*
- unsigned int [CurrReductDelay](#)  
*Time in ms from going to STOP state to reducing current.*
- unsigned int [PowerOffDelay](#)  
*Time in s from going to STOP state to turning power off.*



- unsigned int [CurrentSetTime](#)  
*Time in ms to reach nominal current.*
- unsigned int [PowerFlags](#)  
*Flags of power settings of stepper motor.*

#### 4.37.1 Detailed Description

Step motor power settings.

See also

[set\\_move\\_settings](#)  
[get\\_move\\_settings](#)  
[get\\_power\\_settings](#), [set\\_power\\_settings](#)

#### 4.37.2 Field Documentation

##### 4.37.2.1 unsigned int `CurrentSetTime`

Time in ms to reach nominal current.

Range: 0..65535.

##### 4.37.2.2 unsigned int `CurrReductDelay`

Time in ms from going to STOP state to reducing current.

Range: 0..65535.

##### 4.37.2.3 unsigned int `HoldCurrent`

Current in holding regime, percent of nominal.

Range: 0..100.

##### 4.37.2.4 unsigned int `PowerOffDelay`

Time in s from going to STOP state to turning power off.

Range: 0..65535.

### 4.38 `secure_settings_t` Struct Reference

This structure contains raw analog data from ADC embedded on board.

#### Data Fields

- unsigned int [LowUpwrOff](#)  
*Lower voltage limit to turn off the motor, in mV.*
- unsigned int [CriticalIpwr](#)  
*Maximum motor current which triggers ALARM state, in mA.*
- unsigned int [CriticalUpwr](#)  
*Maximum motor voltage which triggers ALARM state, in mV.*

- unsigned int [CriticalT](#)  
*Maximum temperature, which triggers ALARM state, in tenths of degrees Celcius.*
- unsigned int [CriticalIusb](#)  
*Maximum USB current which triggers ALARM state, in mA.*
- unsigned int [CriticalUusb](#)  
*Maximum USB voltage which triggers ALARM state, in mV.*
- unsigned int [MinimumUusb](#)  
*Minimum USB voltage which triggers ALARM state, in mV.*
- unsigned int [Flags](#)  
*Flags of secure settings.*

#### 4.38.1 Detailed Description

This structure contains raw analog data from ADC embedded on board.

These data used for device testing and deep recalibration by manufacturer only.

See also

[get\\_secure\\_settings](#)  
[set\\_secure\\_settings](#)  
[get\\_secure\\_settings](#), [set\\_secure\\_settings](#)

#### 4.38.2 Field Documentation

##### 4.38.2.1 unsigned int CriticalIpwr

Maximum motor current which triggers ALARM state, in mA.

Range: 0..65535.

##### 4.38.2.2 unsigned int CriticalIusb

Maximum USB current which triggers ALARM state, in mA.

Range: 0..65535.

##### 4.38.2.3 unsigned int CriticalT

Maximum temperature, which triggers ALARM state, in tenths of degrees Celcius.

Range: 0..65535.

##### 4.38.2.4 unsigned int CriticalUpwr

Maximum motor voltage which triggers ALARM state, in mV.

Range: 0..65535.

##### 4.38.2.5 unsigned int CriticalUusb

Maximum USB voltage which triggers ALARM state, in mV.

Range: 0..65535.

## 4.38.2.6 unsigned int LowUpwrOff

Lower voltage limit to turn off the motor, in mV.

Range: 0..65535.

## 4.38.2.7 unsigned int MinimumUusb

Minimum USB voltage which triggers ALARM state, in mV.

Range: 0..65535.

## 4.39 serial\_number\_t Struct Reference

Serial number structure.

### Data Fields

- unsigned int [SN](#)  
*New board serial number.*
- unsigned int [Key](#) [32]  
*Protection key (256 bit).*

### 4.39.1 Detailed Description

Serial number structure.

The structure keep new serial number and valid key. The SN is changed and saved when transmitted key matches stored key. Can be used by manufacturer only.

See also

[set\\_serial\\_number](#)

## 4.40 set\_position\_calb\_t Struct Reference

### Data Fields

- float [Position](#)  
*The position in the engine.*
- long\_t [EncPosition](#)  
*Encoder position.*
- unsigned int [PosFlags](#)  
*Position setting flags.*

## 4.41 set\_position\_t Struct Reference

Position information.

## Data Fields

- int [Position](#)  
*The position of the whole steps in the engine.*
- int [uPosition](#)  
*Microstep position is only used with stepper motors.*
- long\_t [EncPosition](#)  
*Encoder position.*
- unsigned int [PosFlags](#)  
*Position setting flags.*

### 4.41.1 Detailed Description

Position information.

Useful structure that contains position value in steps and micro for stepper motor and encoder steps of all engines.

See also

[set\\_position](#)

## 4.42 stage\_information\_t Struct Reference

Stage information.

## Data Fields

- char [Manufacturer](#) [17]  
*Manufacturer.*
- char [PartNumber](#) [25]  
*Series and PartNumber.*

### 4.42.1 Detailed Description

Stage information.

See also

[set\\_stage\\_information](#)  
[get\\_stage\\_information](#)  
[get\\_stage\\_information](#), [set\\_stage\\_information](#)

### 4.42.2 Field Documentation

#### 4.42.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

4.42.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

## 4.43 stage\_name\_t Struct Reference

Stage user name.

### Data Fields

- char [PositionerName](#) [17]  
*User positioner name.*

### 4.43.1 Detailed Description

Stage user name.

See also

[get\\_stage\\_name](#), [set\\_stage\\_name](#)

### 4.43.2 Field Documentation

4.43.2.1 char PositionerName[17]

User positioner name.

Can be set by user for his/her convinience. Max string length: 16 chars.

## 4.44 stage\_settings\_t Struct Reference

Stage settings.

### Data Fields

- float [LeadScrewPitch](#)  
*Lead screw pitch (mm).*
- char [Units](#) [9]  
*Units for MaxSpeed and TravelRange fields of the structure (steps, degrees, mm, ...).*
- float [MaxSpeed](#)  
*Max speed (Units/c).*
- float [TravelRange](#)  
*Travel range (Units).*
- float [SupplyVoltageMin](#)  
*Supply voltage minimum (V).*
- float [SupplyVoltageMax](#)  
*Supply voltage maximum (V).*
- float [MaxCurrentConsumption](#)

- Max current consumption (A).*
  - float [HorizontalLoadCapacity](#)  
*Horizontal load capacity (kg).*
  - float [VerticalLoadCapacity](#)  
*Vertical load capacity (kg).*

#### 4.44.1 Detailed Description

Stage settings.

See also

[set\\_stage\\_settings](#)  
[get\\_stage\\_settings](#)  
[get\\_stage\\_settings](#), [set\\_stage\\_settings](#)

#### 4.44.2 Field Documentation

##### 4.44.2.1 float HorizontalLoadCapacity

Horizontal load capacity (kg).

Data type: float.

##### 4.44.2.2 float LeadScrewPitch

Lead screw pitch (mm).

Data type: float.

##### 4.44.2.3 float MaxCurrentConsumption

Max current consumption (A).

Data type: float.

##### 4.44.2.4 float MaxSpeed

Max speed (Units/c).

Data type: float.

##### 4.44.2.5 float SupplyVoltageMax

Supply voltage maximum (V).

Data type: float.

##### 4.44.2.6 float SupplyVoltageMin

Supply voltage minimum (V).

Data type: float.

## 4.44.2.7 float TravelRange

Travel range (Units).

Data type: float.

## 4.44.2.8 char Units[9]

Units for MaxSpeed and TravelRange fields of the structure (steps, degrees, mm, ...).

Max string length: 8 chars.

## 4.44.2.9 float VerticalLoadCapacity

Vertical load capacity (kg).

Data type: float.

## 4.45 status\_calb\_t Struct Reference

## Data Fields

- unsigned int [MoveSts](#)  
*Flags of move state.*
- unsigned int [MvCmdSts](#)  
*Move command state.*
- unsigned int [PWRSts](#)  
*Flags of power state of stepper motor.*
- unsigned int [EncSts](#)  
*Encoder state.*
- unsigned int [WindSts](#)  
*Winding state.*
- float [CurPosition](#)  
*Current position.*
- long\_t [EncPosition](#)  
*Current encoder position.*
- float [CurSpeed](#)  
*Motor shaft speed.*
- int [Ipwr](#)  
*Engine current.*
- int [Upwr](#)  
*Power supply voltage.*
- int [Iusb](#)  
*USB current consumption.*
- int [Uusb](#)  
*USB voltage.*
- int [CurT](#)  
*Temperature in tenths of degrees C.*
- unsigned int [Flags](#)  
*Status flags.*
- unsigned int [GPIOFlags](#)  
*Status flags.*
- unsigned int [CmdBufFreeSpace](#)  
*This field shows the amount of free cells buffer synchronization chain.*

## 4.46 status\_t Struct Reference

Device state.

### Data Fields

- unsigned int [MoveSts](#)  
*Flags of move state.*
- unsigned int [MvCmdSts](#)  
*Move command state.*
- unsigned int [PWRSts](#)  
*Flags of power state of stepper motor.*
- unsigned int [EncSts](#)  
*Encoder state.*
- unsigned int [WindSts](#)  
*Winding state.*
- int [CurPosition](#)  
*Current position.*
- int [uCurPosition](#)  
*Step motor shaft position in 1/256 microsteps.*
- long\_t [EncPosition](#)  
*Current encoder position.*
- int [CurSpeed](#)  
*Motor shaft speed.*
- int [uCurSpeed](#)  
*Part of motor shaft speed in 1/256 microsteps.*
- int [lpwr](#)  
*Engine current.*
- int [Upwr](#)  
*Power supply voltage.*
- int [lusb](#)  
*USB current consumption.*
- int [Uusb](#)  
*USB voltage.*
- int [CurT](#)  
*Temperature in tenths of degrees C.*
- unsigned int [Flags](#)  
*Status flags.*
- unsigned int [GPIOFlags](#)  
*Status flags.*
- unsigned int [CmdBufFreeSpace](#)  
*This field shows the amount of free cells buffer synchronization chain.*

### 4.46.1 Detailed Description

Device state.

Useful structure that contains current controller state, including speed, position and boolean flags.

See also

`get_status_impl`



## 4.46.2 Field Documentation

## 4.46.2.1 int uCurPosition

Step motor shaft position in 1/256 microsteps.

Used only with stepper motor.

## 4.46.2.2 int uCurSpeed

Part of motor shaft speed in 1/256 microsteps.

Used only with stepper motor.

## 4.47 sync\_in\_settings\_calb\_t Struct Reference

## Data Fields

- unsigned int [SyncInFlags](#)  
*Flags for synchronization input setup.*
- unsigned int [ClutterTime](#)  
*Input synchronization pulse dead time (mks).*
- float [Position](#)  
*Desired position or shift.*
- float [Speed](#)  
*Target speed.*

## 4.47.1 Field Documentation

## 4.47.1.1 unsigned int ClutterTime

Input synchronization pulse dead time (mks).

Range: 0..65535

## 4.48 sync\_in\_settings\_t Struct Reference

Synchronization settings.

## Data Fields

- unsigned int [SyncInFlags](#)  
*Flags for synchronization input setup.*
- unsigned int [ClutterTime](#)  
*Input synchronization pulse dead time (mks).*
- int [Position](#)  
*Desired position or shift (whole steps)*
- int [uPosition](#)  
*The fractional part of a position or shift in microsteps (-255 .*
- unsigned int [Speed](#)  
*Target speed(for stepper motor: steps / c, for DC: rpm).*

- unsigned int [uSpeed](#)  
*Target speed in microsteps/s.*

#### 4.48.1 Detailed Description

Synchronization settings.

This structure contains all synchronization settings, modes, periods and flags. It specifies behaviour of input synchronization. All boards are supplied with standart set of these settings.

See also

[get\\_sync\\_in\\_settings](#)  
[set\\_sync\\_in\\_settings](#)  
[get\\_sync\\_in\\_settings](#), [set\\_sync\\_in\\_settings](#)

#### 4.48.2 Field Documentation

##### 4.48.2.1 unsigned int ClutterTime

Input synchronization pulse dead time (mks).

Range: 0..65535

##### 4.48.2.2 unsigned int Speed

Target speed(for stepper motor: steps / c, for DC: rpm).

Range: 0..1000000.

##### 4.48.2.3 int uPosition

The fractional part of a position or shift in microsteps (-255 .  
 . 255)(is only used with stepper motor)

##### 4.48.2.4 unsigned int uSpeed

Target speed in microsteps/s.

Using with stepper motor only. Range: 0..255.

## 4.49 sync\_out\_settings\_calb\_t Struct Reference

### Data Fields

- unsigned int [SyncOutFlags](#)  
*Flags of synchronization output.*
- unsigned int [SyncOutPulseSteps](#)  
*This value specifies duration of output pulse.*
- unsigned int [SyncOutPeriod](#)  
*This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT\_ONPERIOD is set.*
- float [Accuracy](#)

*This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.*

#### 4.49.1 Field Documentation

##### 4.49.1.1 unsigned int SyncOutPeriod

This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT\_ONPERIOD is set.

Range: 0..65535

##### 4.49.1.2 unsigned int SyncOutPulseSteps

This value specifies duration of output pulse.

It is measured microseconds when SYNCOUT\_IN\_STEPS flag is cleared or in encoder pulses or motor steps when SYNCOUT\_IN\_STEPS is set. Range: 0..65535

## 4.50 sync\_out\_settings\_t Struct Reference

Synchronization settings.

### Data Fields

- unsigned int [SyncOutFlags](#)  
*Flags of synchronization output.*
- unsigned int [SyncOutPulseSteps](#)  
*This value specifies duration of output pulse.*
- unsigned int [SyncOutPeriod](#)  
*This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT\_ONPERIOD is set.*
- unsigned int [Accuracy](#)  
*This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.*
- unsigned int [uAccuracy](#)  
*This is the neighborhood around the target coordinates in micro steps (only used with stepper motor).*

#### 4.50.1 Detailed Description

Synchronization settings.

This structure contains all synchronization settings, modes, periods and flags. It specifies behaviour of output synchronization. All boards are supplied with standart set of these settings.

See also

[get\\_sync\\_out\\_settings](#)  
[set\\_sync\\_out\\_settings](#)  
[get\\_sync\\_out\\_settings](#), [set\\_sync\\_out\\_settings](#)

### 4.50.2 Field Documentation

#### 4.50.2.1 unsigned int Accuracy

This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.

Range: 0..4294967295.

#### 4.50.2.2 unsigned int SyncOutPeriod

This value specifies number of encoder pulses or steps between two output synchronization pulses when `SYNCOUT_ONPERIOD` is set.

Range: 0..65535

#### 4.50.2.3 unsigned int SyncOutPulseSteps

This value specifies duration of output pulse.

It is measured microseconds when `SYNCOUT_IN_STEPS` flag is cleared or in encoder pulses or motor steps when `SYNCOUT_IN_STEPS` is set. Range: 0..65535

#### 4.50.2.4 unsigned int uAccuracy

This is the neighborhood around the target coordinates in micro steps (only used with stepper motor).

Range: 0 .. 255.

## 4.51 `uart_settings_t` Struct Reference

UART settings.

### Data Fields

- unsigned int [Speed](#)  
*UART speed.*
- unsigned int [UARTSetupFlags](#)  
*UART parity flags.*

### 4.51.1 Detailed Description

UART settings.

This structure contains UART settings.

See also

[get\\_uart\\_settings](#)  
[set\\_uart\\_settings](#)  
[get\\_uart\\_settings](#), [set\\_uart\\_settings](#)

# Chapter 5

## File Documentation

### 5.1 ximc.h File Reference

Header file for libximc library.

#### Data Structures

- struct [calibration\\_t](#)  
*Calibration companion structure.*
- struct [feedback\\_settings\\_t](#)  
*Feedback settings.*
- struct [home\\_settings\\_t](#)  
*Position calibration settings.*
- struct [home\\_settings\\_calb\\_t](#)
- struct [move\\_settings\\_t](#)  
*Move settings.*
- struct [move\\_settings\\_calb\\_t](#)
- struct [engine\\_settings\\_t](#)  
*Engine settings.*
- struct [engine\\_settings\\_calb\\_t](#)
- struct [entype\\_settings\\_t](#)  
*Engine type and driver type settings.*
- struct [power\\_settings\\_t](#)  
*Step motor power settings.*
- struct [secure\\_settings\\_t](#)  
*This structure contains raw analog data from ADC embedded on board.*
- struct [edges\\_settings\\_t](#)  
*Edges settings.*
- struct [edges\\_settings\\_calb\\_t](#)
- struct [pid\\_settings\\_t](#)  
*PID settings.*
- struct [sync\\_in\\_settings\\_t](#)  
*Synchronization settings.*
- struct [sync\\_in\\_settings\\_calb\\_t](#)
- struct [sync\\_out\\_settings\\_t](#)  
*Synchronization settings.*
- struct [sync\\_out\\_settings\\_calb\\_t](#)

- struct [extio\\_settings\\_t](#)  
*EXTIO settings.*
- struct [brake\\_settings\\_t](#)  
*Brake settings.*
- struct [control\\_settings\\_t](#)  
*Control settings.*
- struct [control\\_settings\\_calb\\_t](#)
- struct [joystick\\_settings\\_t](#)  
*Joystick settings.*
- struct [ctp\\_settings\\_t](#)  
*Control position settings(is only used with stepper motor).*
- struct [uart\\_settings\\_t](#)  
*UART settings.*
- struct [controller\\_name\\_t](#)  
*Controller user name and flags of setting.*
- struct [add\\_sync\\_in\\_action\\_t](#)  
*This command adds one element of the FIFO commands.*
- struct [add\\_sync\\_in\\_action\\_calb\\_t](#)
- struct [get\\_position\\_t](#)  
*Position information.*
- struct [get\\_position\\_calb\\_t](#)
- struct [set\\_position\\_t](#)  
*Position information.*
- struct [set\\_position\\_calb\\_t](#)
- struct [status\\_t](#)  
*Device state.*
- struct [status\\_calb\\_t](#)
- struct [chart\\_data\\_t](#)  
*Additional device state.*
- struct [device\\_information\\_t](#)  
*Read command controller information.*
- struct [serial\\_number\\_t](#)  
*Serial number structure.*
- struct [analog\\_data\\_t](#)  
*Analog data.*
- struct [debug\\_read\\_t](#)  
*Debug data.*
- struct [stage\\_name\\_t](#)  
*Stage user name.*
- struct [stage\\_information\\_t](#)  
*Stage information.*
- struct [stage\\_settings\\_t](#)  
*Stage settings.*
- struct [motor\\_information\\_t](#)  
*motor information.*
- struct [motor\\_settings\\_t](#)  
*motor settings.*
- struct [encoder\\_information\\_t](#)  
*Encoder information.*
- struct [encoder\\_settings\\_t](#)  
*Encoder settings.*

- struct [hallsensor\\_information\\_t](#)  
*Hall sensor information.*
- struct [hallsensor\\_settings\\_t](#)  
*Hall sensor settings.*
- struct [gear\\_information\\_t](#)  
*Gear information.*
- struct [gear\\_settings\\_t](#)  
*Gear settings.*
- struct [accessories\\_settings\\_t](#)  
*Additional accessories information.*

## Macros

- #define [XIMC\\_API](#)  
*Library import macro Macros allows to automatically import function from shared library.*
- #define [XIMC\\_CALLCONV](#)  
*Library calling convention macros.*
- #define [device\\_undefined](#) -1  
*Handle specified undefined device.*

## Result statuses

- #define [result\\_ok](#) 0  
*success*
- #define [result\\_error](#) -1  
*generic error*
- #define [result\\_not\\_implemented](#) -2  
*function is not implemented*
- #define [result\\_value\\_error](#) -3  
*value error*
- #define [result\\_nodevice](#) -4  
*device is lost*

## Logging level

- #define [LOGLEVEL\\_ERROR](#) 0x01  
*Logging level - error.*
- #define [LOGLEVEL\\_WARNING](#) 0x02  
*Logging level - warning.*
- #define [LOGLEVEL\\_INFO](#) 0x03  
*Logging level - info.*
- #define [LOGLEVEL\\_DEBUG](#) 0x04  
*Logging level - debug.*

## Enumerate devices flags

- #define [ENUMERATE\\_PROBE](#) 0x01  
*Check if a device with OS name name is XIMC device.*
- #define [ENUMERATE\\_ALL\\_COM](#) 0x02  
*Check all COM devices.*

## Flags of move state

*Specify move states.*

See also

[get.status](#)

`status.t::move.state`

[status.t::MoveSts](#), [get.status\\_impl](#)

- #define [MOVE.STATE.MOVING](#) 0x01  
*This flag indicates that controller is trying to move the motor.*
- #define [MOVE.STATE.TARGET.SPEED](#) 0x02  
*Target speed is reached, if flag set.*
- #define [MOVE.STATE.ANTIPLAY](#) 0x04  
*Motor is playing compensation, if flag set.*

### Flags of internal controller settings

See also

[set.controller.name](#)

[get.controller.name](#)

`controller.name.t::CtrlFlags`, [get.controller.name](#), [set.controller.name](#)

- #define [EEPROM.PRECEDENCE](#) 0x01  
*If the flag is set settings from external EEPROM override controller settings.*

### Flags of power state of stepper motor

*Specify power states.*

See also

`status.t::power.state`

[get.status](#)

[status.t::PWRSts](#), [get.status\\_impl](#)

- #define [PWR.STATE.UNKNOWN](#) 0x00  
*Unknown state, should never happen.*
- #define [PWR.STATE.OFF](#) 0x01  
*Motor windings are disconnected from the driver.*
- #define [PWR.STATE.NORM](#) 0x03  
*Motor windings are powered by nominal current.*
- #define [PWR.STATE.REDUCT](#) 0x04  
*Motor windings are powered by reduced current to lower power consumption.*
- #define [PWR.STATE.MAX](#) 0x05  
*Motor windings are powered by maximum current driver can provide at this voltage.*

### Status flags

*GPIO state flags returned by device query. Contains boolean part of controller state. May be combined with bitwise OR.*

See also

`status.t::flags`

[get.status](#)

[status.t::GPIOFlags](#), [get.status\\_impl](#)

- #define [STATE.CONTR](#) 0x0003F  
*Flags of controller states.*
- #define [STATE.ERRC](#) 0x00001  
*Command error encountered.*
- #define [STATE.ERRD](#) 0x00002  
*Data integrity error encountered.*



- #define `STATE_ERRV` 0x00004  
*Value error encountered.*
- #define `STATE_EEPROM_CONNECTED` 0x00010  
*EEPROM with settings is connected.*
- #define `STATE_SECUR` 0x3FFC0  
*Flags of security.*
- #define `STATE_ALARM` 0x00040  
*Controller is in alarm state indicating that something dangerous had happened.*
- #define `STATE_CTP_ERROR` 0x00080  
*Control position error(is only used with stepper motor).*
- #define `STATE_POWER_OVERHEAT` 0x00100  
*Power driver overheat.*
- #define `STATE_CONTROLLER_OVERHEAT` 0x00200  
*Controller overheat.*
- #define `STATE_OVERLOAD_POWER_VOLTAGE` 0x00400  
*Power voltage exceeds safe limit.*
- #define `STATE_OVERLOAD_POWER_CURRENT` 0x00800  
*Power current exceeds safe limit.*
- #define `STATE_OVERLOAD_USB_VOLTAGE` 0x01000  
*USB voltage exceeds safe limit.*
- #define `STATE_LOW_USB_VOLTAGE` 0x02000  
*USB voltage is insufficient for normal operation.*
- #define `STATE_OVERLOAD_USB_CURRENT` 0x04000  
*USB current exceeds safe limit.*
- #define `STATE_BORDERS_SWAP_MISSET` 0x08000  
*Engine stuck at the wrong edge.*
- #define `STATE_LOW_POWER_VOLTAGE` 0x10000  
*Power voltage is lower than Low Voltage Protection limit.*
- #define `STATE_H_BRIDGE_FAULT` 0x20000  
*Signal from the driver that fault happened.*
- #define `STATE_DIG_SIGNAL` 0xFFFF  
*Flags of digital signals.*
- #define `STATE_RIGHT_EDGE` 0x0001  
*Engine stuck at the right edge.*
- #define `STATE_LEFT_EDGE` 0x0002  
*Engine stuck at the left edge.*
- #define `STATE_BUTTON_RIGHT` 0x0004  
*Button "right" state (1 if pressed).*
- #define `STATE_BUTTON_LEFT` 0x0008  
*Button "left" state (1 if pressed).*
- #define `STATE_GPIO_PINOUT` 0x0010  
*External GPIO works as Out, if flag set; otherwise works as In.*
- #define `STATE_GPIO_LEVEL` 0x0020  
*State of external GPIO pin.*
- #define `STATE_HALL_A` 0x0040  
*State of Hall.a pin.*
- #define `STATE_HALL_B` 0x0080  
*State of Hall.b pin.*
- #define `STATE_HALL_C` 0x0100  
*State of Hall.c pin.*
- #define `STATE_BRAKE` 0x0200  
*State of Brake pin.*
- #define `STATE_REV_SENSOR` 0x0400  
*State of Revolution sensor pin.*
- #define `STATE_SYNC_INPUT` 0x0800

- State of Sync input pin.*
- #define [STATE\\_SYNC\\_OUTPUT](#) 0x1000
- State of Sync output pin.*
- #define [STATE\\_ENC\\_A](#) 0x2000
- State of encoder A pin.*
- #define [STATE\\_ENC\\_B](#) 0x4000
- State of encoder B pin.*

### Encoder state

Encoder state returned by device query.

See also

[status\\_t::encsts](#)  
[get\\_status](#)  
[status\\_t::EncSts](#), [get\\_status\\_impl](#)

- #define [ENC\\_STATE\\_ABSENT](#) 0x00
- Encoder is absent.*
- #define [ENC\\_STATE\\_UNKNOWN](#) 0x01
- Encoder state is unknown.*
- #define [ENC\\_STATE\\_MALFUNC](#) 0x02
- Encoder is connected and malfunctioning.*
- #define [ENC\\_STATE\\_REVERS](#) 0x03
- Encoder is connected and operational but counts in otyher direction.*
- #define [ENC\\_STATE\\_OK](#) 0x04
- Encoder is connected and working properly.*

### Winding state

Motor winding state returned by device query.

See also

[status\\_t::windsts](#)  
[get\\_status](#)  
[status\\_t::WindSts](#), [get\\_status\\_impl](#)

- #define [WIND\\_A.STATE\\_ABSENT](#) 0x00
- Winding A is disconnected.*
- #define [WIND\\_A.STATE\\_UNKNOWN](#) 0x01
- Winding A state is unknown.*
- #define [WIND\\_A.STATE\\_MALFUNC](#) 0x02
- Winding A is short-circuited.*
- #define [WIND\\_A.STATE\\_OK](#) 0x03
- Winding A is connected and working properly.*
- #define [WIND\\_B.STATE\\_ABSENT](#) 0x00
- Winding B is disconnected.*
- #define [WIND\\_B.STATE\\_UNKNOWN](#) 0x10
- Winding B state is unknown.*
- #define [WIND\\_B.STATE\\_MALFUNC](#) 0x20
- Winding B is short-circuited.*
- #define [WIND\\_B.STATE\\_OK](#) 0x30
- Winding B is connected and working properly.*

### Move command state

Move command ([command\\_move](#), [command\\_movr](#), [command\\_left](#), [command\\_right](#), [command\\_stop](#), [command\\_home](#), [command\\_loft](#), [command\\_sstp](#)) and its state (*run*, *finished*, *error*).

See also

`status_t::mvcmdsts`  
[get.status](#)  
[status\\_t::MvCmdSIs](#), [get.status\\_impl](#)

- #define [MVCMD\\_NAME\\_BITS](#) 0x3F  
*Move command bit mask.*
- #define [MVCMD\\_UKNWN](#) 0x00  
*Unknown command.*
- #define [MVCMD\\_MOVE](#) 0x01  
*Command move.*
- #define [MVCMD\\_MOVR](#) 0x02  
*Command movr.*
- #define [MVCMD\\_LEFT](#) 0x03  
*Command left.*
- #define [MVCMD\\_RIGHT](#) 0x04  
*Command rigt.*
- #define [MVCMD\\_STOP](#) 0x05  
*Command stop.*
- #define [MVCMD\\_HOME](#) 0x06  
*Command home.*
- #define [MVCMD\\_LOFT](#) 0x07  
*Command loft.*
- #define [MVCMD\\_SSTP](#) 0x08  
*Command soft stop.*
- #define [MVCMD\\_ERROR](#) 0x40  
*Finish state (1 - move command have finished with an error, 0 - move command have finished correctly).*
- #define [MVCMD\\_RUNNING](#) 0x80  
*Move command state (0 - move command have finished, 1 - move command is being executed).*

### Flags of engine settings

Specify motor shaft movement algorithm and list of limitations. Flags returned by query of engine settings. May be combined with bitwise OR.

See also

`engine_settings_t::flags`  
[set\\_engine\\_settings](#)  
[get\\_engine\\_settings](#)  
[engine\\_settings\\_t::EngineFlags](#), [get\\_engine\\_settings](#), [set\\_engine\\_settings](#)

- #define [ENGINE\\_REVERSE](#) 0x01  
*Reverse flag.*
- #define [ENGINE\\_MAX\\_SPEED](#) 0x04  
*Max speed flag.*
- #define [ENGINE\\_ANTIPLAY](#) 0x08  
*Play compensation flag.*
- #define [ENGINE\\_ACCEL\\_ON](#) 0x10  
*Acceleration enable flag.*
- #define [ENGINE\\_LIMIT\\_VOLT](#) 0x20  
*Maxumum motor voltage limit enable flag(is only used with DC motor).*
- #define [ENGINE\\_LIMIT\\_CURR](#) 0x40  
*Maxumum motor current limit enable flag(is only used with DC motor).*
- #define [ENGINE\\_LIMIT\\_RPM](#) 0x80  
*Maxumum motor speed limit enable flag.*

### Flags of microstep mode

Specify settings of microstep mode. Using with step motors. Flags returned by query of engine settings. May be combined with bitwise OR

See also

[engine\\_settings\\_t::flags](#)  
[set\\_engine\\_settings](#)  
[get\\_engine\\_settings](#)  
[engine\\_settings\\_t::MicrostepMode](#), [get\\_engine\\_settings](#), [set\\_engine\\_settings](#)

- #define [MICROSTEP\\_MODE\\_FULL](#) 0x01  
*Full step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_2](#) 0x02  
*1/2 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_4](#) 0x03  
*1/4 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_8](#) 0x04  
*1/8 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_16](#) 0x05  
*1/16 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_32](#) 0x06  
*1/32 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_64](#) 0x07  
*1/64 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_128](#) 0x08  
*1/128 step mode.*
- #define [MICROSTEP\\_MODE\\_FRAC\\_256](#) 0x09  
*1/256 step mode.*

### Flags of engine type

Specify motor type. Flags returned by query of engine settings.

See also

[engine\\_settings\\_t::flags](#)  
[set\\_entype\\_settings](#)  
[get\\_entype\\_settings](#)  
[entype\\_settings\\_t::EngineType](#), [get\\_entype\\_settings](#), [set\\_entype\\_settings](#)

- #define [ENGINE\\_TYPE\\_NONE](#) 0x00  
*A value that shouldn't be used.*
- #define [ENGINE\\_TYPE\\_DC](#) 0x01  
*DC motor.*
- #define [ENGINE\\_TYPE\\_2DC](#) 0x02  
*2 DC motors.*
- #define [ENGINE\\_TYPE\\_STEP](#) 0x03  
*Step motor.*
- #define [ENGINE\\_TYPE\\_TEST](#) 0x04  
*Duty cycle are fixed.*
- #define [ENGINE\\_TYPE\\_BRUSHLESS](#) 0x05  
*Brushless motor.*

### Flags of driver type

Specify driver type. Flags returned by query of engine settings.

See also

[engine\\_settings\\_t::flags](#)  
[set\\_entype\\_settings](#)  
[get\\_entype\\_settings](#)  
[entype\\_settings\\_t::DriverType](#), [get\\_entype\\_settings](#), [set\\_entype\\_settings](#)

- #define [DRIVER\\_TYPE\\_DISCRETE\\_FET](#) 0x01  
*Driver with discrete FET keys.*
- #define [DRIVER\\_TYPE\\_INTEGRATE](#) 0x02  
*Driver with integrated IC.*
- #define [DRIVER\\_TYPE\\_EXTERNAL](#) 0x03  
*External driver.*

### Flags of power settings of stepper motor

*Specify power settings. Flags returned by query of power settings.*

See also

[power\\_settings\\_t::flags](#)  
[get\\_power\\_settings](#)  
[set\\_power\\_settings](#)  
[power\\_settings\\_t::PowerFlags](#), [get\\_power\\_settings](#), [set\\_power\\_settings](#)

- #define [POWER\\_REDUCT\\_ENABLED](#) 0x01  
*Current reduction enabled after CurrReductDelay, if this flag is set.*
- #define [POWER\\_OFF\\_ENABLED](#) 0x02  
*Power off enabled after PowerOffDelay, if this flag is set.*
- #define [POWER\\_SMOOTH\\_CURRENT](#) 0x04  
*Current ramp-up/down is performed smoothly during current.set.time, if this flag is set.*

### Flags of secure settings

*Specify secure settings. Flags returned by query of secure settings.*

See also

[secure\\_settings\\_t::flags](#)  
[get\\_secure\\_settings](#)  
[set\\_secure\\_settings](#)  
[secure\\_settings\\_t::Flags](#), [get\\_secure\\_settings](#), [set\\_secure\\_settings](#)

- #define [ALARM\\_ON\\_DRIVER\\_OVERHEATING](#) 0x01  
*If this flag is set enter Alarm state on driver overheat signal.*
- #define [LOW\\_UPWR\\_PROTECTION](#) 0x02  
*If this flag is set turn off motor when voltage is lower than LowUpwrOff.*
- #define [H\\_BRIDGE\\_ALERT](#) 0x04  
*If this flag is set then turn off the power unit with a signal problem in one of the transistor bridge.*
- #define [ALARM\\_ON\\_BORDERS\\_SWAP\\_MISSET](#) 0x08  
*If this flag is set enter Alarm state on borders swap misset.*
- #define [ALARM\\_FLAGS\\_STICKING](#) 0x10  
*If this flag is set only a STOP command can turn all alarms to 0.*
- #define [USB\\_BREAK\\_RECONNECT](#) 0x20  
*If this flag is set USB brake reconnect module will be enable.*

### Position setting flags

*Flags used in setting of position.*

See also

[get\\_position](#)  
[set\\_position](#)  
[set\\_position.t::PosFlags](#), [set\\_position](#)

- #define [SETPOS\\_IGNORE\\_POSITION](#) 0x01  
*Will not reload position in steps/microsteps if this flag is set.*
- #define [SETPOS\\_IGNORE\\_ENCODER](#) 0x02  
*Will not reload encoder state if this flag is set.*

### Feedback type.

See also

[set\\_feedback\\_settings](#)  
[get\\_feedback\\_settings](#)  
[feedback\\_settings.t::FeedbackType](#), [get\\_feedback\\_settings](#), [set\\_feedback\\_settings](#)

- #define [FEEDBACK\\_ENCODER](#) 0x01  
*Feedback by encoder.*
- #define [FEEDBACK\\_ENCODERHALL](#) 0x03  
*Feedback by Hall detector.*
- #define [FEEDBACK\\_EMF](#) 0x04  
*Feedback by EMF.*
- #define [FEEDBACK\\_NONE](#) 0x05  
*Feedback is absent.*

### Describes feedback flags.

See also

[set\\_feedback\\_settings](#)  
[get\\_feedback\\_settings](#)  
[feedback\\_settings.t::FeedbackFlags](#), [get\\_feedback\\_settings](#), [set\\_feedback\\_settings](#)

- #define [FEEDBACK\\_ENC\\_REVERSE](#) 0x01  
*Reverse count of encoder.*
- #define [FEEDBACK\\_HALL\\_REVERSE](#) 0x02  
*Reverse count position on the Hall sensor.*

### Flags for synchronization input setup

See also

[sync\\_settings.t::syncin\\_flags](#)  
[get\\_sync\\_settings](#)  
[set\\_sync\\_settings](#)  
[sync\\_in\\_settings.t::SyncInFlags](#), [get\\_sync\\_in\\_settings](#), [set\\_sync\\_in\\_settings](#)

- #define [SYNCIN\\_ENABLED](#) 0x01  
*Synchronization in mode is enabled, if this flag is set.*
- #define [SYNCIN\\_INVERT](#) 0x02  
*Trigger on falling edge if flag is set, on rising edge otherwise.*
- #define [SYNCIN\\_GOTOPOSITION](#) 0x04  
*The engine is go to position specified in Position and uPosition, if this flag is set.*

### Flags of synchronization output

See also

[sync\\_settings.t::syncout\\_flags](#)

[get\\_sync\\_settings](#)

[set\\_sync\\_settings](#)

[sync\\_out\\_settings.t::SyncOutFlags](#), [get\\_sync\\_out\\_settings](#), [set\\_sync\\_out\\_settings](#)

- #define [SYNCOUT\\_ENABLED](#) 0x01  
*Synchronization out pin follows the synchronization logic, if set.*
- #define [SYNCOUT\\_STATE](#) 0x02  
*When output state is fixed by negative SYNCOUT\_ENABLED flag, the pin state is in accordance with this flag state.*
- #define [SYNCOUT\\_INVERT](#) 0x04  
*Low level is active, if set, and high level is active otherwise.*
- #define [SYNCOUT\\_IN\\_STEPS](#) 0x08  
*Use motor steps/encoder pulses instead of milliseconds for output pulse generation if the flag is set.*
- #define [SYNCOUT\\_ONSTART](#) 0x10  
*Generate synchronization pulse when movement starts.*
- #define [SYNCOUT\\_ONSTOP](#) 0x20  
*Generate synchronization pulse when movement stops.*
- #define [SYNCOUT\\_ONPERIOD](#) 0x40  
*Generate synchronization pulse every SyncOutPeriod encoder pulses.*

### External IO setup flags

See also

[extio\\_settings.t::setup\\_flags](#)

[get\\_extio\\_settings](#)

[set\\_extio\\_settings](#)

[extio\\_settings.t::EXTIOSetupFlags](#), [get\\_extio\\_settings](#), [set\\_extio\\_settings](#)

- #define [EXTIO\\_SETUP\\_OUTPUT](#) 0x01  
*EXTIO works as output if flag is set, works as input otherwise.*
- #define [EXTIO\\_SETUP\\_INVERT](#) 0x02  
*Interpret EXTIO states and fronts inverted if flag is set.*

### External IO mode flags

See also

[extio\\_settings.t::extio\\_mode\\_flags](#)

[get\\_extio\\_settings](#)

[set\\_extio\\_settings](#)

[extio\\_settings.t::EXTIOModeFlags](#), [get\\_extio\\_settings](#), [set\\_extio\\_settings](#)

- #define [EXTIO\\_SETUP\\_MODE\\_IN\\_NOP](#) 0x00  
*Do nothing.*
- #define [EXTIO\\_SETUP\\_MODE\\_IN\\_STOP](#) 0x01  
*Issue STOP command, ceasing the engine movement.*
- #define [EXTIO\\_SETUP\\_MODE\\_IN\\_PWOF](#) 0x02  
*Issue PWOF command, powering off all engine windings.*
- #define [EXTIO\\_SETUP\\_MODE\\_IN\\_MOVR](#) 0x03  
*Issue MOVR command with last used settings.*
- #define [EXTIO\\_SETUP\\_MODE\\_IN\\_HOME](#) 0x04  
*Issue HOME command.*
- #define [EXTIO\\_SETUP\\_MODE\\_OUT\\_OFF](#) 0x00  
*EXTIO pin always set in inactive state.*
- #define [EXTIO\\_SETUP\\_MODE\\_OUT\\_ON](#) 0x10

- *EXTIO pin always set in active state.*
- #define [EXTIO.SETUP\\_MODE\\_OUT\\_MOVING](#) 0x20  
*EXTIO pin stays active during moving state.*
- #define [EXTIO.SETUP\\_MODE\\_OUT\\_ALARM](#) 0x30  
*EXTIO pin stays active during Alarm state.*
- #define [EXTIO.SETUP\\_MODE\\_OUT\\_MOTOR\\_ON](#) 0x40  
*EXTIO pin stays active when windings are powered.*
- #define [EXTIO.SETUP\\_MODE\\_OUT\\_MOTOR\\_FOUND](#) 0x50  
*EXTIO pin stays active when motor is connected (first winding).*

### Border flags

Specify types of borders and motor behaviour on borders. May be combined with bitwise OR.

See also

[get\\_edges\\_settings](#)  
[set\\_edges\\_settings](#)  
[edges\\_settings.t::BorderFlags](#), [get\\_edges\\_settings](#), [set\\_edges\\_settings](#)

- #define [BORDER.IS.ENCODER](#) 0x01  
*Borders are fixed by predetermined encoder values, if set; borders position on limit switches, if not set.*
- #define [BORDER.STOP.LEFT](#) 0x02  
*Motor should stop on left border.*
- #define [BORDER.STOP.RIGHT](#) 0x04  
*Motor should stop on right border.*
- #define [BORDERS.SWAP.MISSET.DETECTION](#) 0x08  
*Motor should stop on both borders.*

### Limit switches flags

Specify electrical behaviour of limit switches like order and pulled positions. May be combined with bitwise OR.

See also

[get\\_edges\\_settings](#)  
[set\\_edges\\_settings](#)  
[edges\\_settings.t::EnderFlags](#), [get\\_edges\\_settings](#), [set\\_edges\\_settings](#)

- #define [ENDER.SWAP](#) 0x01  
*First limit switch on the right side, if set; otherwise on the left side.*
- #define [ENDER.SW1.ACTIVE.LOW](#) 0x02  
*1 - Limit switch connected to pin SW1 is triggered by a low level on pin.*
- #define [ENDER.SW2.ACTIVE.LOW](#) 0x04  
*1 - Limit switch connected to pin SW2 is triggered by a low level on pin.*

### Brake settings flags

Specify behaviour of brake. May be combined with bitwise OR.

See also

[get\\_brake\\_settings](#)  
[set\\_brake\\_settings](#)  
[brake\\_settings.t::BrakeFlags](#), [get\\_brake\\_settings](#), [set\\_brake\\_settings](#)

- #define [BRAKE.ENABLED](#) 0x01  
*Brake control is enabled, if this flag is set.*
- #define [BRAKE.ENG.PWROFF](#) 0x02  
*Brake turns off power of step motor, if this flag is set.*

### Control flags

Specify motor control settings by joystick or buttons. May be combined with bitwise OR.



See also

[get\\_control\\_settings](#)  
[set\\_control\\_settings](#)  
[control\\_settings.t::Flags](#), [get\\_control\\_settings](#), [set\\_control\\_settings](#)

- #define [CONTROL\\_MODE\\_BITS](#) 0x03  
*Bits to control engine by joystick or buttons.*
- #define [CONTROL\\_MODE\\_OFF](#) 0x00  
*Control is disabled.*
- #define [CONTROL\\_MODE\\_JOY](#) 0x01  
*Control by joystick.*
- #define [CONTROL\\_MODE\\_LR](#) 0x02  
*Control by left/right buttons.*
- #define [CONTROL\\_BTN\\_LEFT\\_PUSHED\\_OPEN](#) 0x04  
*Pushed left button corresponds to open contact, if this flag is set.*
- #define [CONTROL\\_BTN\\_RIGHT\\_PUSHED\\_OPEN](#) 0x08  
*Pushed right button corresponds to open contact, if this flag is set.*

### Joystick flags

Control joystick states.

See also

[set\\_joystick\\_settings](#)  
[get\\_joystick\\_settings](#)  
[joystick\\_settings.t::JoyFlags](#), [get\\_joystick\\_settings](#), [set\\_joystick\\_settings](#)

- #define [JOY\\_REVERSE](#) 0x01  
*Joystick action is reversed.*

### Position control flags

Specify settings of position control. May be combined with bitwise OR.

See also

[get\\_ctp\\_settings](#)  
[set\\_ctp\\_settings](#)  
[ctp\\_settings.t::CTPFlags](#), [get\\_ctp\\_settings](#), [set\\_ctp\\_settings](#)

- #define [CTP\\_ENABLED](#) 0x01  
*Position control is enabled, if flag set.*
- #define [CTP\\_BASE](#) 0x02  
*Position control is based on revolution sensor, if this flag is set; otherwise it is based on encoder.*
- #define [CTP\\_ALARM\\_ON\\_ERROR](#) 0x04  
*Set ALARM on mismatch, if flag set.*
- #define [REV\\_SENS\\_INV](#) 0x08  
*Sensor is active when it 0 and invert makes active level 1.*

### Home settings flags

Specify behaviour for home command. May be combined with bitwise OR.

See also

[get\\_home\\_settings](#)  
[set\\_home\\_settings](#)  
[command\\_home](#)  
[home\\_settings.t::HomeFlags](#), [get\\_home\\_settings](#), [set\\_home\\_settings](#)

- #define [HOME\\_DIR\\_FIRST](#) 0x01

- *Flag defines direction of 1st motion after execution of home command.*  
• #define [HOME\\_DIR\\_SECOND](#) 0x02
- *Flag defines direction of 2nd motion.*  
• #define [HOME\\_MV\\_SEC\\_EN](#) 0x04
- *Use the second phase of calibration to the home position, if set; otherwise the second phase is skipped.*  
• #define [HOME\\_HALF\\_MV](#) 0x08
- *If the flag is set, the stop signals are ignored in start of second movement the first half-turn.*  
• #define [HOME\\_STOP\\_FIRST\\_BITS](#) 0x30
- *Bits of the first stop selector.*  
• #define [HOME\\_STOP\\_FIRST\\_REV](#) 0x10
- *First motion stops by revolution sensor.*  
• #define [HOME\\_STOP\\_FIRST\\_SYN](#) 0x20
- *First motion stops by synchronization input.*  
• #define [HOME\\_STOP\\_FIRST\\_LIM](#) 0x30
- *First motion stops by limit switch.*  
• #define [HOME\\_STOP\\_SECOND\\_BITS](#) 0xC0
- *Bits of the second stop selector.*  
• #define [HOME\\_STOP\\_SECOND\\_REV](#) 0x40
- *Second motion stops by revolution sensor.*  
• #define [HOME\\_STOP\\_SECOND\\_SYN](#) 0x80
- *Second motion stops by synchronization input.*  
• #define [HOME\\_STOP\\_SECOND\\_LIM](#) 0xC0
- *Second motion stops by limit switch.*

### UART parity flags

See also

[uart.settings.t::UARTSetupFlags](#), [get\\_uart\\_settings](#), [set\\_uart\\_settings](#)

- #define [UART\\_PARITY\\_BITS](#) 0x03
- *Bits of the parity.*  
• #define [UART\\_PARITY\\_BIT\\_EVEN](#) 0x00
- *Parity bit 1, if even.*  
• #define [UART\\_PARITY\\_BIT\\_ODD](#) 0x01
- *Parity bit 1, if odd.*  
• #define [UART\\_PARITY\\_BIT\\_SPACE](#) 0x02
- *Parity bit always 0.*  
• #define [UART\\_PARITY\\_BIT\\_MARK](#) 0x03
- *Parity bit always 1.*  
• #define [UART\\_PARITY\\_BIT\\_USE](#) 0x04
- *None parity.*  
• #define [UART\\_STOP\\_BIT](#) 0x08
- *If set - one stop bit, else two stop bit.*

### Motor Type flags

See also

[motor.settings.t::MotorType](#), [get\\_motor\\_settings](#), [set\\_motor\\_settings](#)

- #define [MOTOR\\_TYPE\\_UNKNOWN](#) 0x00
- *Unknown type of engine.*  
• #define [MOTOR\\_TYPE\\_STEP](#) 0x01
- *Step engine.*  
• #define [MOTOR\\_TYPE\\_DC](#) 0x02
- *DC engine.*  
• #define [MOTOR\\_TYPE\\_BLDC](#) 0x03
- *BLDC engine.*

### Encoder settings flags

See also

[encoder\\_settings\\_t::EncoderSettings](#), [get\\_encoder\\_settings](#), [set\\_encoder\\_settings](#)

- #define [ENCSET\\_DIFFERENTIAL\\_OUTPUT](#) 0x001  
*If flag is set the encoder has differential output, else single ended output.*
- #define [ENCSET\\_PUSHPULL\\_OUTPUT](#) 0x004  
*If flag is set the encoder has push-pull output, else open drain output.*
- #define [ENCSET\\_INDEXCHANNEL\\_PRESENT](#) 0x010  
*If flag is set the encoder has index channel, else encoder hasn't it.*
- #define [ENCSET\\_REOLUTIONSENSOR\\_PRESENT](#) 0x040  
*If flag is set the encoder has revolution sensor, else encoder hasn't it.*
- #define [ENCSET\\_REOLUTIONSENSOR\\_ACTIVE\\_HIGH](#) 0x100  
*If flag is set the revolution sensor active state is high logic state, else active state is low logic state.*

### Magnetic brake settings flags

See also

[accessories\\_settings\\_t::MBSettings](#), [get\\_accessories\\_settings](#), [set\\_accessories\\_settings](#)

- #define [MB\\_AVAILABLE](#) 0x01  
*If flag is set the magnetic brake is available.*
- #define [MB\\_POWERED\\_HOLD](#) 0x02  
*If this flag is set the magnetic brake is on when powered.*

### Temperature sensor settings flags

See also

[accessories\\_settings\\_t::LimitSwitchesSettings](#), [get\\_accessories\\_settings](#), [set\\_accessories\\_settings](#)

- #define [TS\\_TYPE\\_BITS](#) 0x07  
*Bits of the temperature sensor type.*
- #define [TS\\_TYPE\\_UNKNOWN](#) 0x00  
*Unknow type of sensor.*
- #define [TS\\_TYPE\\_THERMOCOUPLE](#) 0x01  
*Thermocouple.*
- #define [TS\\_TYPE\\_SEMICONDUCTOR](#) 0x02  
*The semiconductor temperature sensor.*
- #define [TS\\_AVAILABLE](#) 0x08  
*If flag is set the temperature sensor is available.*
- #define [LS\\_ON\\_SW1\\_AVAILABLE](#) 0x01  
*If flag is set the limit switch connected to pin SW1 is available.*
- #define [LS\\_ON\\_SW2\\_AVAILABLE](#) 0x02  
*If flag is set the limit switch connected to pin SW2 is available.*
- #define [LS\\_SW1\\_ACTIVE\\_LOW](#) 0x04  
*If flag is set the limit switch connected to pin SW1 is triggered by a low level on pin.*
- #define [LS\\_SW2\\_ACTIVE\\_LOW](#) 0x08  
*If flag is set the limit switch connected to pin SW2 is triggered by a low level on pin.*
- #define [LS\\_SHORTED](#) 0x10  
*If flag is set the Limit switches is shorted.*

## Typedefs

- typedef unsigned long long **ulong\_t**
- typedef long long **long\_t**
- typedef int **device\_t**  
*Type describes device identifier.*
- typedef int **result\_t**  
*Type specifies result of any operation.*
- typedef uint32\_t **device\_enumeration\_t**  
*Type describes device enumeration structure.*
- typedef struct **calibration\_t** **calibration\_t**  
*Calibration companion structure.*

## Functions

### Controller settings setup

Functions for adjusting engine read/write almost all controller settings.

- **result\_t** XIMC\_API **set\_feedback\_settings** (**device\_t** id, const **feedback\_settings\_t** \*feedback\_settings)  
*Set feedback settings.*
- **result\_t** XIMC\_API **get\_feedback\_settings** (**device\_t** id, **feedback\_settings\_t** \*feedback\_settings)  
*Read feedback settings.*
- **result\_t** XIMC\_API **set\_home\_settings** (**device\_t** id, const **home\_settings\_t** \*home\_settings)  
*Set home settings.*
- **result\_t** XIMC\_API **set\_home\_settings\_calb** (**device\_t** id, const **home\_settings\_calb\_t** \*home\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **get\_home\_settings** (**device\_t** id, **home\_settings\_t** \*home\_settings)  
*Read home settings.*
- **result\_t** XIMC\_API **get\_home\_settings\_calb** (**device\_t** id, **home\_settings\_calb\_t** \*home\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **set\_move\_settings** (**device\_t** id, const **move\_settings\_t** \*move\_settings)  
*Set command setup movement (speed, acceleration, threshold and etc).*
- **result\_t** XIMC\_API **set\_move\_settings\_calb** (**device\_t** id, const **move\_settings\_calb\_t** \*move\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **get\_move\_settings** (**device\_t** id, **move\_settings\_t** \*move\_settings)  
*Read command setup movement (speed, acceleration, threshold and etc).*
- **result\_t** XIMC\_API **get\_move\_settings\_calb** (**device\_t** id, **move\_settings\_calb\_t** \*move\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **set\_engine\_settings** (**device\_t** id, const **engine\_settings\_t** \*engine\_settings)  
*Set engine settings.*
- **result\_t** XIMC\_API **set\_engine\_settings\_calb** (**device\_t** id, const **engine\_settings\_calb\_t** \*engine\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **get\_engine\_settings** (**device\_t** id, **engine\_settings\_t** \*engine\_settings)  
*Read engine settings.*
- **result\_t** XIMC\_API **get\_engine\_settings\_calb** (**device\_t** id, **engine\_settings\_calb\_t** \*engine\_settings\_calb, const **calibration\_t** \*calibration)
- **result\_t** XIMC\_API **set\_entype\_settings** (**device\_t** id, const **entype\_settings\_t** \*entype\_settings)  
*Set engine type and driver type.*
- **result\_t** XIMC\_API **get\_entype\_settings** (**device\_t** id, **entype\_settings\_t** \*entype\_settings)  
*Return engine type and driver type.*
- **result\_t** XIMC\_API **set\_power\_settings** (**device\_t** id, const **power\_settings\_t** \*power\_settings)  
*Set settings of step motor power control.*
- **result\_t** XIMC\_API **get\_power\_settings** (**device\_t** id, **power\_settings\_t** \*power\_settings)  
*Read settings of step motor power control.*
- **result\_t** XIMC\_API **set\_secure\_settings** (**device\_t** id, const **secure\_settings\_t** \*secure\_settings)  
*Set protection settings.*
- **result\_t** XIMC\_API **get\_secure\_settings** (**device\_t** id, **secure\_settings\_t** \*secure\_settings)

- Read protection settings.*
- [result\\_t XIMC\\_API set\\_edges\\_settings](#) ([device\\_t](#) id, const [edges\\_settings\\_t](#) \*edges\_settings)
- Set border and limit switches settings.*
- [result\\_t XIMC\\_API set\\_edges\\_settings\\_calb](#) ([device\\_t](#) id, const [edges\\_settings\\_calb\\_t](#) \*edges\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API get\\_edges\\_settings](#) ([device\\_t](#) id, [edges\\_settings\\_t](#) \*edges\_settings)
- Read border and limit switches settings.*
- [result\\_t XIMC\\_API get\\_edges\\_settings\\_calb](#) ([device\\_t](#) id, [edges\\_settings\\_calb\\_t](#) \*edges\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API set\\_pid\\_settings](#) ([device\\_t](#) id, const [pid\\_settings\\_t](#) \*pid\_settings)
- Set PID settings.*
- [result\\_t XIMC\\_API get\\_pid\\_settings](#) ([device\\_t](#) id, [pid\\_settings\\_t](#) \*pid\_settings)
- Read PID settings.*
- [result\\_t XIMC\\_API set\\_sync\\_in\\_settings](#) ([device\\_t](#) id, const [sync\\_in\\_settings\\_t](#) \*sync\_in\_settings)
- Set input synchronization settings.*
- [result\\_t XIMC\\_API set\\_sync\\_in\\_settings\\_calb](#) ([device\\_t](#) id, const [sync\\_in\\_settings\\_calb\\_t](#) \*sync\_in\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API get\\_sync\\_in\\_settings](#) ([device\\_t](#) id, [sync\\_in\\_settings\\_t](#) \*sync\_in\_settings)
- Read input synchronization settings.*
- [result\\_t XIMC\\_API get\\_sync\\_in\\_settings\\_calb](#) ([device\\_t](#) id, [sync\\_in\\_settings\\_calb\\_t](#) \*sync\_in\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API set\\_sync\\_out\\_settings](#) ([device\\_t](#) id, const [sync\\_out\\_settings\\_t](#) \*sync\_out\_settings)
- Set output synchronization settings.*
- [result\\_t XIMC\\_API set\\_sync\\_out\\_settings\\_calb](#) ([device\\_t](#) id, const [sync\\_out\\_settings\\_calb\\_t](#) \*sync\_out\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API get\\_sync\\_out\\_settings](#) ([device\\_t](#) id, [sync\\_out\\_settings\\_t](#) \*sync\_out\_settings)
- Read output synchronization settings.*
- [result\\_t XIMC\\_API get\\_sync\\_out\\_settings\\_calb](#) ([device\\_t](#) id, [sync\\_out\\_settings\\_calb\\_t](#) \*sync\_out\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API set\\_extio\\_settings](#) ([device\\_t](#) id, const [extio\\_settings\\_t](#) \*extio\_settings)
- Set EXTIO settings.*
- [result\\_t XIMC\\_API get\\_extio\\_settings](#) ([device\\_t](#) id, [extio\\_settings\\_t](#) \*extio\_settings)
- Read EXTIO settings.*
- [result\\_t XIMC\\_API set\\_brake\\_settings](#) ([device\\_t](#) id, const [brake\\_settings\\_t](#) \*brake\_settings)
- Set settings of brake control.*
- [result\\_t XIMC\\_API get\\_brake\\_settings](#) ([device\\_t](#) id, [brake\\_settings\\_t](#) \*brake\_settings)
- Read settings of brake control.*
- [result\\_t XIMC\\_API set\\_control\\_settings](#) ([device\\_t](#) id, const [control\\_settings\\_t](#) \*control\_settings)
- Set settings of motor control.*
- [result\\_t XIMC\\_API set\\_control\\_settings\\_calb](#) ([device\\_t](#) id, const [control\\_settings\\_calb\\_t](#) \*control\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API get\\_control\\_settings](#) ([device\\_t](#) id, [control\\_settings\\_t](#) \*control\_settings)
- Read settings of motor control.*
- [result\\_t XIMC\\_API get\\_control\\_settings\\_calb](#) ([device\\_t](#) id, [control\\_settings\\_calb\\_t](#) \*control\_settings\_calb, const [calibration\\_t](#) \*calibration)
- [result\\_t XIMC\\_API set\\_joytick\\_settings](#) ([device\\_t](#) id, const [joytick\\_settings\\_t](#) \*joytick\_settings)
- Set settings of joytick.*
- [result\\_t XIMC\\_API get\\_joytick\\_settings](#) ([device\\_t](#) id, [joytick\\_settings\\_t](#) \*joytick\_settings)
- Read settings of joytick.*
- [result\\_t XIMC\\_API set\\_ctp\\_settings](#) ([device\\_t](#) id, const [ctp\\_settings\\_t](#) \*ctp\_settings)
- Set settings of control position(is only used with stepper motor).*
- [result\\_t XIMC\\_API get\\_ctp\\_settings](#) ([device\\_t](#) id, [ctp\\_settings\\_t](#) \*ctp\_settings)
- Read settings of control position(is only used with stepper motor).*
- [result\\_t XIMC\\_API set\\_uart\\_settings](#) ([device\\_t](#) id, const [uart\\_settings\\_t](#) \*uart\_settings)
- Set UART settings.*
- [result\\_t XIMC\\_API get\\_uart\\_settings](#) ([device\\_t](#) id, [uart\\_settings\\_t](#) \*uart\_settings)
- Read UART settings.*
- [result\\_t XIMC\\_API set\\_controller\\_name](#) ([device\\_t](#) id, const [controller\\_name\\_t](#) \*controller\_name)
- Write user controller name and flags of setting from FRAM.*
- [result\\_t XIMC\\_API get\\_controller\\_name](#) ([device\\_t](#) id, [controller\\_name\\_t](#) \*controller\_name)

*Read user controller name and flags of setting from FRAM.*

### Group of commands movement control

- [result\\_t XIMC\\_API command\\_stop \(device\\_t id\)](#)  
*Immediately stop the engine, the transition to the STOP, mode key BREAK (winding short-circuited), the regime "retention" is deactivated for DC motors, keeping current in the windings for stepper motors (with Power management settings).*
- [result\\_t XIMC\\_API set\\_add\\_sync\\_in\\_action \(device\\_t id, const \[add\\\_sync\\\_in\\\_action\\\_t\]\(#\) \\*add\\_sync\\_in\\_action\)](#)  
*This command adds one element of the FIFO commands that are executed when input clock pulse.*
- [result\\_t XIMC\\_API set\\_add\\_sync\\_in\\_action\\_calb \(device\\_t id, const \[add\\\_sync\\\_in\\\_action\\\_calb\\\_t\]\(#\) \\*add\\_sync\\_in\\_action\\_calb, const \[calibration\\\_t\]\(#\) \\*calibration\)](#)
- [result\\_t XIMC\\_API command\\_power\\_off \(device\\_t id\)](#)  
*Immediately power off motor regardless its state.*
- [result\\_t XIMC\\_API command\\_move \(device\\_t id, int Position, int uPosition\)](#)  
*Upon receiving the command "move" the engine starts to move with pre-set parameters (speed, acceleration, retention), to the point specified to the Position, uPosition.*
- [result\\_t XIMC\\_API command\\_move\\_calb \(device\\_t id, float Position, const \[calibration\\\_t\]\(#\) \\*calibration\)](#)
- [result\\_t XIMC\\_API command\\_movr \(device\\_t id, int DeltaPosition, int uDeltaPosition\)](#)  
*Upon receiving the command "movr" engine starts to move with pre-set parameters (speed, acceleration, hold), left or right (depending on the sign of DeltaPosition) by the number of pulses specified in the fields DeltaPosition, uDeltaPosition.*
- [result\\_t XIMC\\_API command\\_movr\\_calb \(device\\_t id, float DeltaPosition, const \[calibration\\\_t\]\(#\) \\*calibration\)](#)
- [result\\_t XIMC\\_API command\\_home \(device\\_t id\)](#)  
*The positive direction is to the right.*
- [result\\_t XIMC\\_API command\\_left \(device\\_t id\)](#)  
*Start continuous moving to the left.*
- [result\\_t XIMC\\_API command\\_right \(device\\_t id\)](#)  
*Start continuous moving to the right.*
- [result\\_t XIMC\\_API command\\_loft \(device\\_t id\)](#)  
*Upon receiving the command "loft" the engine is shifted from the current point to a distance GENG :: Antiploy, then move to the same point.*
- [result\\_t XIMC\\_API command\\_sstp \(device\\_t id\)](#)  
*soft stop engine.*
- [result\\_t XIMC\\_API get\\_position \(device\\_t id, \[get\\\_position\\\_t\]\(#\) \\*the\\_get\\_position\)](#)  
*Reads the value position in steps and micro for stepper motor and encoder steps all engines.*
- [result\\_t XIMC\\_API get\\_position\\_calb \(device\\_t id, \[get\\\_position\\\_calb\\\_t\]\(#\) \\*the\\_get\\_position\\_calb, const \[calibration\\\_t\]\(#\) \\*calibration\)](#)
- [result\\_t XIMC\\_API set\\_position \(device\\_t id, const \[set\\\_position\\\_t\]\(#\) \\*the\\_set\\_position\)](#)  
*Sets any position value in steps and micro for stepper motor and encoder steps of all engines.*
- [result\\_t XIMC\\_API set\\_position\\_calb \(device\\_t id, const \[set\\\_position\\\_calb\\\_t\]\(#\) \\*the\\_set\\_position\\_calb, const \[calibration\\\_t\]\(#\) \\*calibration\)](#)
- [result\\_t XIMC\\_API command\\_zero \(device\\_t id\)](#)  
*Sets the current position and the position in which the traffic moves by the move command and movr zero for all cases, except for movement to the target position.*

### Group of commands to save and load settings

- [result\\_t XIMC\\_API command\\_save\\_settings \(device\\_t id\)](#)  
*Save all settings from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.*
- [result\\_t XIMC\\_API command\\_read\\_settings \(device\\_t id\)](#)  
*Read all settings from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.*
- [result\\_t XIMC\\_API command\\_eesave\\_settings \(device\\_t id\)](#)  
*Save settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.*

- [result\\_t XIMC\\_API command\\_eeread\\_settings](#) ([device\\_t](#) id)  
*Read settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.*
- [result\\_t XIMC\\_API get\\_chart\\_data](#) ([device\\_t](#) id, [chart\\_data\\_t](#) \*chart\_data)  
*Return device electrical parameters, useful for charts.*
- [result\\_t XIMC\\_API get\\_serial\\_number](#) ([device\\_t](#) id, unsigned int \*SerialNumber)  
*Read device serial number.*
- [result\\_t XIMC\\_API get\\_firmware\\_version](#) ([device\\_t](#) id, unsigned int \*Major, unsigned int \*Minor, unsigned int \*Release)  
*Read controller's firmware version.*
- [result\\_t XIMC\\_API service\\_command\\_updf](#) ([device\\_t](#) id)  
*Command puts the controller to update the firmware.*

### Service commands

- [result\\_t XIMC\\_API set\\_serial\\_number](#) ([device\\_t](#) id, const [serial\\_number\\_t](#) \*serial\_number)  
*Write device serial number to controller's flash memory.*
- [result\\_t XIMC\\_API get\\_analog\\_data](#) ([device\\_t](#) id, [analog\\_data\\_t](#) \*analog\_data)  
*Read analog data structure that contains raw analog data from ADC embedded on board.*
- [result\\_t XIMC\\_API get\\_debug\\_read](#) ([device\\_t](#) id, [debug\\_read\\_t](#) \*debug\_read)  
*Read data from firmware for debug purpose.*

### Group of commands to work with EEPROM

- [result\\_t XIMC\\_API set\\_stage\\_name](#) ([device\\_t](#) id, const [stage\\_name\\_t](#) \*stage\_name)  
*Write user stage name from EEPROM.*
- [result\\_t XIMC\\_API get\\_stage\\_name](#) ([device\\_t](#) id, [stage\\_name\\_t](#) \*stage\_name)  
*Read user stage name from EEPROM.*
- [result\\_t XIMC\\_API set\\_stage\\_information](#) ([device\\_t](#) id, const [stage\\_information\\_t](#) \*stage\_information)  
*Set stage information to EEPROM.*
- [result\\_t XIMC\\_API get\\_stage\\_information](#) ([device\\_t](#) id, [stage\\_information\\_t](#) \*stage\_information)  
*Read stage information from EEPROM.*
- [result\\_t XIMC\\_API set\\_stage\\_settings](#) ([device\\_t](#) id, const [stage\\_settings\\_t](#) \*stage\_settings)  
*Set stage settings to EEPROM.*
- [result\\_t XIMC\\_API get\\_stage\\_settings](#) ([device\\_t](#) id, [stage\\_settings\\_t](#) \*stage\_settings)  
*Read stage settings from EEPROM.*
- [result\\_t XIMC\\_API set\\_motor\\_information](#) ([device\\_t](#) id, const [motor\\_information\\_t](#) \*motor\_information)  
*Set motor information to EEPROM.*
- [result\\_t XIMC\\_API get\\_motor\\_information](#) ([device\\_t](#) id, [motor\\_information\\_t](#) \*motor\_information)  
*Read motor information from EEPROM.*
- [result\\_t XIMC\\_API set\\_motor\\_settings](#) ([device\\_t](#) id, const [motor\\_settings\\_t](#) \*motor\_settings)  
*Set motor settings to EEPROM.*
- [result\\_t XIMC\\_API get\\_motor\\_settings](#) ([device\\_t](#) id, [motor\\_settings\\_t](#) \*motor\_settings)  
*Read motor settings from EEPROM.*
- [result\\_t XIMC\\_API set\\_encoder\\_information](#) ([device\\_t](#) id, const [encoder\\_information\\_t](#) \*encoder\_information)  
*Set encoder information to EEPROM.*
- [result\\_t XIMC\\_API get\\_encoder\\_information](#) ([device\\_t](#) id, [encoder\\_information\\_t](#) \*encoder\_information)  
*Read encoder information from EEPROM.*
- [result\\_t XIMC\\_API set\\_encoder\\_settings](#) ([device\\_t](#) id, const [encoder\\_settings\\_t](#) \*encoder\_settings)  
*Set encoder settings to EEPROM.*
- [result\\_t XIMC\\_API get\\_encoder\\_settings](#) ([device\\_t](#) id, [encoder\\_settings\\_t](#) \*encoder\_settings)  
*Read encoder settings from EEPROM.*
- [result\\_t XIMC\\_API set\\_hallsensor\\_information](#) ([device\\_t](#) id, const [hallsensor\\_information\\_t](#) \*hallsensor\_information)  
*Set hall sensor information to EEPROM.*



- Set hall sensor information to EEPROM.*

  - [result\\_t XIMC\\_API get\\_hallsensor\\_information](#) ([device\\_t](#) id, [hallsensor\\_information\\_t](#) \*hallsensor\_information)
- Read hall sensor information from EEPROM.*

  - [result\\_t XIMC\\_API set\\_hallsensor\\_settings](#) ([device\\_t](#) id, const [hallsensor\\_settings\\_t](#) \*hallsensor\_settings)
- Set hall sensor settings to EEPROM.*

  - [result\\_t XIMC\\_API get\\_hallsensor\\_settings](#) ([device\\_t](#) id, [hallsensor\\_settings\\_t](#) \*hallsensor\_settings)
- Read hall sensor settings from EEPROM.*

  - [result\\_t XIMC\\_API set\\_gear\\_information](#) ([device\\_t](#) id, const [gear\\_information\\_t](#) \*gear\_information)
- Set gear information to EEPROM.*

  - [result\\_t XIMC\\_API get\\_gear\\_information](#) ([device\\_t](#) id, [gear\\_information\\_t](#) \*gear\_information)
- Read gear information from EEPROM.*

  - [result\\_t XIMC\\_API set\\_gear\\_settings](#) ([device\\_t](#) id, const [gear\\_settings\\_t](#) \*gear\_settings)
- Set gear settings to EEPROM.*

  - [result\\_t XIMC\\_API get\\_gear\\_settings](#) ([device\\_t](#) id, [gear\\_settings\\_t](#) \*gear\_settings)
- Read gear settings from EEPROM.*

  - [result\\_t XIMC\\_API set\\_accessories\\_settings](#) ([device\\_t](#) id, const [accessories\\_settings\\_t](#) \*accessories\_settings)
- Set additional accessories information to EEPROM.*

  - [result\\_t XIMC\\_API get\\_accessories\\_settings](#) ([device\\_t](#) id, [accessories\\_settings\\_t](#) \*accessories\_settings)
- Read additional accessories information from EEPROM.*

  - [result\\_t XIMC\\_API get\\_bootloader\\_version](#) ([device\\_t](#) id, unsigned int \*Major, unsigned int \*Minor, unsigned int \*Release)
- Read controller's firmware version.*

  - [result\\_t XIMC\\_API goto\\_firmware](#) ([device\\_t](#) id, uint8\_t \*ret)
- Reboot to firmware.*

  - [result\\_t XIMC\\_API has\\_firmware](#) (const char \*name, uint8\_t \*ret)
- Check for firmware on device.*

  - [result\\_t XIMC\\_API command\\_update\\_firmware](#) (const char \*name, const uint8\_t \*data, uint32\_t data\_size)
- Update firmware.*

  - [result\\_t XIMC\\_API write\\_key](#) (const char \*name, uint8\_t \*key)
- Write controller key.*

  - [result\\_t XIMC\\_API command\\_reset](#) ([device\\_t](#) id)
- Reset controller.*

  - [result\\_t XIMC\\_API command\\_clear\\_fram](#) ([device\\_t](#) id)
- Clear controller FRAM.*

## Boards and drivers control

### Functions for searching and opening/closing devices

- typedef char \* [pchar](#)
  - Nevermind.*
- typedef void([XIMC\\_CALLCONV](#) \* [logging\\_callback\\_t](#) )(int loglevel, const wchar\_t \*message)
  - Logging callback prototype.*
- [device\\_t XIMC\\_API open\\_device](#) (const char \*name)
  - Open a device with OS name name and return identifier of the device which can be used in calls.*
- [result\\_t XIMC\\_API close\\_device](#) ([device\\_t](#) \*id)
  - Close specified device.*
- [result\\_t XIMC\\_API probe\\_device](#) (const char \*name)
  - Check if a device with OS name name is XIMC device.*
- [device\\_enumeration\\_t XIMC\\_API enumerate\\_devices](#) (int probe\_flags)
  - Enumerate all devices that looks like valid.*
- [result\\_t XIMC\\_API free\\_enumerate\\_devices](#) ([device\\_enumeration\\_t](#) device\_enumeration)
  - Free memory returned by enumerate\_devices.*
- int [XIMC\\_API get\\_device\\_count](#) ([device\\_enumeration\\_t](#) device\_enumeration)



- Get device count.*
  - `pchar XIMC_API get_device_name (device_enumeration_t device_enumeration, int device_index)`
- Get device name from the device enumeration.*
  - `result_t XIMC_API get_enumerate_device_serial (device_enumeration_t device_enumeration, int device_index, uint32_t *serial)`
- Get device serial number from the device enumeration.*
  - `result_t XIMC_API get_enumerate_device_information (device_enumeration_t device_enumeration, int device_index, device_information_t *device_information)`
- Get device information from the device enumeration.*
  - `result_t XIMC_API reset_locks ()`
- Reset library locks in a case of deadlock.*
  - `result_t XIMC_API ximc_fix_usbser_sys (const char *device_name)`
- Fix for errors in Windows USB driver stack.*
  - `void XIMC_API msec_sleep (unsigned int msec)`
- Sleeps for a specified amount of time.*
  - `void XIMC_API ximc_version (char *version)`
- Returns a library version.*
  - `void XIMC_API logging_callback_stderr_wide (int loglevel, const wchar_t *message)`
- Simple callback for logging to stderr in wide chars.*
  - `void XIMC_API logging_callback_stderr_narrow (int loglevel, const wchar_t *message)`
- Simple callback for logging to stderr in narrow (single byte) chars.*
  - `void XIMC_API set_logging_callback (logging_callback_t logging_callback)`
- Sets a logging callback.*
  - `result_t XIMC_API get_status (device_t id, status_t *status)`
- Return device state.*
  - `result_t XIMC_API get_status_calb (device_t id, status_calb_t *status, const calibration_t *calibration)`
- Calibrated device state.*
  - `result_t XIMC_API get_device_information (device_t id, device_information_t *device_information)`
- Return device information.*

### 5.1.1 Detailed Description

Header file for libximc library.

### 5.1.2 Macro Definition Documentation

#### 5.1.2.1 `#define BORDERS_SWAP_MISSET_DETECTION 0x08`

Motor should stop on both borders.

Need to save motor then wrong border settings is set

#### 5.1.2.2 `#define DRIVER_TYPE_DISCRETE_FET 0x01`

Driver with discrete FET keys.

Default option.

#### 5.1.2.3 `#define ENGINE_ACCEL_ON 0x10`

Acceleration enable flag.

If it set, motion begins with acceleration and ends with deceleration.

5.1.2.4 `#define ENGINE_ANTIPLAY 0x08`

Play compensation flag.

If it set, engine makes backlash (play) compensation procedure and reach the predetermined position accurately on low speed.

5.1.2.5 `#define ENGINE_MAX_SPEED 0x04`

Max speed flag.

If it is set, engine uses maximum speed achievable with the present engine settings as nominal speed.

5.1.2.6 `#define ENGINE_REVERSE 0x01`

Reverse flag.

It determines motor shaft rotation direction that corresponds to feedback counts increasing. If not set (default), motor shaft rotation direction under positive voltage corresponds to feedback counts increasing and vice versa. Change it if you see that positive directions on motor and feedback are opposite.

5.1.2.7 `#define ENGINE_TYPE_TEST 0x04`

Duty cycle are fixed.

Used only manufacturer.

5.1.2.8 `#define ENUMERATE_PROBE 0x01`

Check if a device with OS name name is XIMC device.

Be carefully with this flag because it sends some data to the device.

5.1.2.9 `#define EXTIO_SETUP_INVERT 0x02`

Interpret EXTIO states and fronts inverted if flag is set.

Falling front as input event and low logic level as active state.

5.1.2.10 `#define HOME_DIR_FIRST 0x01`

Flag defines direction of 1st motion after execution of home command.

Direction is right, if set; otherwise left.

5.1.2.11 `#define HOME_DIR_SECOND 0x02`

Flag defines direction of 2nd motion.

Direction is right, if set; otherwise left.

5.1.2.12 `#define JOY_REVERSE 0x01`

Joystick action is reversed.

Joystick deviation to the upper values correspond to negative speeds and vice versa.

5.1.2.13 `#define MVCMD_ERROR 0x40`

Finish state (1 - move command have finished with an error, 0 - move command have finished correctly).

This flags is actual when MVCMD\_RUNNING signals movement finish.

5.1.2.14 `#define REV_SENS_INV 0x08`

Sensor is active when it 0 and invert makes active level 1.

That is, if you do not invert, it is normal logic - 0 is the activation.

5.1.2.15 `#define STATE_ALARM 0x00040`

Controller is in alarm state indicating that something dangerous had happened.

Most commands are ignored in this state. To reset the flag a STOP command must be issued.

5.1.2.16 `#define SYNCIN_GOTOPOSITION 0x04`

The engine is go to position specified in Position and uPosition, if this flag is set.

And it is shift on the Position and uPosition, if this flag is unset

5.1.2.17 `#define SYNCOUT_ENABLED 0x01`

Synchronization out pin follows the synchronization logic, if set.

It governed by SYNCOUT\_STATE flag otherwise.

5.1.2.18 `#define XIMC_API`

Library import macro Macros allows to automatically import function from shared library.

It automatically expands to `__declspec(dllexport)` on `msvc` when including header file

## 5.1.3 Typedef Documentation

5.1.3.1 `typedef void(XIMC_CALLCONV * logging_callback_t)(int loglevel, const wchar_t *message)`

Logging callback prototype.

Parameters

|                 |            |
|-----------------|------------|
| <i>loglevel</i> | a loglevel |
| <i>message</i>  | a message  |

## 5.1.4 Function Documentation

5.1.4.1 `result_t XIMC_API close_device ( device_t * id )`

Close specified device.

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.2 **result\_t XIMC\_API** command\_clear\_fram ( **device\_t id** )

Clear controller FRAM.

Can be used by manufacturer only

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.3 **result\_t XIMC\_API** command\_eeread\_settings ( **device\_t id** )

Read settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.4 **result\_t XIMC\_API** command\_eesave\_settings ( **device\_t id** )

Save settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.

Can be used by manufacturer only.

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.5 **result\_t XIMC\_API** command\_home ( **device\_t id** )

The positive direction is to the right.

A value of zero reverses the direction of the direction of the flag, the set speed. Restriction imposed by the trailer, act the same, except that the limit switch contact does not stop. Limit the maximum speed, acceleration and deceleration function. 1) moves the motor according to the speed FastHome, uFastHome and flag HOME.DIR.-FAST until limit switch, if the flag is set HOME.STOP.ENDS, until the signal from the input synchronization if the flag HOME.STOP.SYNC (as accurately as possible is important to catch the moment of operation limit switch) or until the signal is received from the speed sensor, if the flag HOME.STOP.REV.SN 2) then moves according to the speed SlowHome, uSlowHome and flag HOME.DIR.SLOW until signal from the clock input, if the flag HOME.MV.SEC. If the flag HOME.MV.SEC reset skip this paragraph. 3) then move the motor according to the speed FastHome, uFastHome and flag HOME.DIR.SLOW a distance HomeDelta, uHomeDelta. description of flags and variable see in description for commands GHOM/SHOM

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

See also

[home\\_settings\\_t](#)  
[get\\_home\\_settings](#)  
[set\\_home\\_settings](#)

#### 5.1.4.6 **result\_t XIMC\_API** command\_loft ( **device\_t** id )

Start continous moving to the left.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.7 **result\_t XIMC\_API** command\_loft ( **device\_t** id )

Upon receiving the command "loft" the engine is shifted from the current point to a distance GENG :: Antiplay, then move to the same point.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.8 **result\_t XIMC\_API** command\_move ( **device\_t** id, int Position, int uPosition )

Upon receiving the command "move" the engine starts to move with pre-set parameters (speed, acceleration, retention), to the point specified to the Position, uPosition.

For stepper motor uPosition sets the microstep for DC motor, this field is not used.

Parameters

|                  |   |
|------------------|---|
| <i>Position</i>  | position to move. Range: -2147483647..2147483647.           |
| <i>uPosition</i> | part of the position to move, microsteps. Range: -255..255. |
| <i>id</i>        | an identifier of device                                     |

#### 5.1.4.9 **result\_t XIMC\_API** command\_movr ( **device\_t** id, int DeltaPosition, int uDeltaPosition )

Upon receiving the command "movr" engine starts to move with pre-set parameters (speed, acceleration, hold), left or right (depending on the sign of DeltaPosition) by the number of pulses specified in the fields DeltaPosition, uDeltaPosition.

For stepper motor uDeltaPosition sets the microstep for DC motor, this field is not used.

Parameters

|                       |  |
|-----------------------|--|
| <i>DeltaPosition</i>  | shift from initial position. Range: -2147483647..2147483647. |
| <i>uDeltaPosition</i> | part of the offset shift, microsteps. Range: -255..255.      |
| <i>id</i>             | an identifier of device                                      |

#### 5.1.4.10 **result\_t XIMC\_API** command\_power\_off ( **device\_t** id )

Immediately power off motor regardless its state.

Shouldn't be used during motion as the motor could be power on again automatically to continue movement. The command is designed for manual motor power off. When automatic power off after stop is required, use power management system.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

See also

[get\\_power\\_settings](#)  
[set\\_power\\_settings](#)

#### 5.1.4.11 **result\_t XIMC\_API** command\_read\_settings ( **device\_t** id )

Read all settings from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.12 **result\_t XIMC\_API** command\_reset ( **device\_t** id )

Reset controller.

Can be used by manufacturer only

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.13 **result\_t XIMC\_API** command\_right ( **device\_t** id )

Start continuous moving to the right.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.14 **result\_t XIMC\_API** command\_save\_settings ( **device\_t** id )

Save all settings from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.

Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

#### 5.1.4.15 **result\_t XIMC\_API** command\_sstp ( **device\_t** id )

soft stop engine.

The motor stops with deceleration speed.

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.16 **result\_t XIMC\_API** command\_stop ( **device\_t** id )

Immediately stop the engine, the transition to the STOP, mode key BREAK (winding short-circuited), the regime "retention" is deactivated for DC motors, keeping current in the windings for stepper motors (with Power management settings).

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.17 **result\_t XIMC\_API** command\_update\_firmware ( const char \* name, const uint8\_t \* data, uint32\_t data\_size )

Update firmware.

Service command

## Parameters

|                  |                      |
|------------------|----------------------|
| <i>name</i>      | a name of device     |
| <i>data</i>      | firmware byte stream |
| <i>data_size</i> | size of byte stream  |

5.1.4.18 **result\_t XIMC\_API** command\_zero ( **device\_t** id )

Sets the current position and the position in which the traffic moves by the move command and movr zero for all cases, except for movement to the target position.

In the latter case, set the zero current position and the target position counted so that the absolute position of the destination is the same. That is, if we were at 400 and moved to 500, then the command Zero makes the current position of 0, and the position of the destination - 100. Does not change the mode of movement that is if the motion is carried, it continues, and if the engine is in the "hold", the type of retention remains.

## Parameters

|           |                         |
|-----------|-------------------------|
| <i>id</i> | an identifier of device |
|-----------|-------------------------|

5.1.4.19 **device\_enumeration\_t XIMC\_API** enumerate\_devices ( int probe\_flags )

Enumerate all devices that looks like valid.

## Parameters

|           |                    |                         |
|-----------|--------------------|-------------------------|
| <i>in</i> | <i>probe_flags</i> | enumerate devices flags |
|-----------|--------------------|-------------------------|

5.1.4.20 **result\_t XIMC\_API** free\_enumerate\_devices ( **device\_enumeration\_t** device\_enumeration )

Free memory returned by *enumerate\_devices*.

## Parameters

|    |                           |  |
|----|---------------------------|--|
| in | <i>device_Enumeration</i> | opaque pointer to an enumeration device data |
|----|---------------------------|--|

5.1.4.21 **result\_t XIMC\_API** get\_accessories\_settings ( **device\_t** id, **accessories\_settings\_t** \* accessories\_settings )

Read additional accessories information from EEPROM.

## Parameters

|     |                             |   |
|-----|-----------------------------|---|
|     | <i>id</i>                   | an identifier of device                                     |
| out | <i>accessories_settings</i> | structure contains information about additional accessories |

5.1.4.22 **result\_t XIMC\_API** get\_analog\_data ( **device\_t** id, **analog\_data\_t** \* analog\_data )

Read analog data structure that contains raw analog data from ADC embedded on board.

This function used for device testing and deep recalibration by manufacturer only.

## Parameters

|     |                    |                          |
|-----|--------------------|--------------------------|
|     | <i>id</i>          | an identifier of device  |
| out | <i>analog_data</i> | analog data coefficients |

5.1.4.23 **result\_t XIMC\_API** get\_bootloader\_version ( **device\_t** id, unsigned int \* Major, unsigned int \* Minor, unsigned int \* Release )

Read controller's firmware version.

## Parameters

|     |                |                         |
|-----|----------------|-------------------------|
|     | <i>id</i>      | an identifier of device |
| out | <i>Major</i>   | major version           |
| out | <i>Minor</i>   | minor version           |
| out | <i>Release</i> | release version         |

5.1.4.24 **result\_t XIMC\_API** get\_brake\_settings ( **device\_t** id, **brake\_settings\_t** \* brake\_settings )

Read settings of brake control.

## Parameters

|     |                       |  |
|-----|-----------------------|--|
|     | <i>id</i>             | an identifier of device                      |
| out | <i>brake_settings</i> | structure contains settings of brake control |

5.1.4.25 **result\_t XIMC\_API** get\_chart\_data ( **device\_t** id, **chart\_data\_t** \* chart\_data )

Return device electrical parameters, useful for charts.

Useful function that fill structure with snapshot of controller voltages and currents.



See also

[chart\\_data.t](#)

Parameters

|     |                   |   |
|-----|-------------------|---|
|     | <i>id</i>         | an identifier of device                           |
| out | <i>chart_data</i> | structure with snapshot of controller parameters. |

5.1.4.26 **result\_t XIMC\_API** get\_control\_settings ( **device\_t** id, **control\_settings\_t** \* control\_settings )

Read settings of motor control.

When choosing CTL\_MODE = 1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i = 0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL\_MODE = 2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout [i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i +1] to acceleration, as usual.

Parameters

|     |                         |  |
|-----|-------------------------|--|
|     | <i>id</i>               | an identifier of device  |
| out | <i>control_settings</i> | structure contains settings motor control by joystick or buttons left/right. |

5.1.4.27 **result\_t XIMC\_API** get\_controller\_name ( **device\_t** id, **controller\_name\_t** \* controller\_name )

Read user controller name and flags of setting from FRAM.

Parameters

|     |                        |  |
|-----|------------------------|--|
|     | <i>id</i>              | an identifier of device                                |
| out | <i>controller_name</i> | structure contains previously set user controller name |

5.1.4.28 **result\_t XIMC\_API** get\_ctp\_settings ( **device\_t** id, **ctp\_settings\_t** \* ctp\_settings )

Read settings of control position(is only used with stepper motor).

When controlling the step motor with encoder (CTP\_BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP\_ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is greater CTPMinError, a flag STATE\_CTP\_ERROR. When controlling the step motor with speed sensor (CTP\_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE\_CTP\_ERROR.

Parameters

|     |                     |   |
|-----|---------------------|---|
|     | <i>id</i>           | an identifier of device                         |
| out | <i>ctp_settings</i> | structure contains settings of control position |

5.1.4.29 **result\_t XIMC\_API** get\_debug\_read ( **device\_t** id, **debug\_read\_t** \* debug\_read )

Read data from firmware for debug purpose.

Its use depends on context, firmware version and previous history.

Parameters

|     |                       |                         |
|-----|-----------------------|-------------------------|
|     | <i>id</i>             | an identifier of device |
| out | <i>DebugData[128]</i> | Debug data.             |

5.1.4.30 **int** **XIMC\_API** get\_device\_count ( **device\_enumeration\_t** device\_enumeration )

Get device count.

Parameters

|    |                           |  |
|----|---------------------------|--|
| in | <i>device_enumeration</i> | opaque pointer to an enumeration device data |
|----|---------------------------|--|

5.1.4.31 **result\_t** **XIMC\_API** get\_device\_information ( **device\_t** id, **device\_information\_t** \* device\_information )

Return device information.

All fields must point to allocated string buffers with at least 10 bytes. Works with both raw or initialized device.

Parameters

|     |                           |  |
|-----|---------------------------|--|
|     | <i>id</i>                 | an identifier of device                |
| out | <i>device_information</i> | device information Device information. |

See also

[get\\_device\\_information](#)

5.1.4.32 **pchar** **XIMC\_API** get\_device\_name ( **device\_enumeration\_t** device\_enumeration, int device\_index )

Get device name from the device enumeration.

Returns *device\_index* device name.

Parameters

|    |                           |  |
|----|---------------------------|--|
| in | <i>device_enumeration</i> | opaque pointer to an enumeration device data |
| in | <i>device_index</i>       | device index                                 |

5.1.4.33 **result\_t** **XIMC\_API** get\_edges\_settings ( **device\_t** id, **edges\_settings\_t** \* edges\_settings )

Read border and limit switches settings.

See also

[set\\_edges\\_settings](#)

## Parameters

|     |                       |  |
|-----|-----------------------|--|
|     | <i>id</i>             | an identifier of device  |
| out | <i>edges_settings</i> | edges settings, specify types of borders, motor behaviour and electrical behaviour of limit switches |

5.1.4.34 **result\_t XIMC\_API** get\_encoder\_information ( **device\_t** id, **encoder\_information\_t** \* encoder\_information )

Read encoder information from EEPROM.

## Parameters

|     |                            |  |
|-----|----------------------------|--|
|     | <i>id</i>                  | an identifier of device                      |
| out | <i>encoder_information</i> | structure contains information about encoder |

5.1.4.35 **result\_t XIMC\_API** get\_encoder\_settings ( **device\_t** id, **encoder\_settings\_t** \* encoder\_settings )

Read encoder settings from EEPROM.

## Parameters

|     |                         |                                     |
|-----|-------------------------|-------------------------------------|
|     | <i>id</i>               | an identifier of device             |
| out | <i>encoder_settings</i> | structure contains encoder settings |

5.1.4.36 **result\_t XIMC\_API** get\_engine\_settings ( **device\_t** id, **engine\_settings\_t** \* engine\_settings )

Read engine settings.

This function fill structure with set of useful motor settings stored in controller's memory. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics.

See also

[set\\_engine\\_settings](#)

## Parameters

|     |                        |                         |
|-----|------------------------|-------------------------|
|     | <i>id</i>              | an identifier of device |
| out | <i>engine_settings</i> | engine settings         |

5.1.4.37 **result\_t XIMC\_API** get\_entype\_settings ( **device\_t** id, **entype\_settings\_t** \* entype\_settings )

Return engine type and driver type.

## Parameters

|     |                   |                         |
|-----|-------------------|-------------------------|
|     | <i>id</i>         | an identifier of device |
| out | <i>EngineType</i> | engine type             |
| out | <i>DriverType</i> | driver type             |

5.1.4.38 **result\_t XIMC\_API** get\_enumerate\_device\_information ( **device\_enumeration\_t** device\_enumeration, int device\_index, **device\_information\_t** \* device\_information )

Get device information from the device enumeration.

Returns *device\_index* device serial number.

Parameters

|     |                           |  |
|-----|---------------------------|--|
| in  | <i>device_enumeration</i> | opaque pointer to an enumeration device data |
| in  | <i>device_index</i>       | device index                                 |
| out | <i>device_information</i> | device information data                      |

5.1.4.39 **result\_t XIMC\_API** get\_enumerate\_device\_serial ( **device\_enumeration\_t** device\_enumeration, int device\_index, uint32\_t \* serial )

Get device serial number from the device enumeration.

Returns *device\_index* device serial number.

Parameters

|     |                           |  |
|-----|---------------------------|--|
| in  | <i>device_enumeration</i> | opaque pointer to an enumeration device data |
| in  | <i>device_index</i>       | device index                                 |
| out | <i>serial</i>             | device serial number                         |

5.1.4.40 **result\_t XIMC\_API** get\_extio\_settings ( **device\_t** id, **extio\_settings\_t** \* extio\_settings )

Read EXTIO settings.

This function reads a structure with a set of EXTIO settings from controller's memory.

See also

[set\\_extio\\_settings](#)

Parameters

|     |                       |                         |
|-----|-----------------------|-------------------------|
|     | <i>id</i>             | an identifier of device |
| out | <i>extio_settings</i> | EXTIO settings          |

5.1.4.41 **result\_t XIMC\_API** get\_feedback\_settings ( **device\_t** id, **feedback\_settings\_t** \* feedback\_settings )

Read feedback settings.

Parameters

|     |                      |  |
|-----|----------------------|--|
|     | <i>id</i>            | an identifier of device  |
| out | <i>IPS</i>           | number of encoder pulses per shaft revolution. Range: 1..65535 |
| out | <i>FeedbackType</i>  | type of feedback   |
| out | <i>FeedbackFlags</i> | flags of feedback  |

5.1.4.42 **result\_t XIMC\_API** get\_firmware\_version ( **device\_t** id, unsigned int \* Major, unsigned int \* Minor, unsigned int \* Release )

Read controller's firmware version.

Parameters

|     |                |                         |
|-----|----------------|-------------------------|
|     | <i>id</i>      | an identifier of device |
| out | <i>Major</i>   | major version           |
| out | <i>Minor</i>   | minor version           |
| out | <i>Release</i> | release version         |

5.1.4.43 **result\_t XIMC\_API** get\_gear\_information ( **device\_t** id, **gear\_information\_t** \* gear\_information )

Read gear information from EEPROM.

Parameters

|     |                         |  |
|-----|-------------------------|--|
|     | <i>id</i>               | an identifier of device                            |
| out | <i>gear_information</i> | structure contains information about step gearhead |

5.1.4.44 **result\_t XIMC\_API** get\_gear\_settings ( **device\_t** id, **gear\_settings\_t** \* gear\_settings )

Read gear settings from EEPROM.

Parameters

|     |                      |   |
|-----|----------------------|---|
|     | <i>id</i>            | an identifier of device                   |
| out | <i>gear_settings</i> | structure contains step gearhead settings |

5.1.4.45 **result\_t XIMC\_API** get\_hallsensor\_information ( **device\_t** id, **hallsensor\_information\_t** \* hallsensor\_information )

Read hall sensor information from EEPROM.

Parameters

|     |                               |  |
|-----|-------------------------------|--|
|     | <i>id</i>                     | an identifier of device                          |
| out | <i>hallsensor_information</i> | structure contains information about hall sensor |

5.1.4.46 **result\_t XIMC\_API** get\_hallsensor\_settings ( **device\_t** id, **hallsensor\_settings\_t** \* hallsensor\_settings )

Read hall sensor settings from EEPROM.

Parameters

|     |                            |   |
|-----|----------------------------|---|
|     | <i>id</i>                  | an identifier of device                 |
| out | <i>hallsensor_settings</i> | structure contains hall sensor settings |

5.1.4.47 **result\_t XIMC\_API** get\_home\_settings ( **device\_t** id, **home\_settings\_t** \* home\_settings )

Read home settings.

This function fill structure with settings of calibrating position.

See also



[home\\_settings\\_t](#)

Parameters

|     |                      |                               |
|-----|----------------------|-------------------------------|
|     | <i>id</i>            | an identifier of device       |
| out | <i>home_settings</i> | calibrating position settings |

5.1.4.48 **result\_t XIMC\_API** get\_joystick\_settings ( **device\_t** id, **joystick\_settings\_t** \* joystick\_settings )

Read settings of joystick.

If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The DeadZone ranges are illustrated on the following picture.  The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy. The following picture illustrates this:  The nonlinearity parameter is adjustable. Setting it to zero makes deviation/speed relation linear.

Parameters

|     |                          |                                      |
|-----|--------------------------|--------------------------------------|
|     | <i>id</i>                | an identifier of device              |
| out | <i>joystick_settings</i> | structure contains joystick settings |

5.1.4.49 **result\_t XIMC\_API** get\_motor\_information ( **device\_t** id, **motor\_information\_t** \* motor\_information )

Read motor information from EEPROM.

Parameters

|     |                          |                                      |
|-----|--------------------------|--------------------------------------|
|     | <i>id</i>                | an identifier of device              |
| out | <i>motor_information</i> | structure contains motor information |

5.1.4.50 **result\_t XIMC\_API** get\_motor\_settings ( **device\_t** id, **motor\_settings\_t** \* motor\_settings )

Read motor settings from EEPROM.

Parameters

|     |                       |                                   |
|-----|-----------------------|-----------------------------------|
|     | <i>id</i>             | an identifier of device           |
| out | <i>motor_settings</i> | structure contains motor settings |

5.1.4.51 **result\_t XIMC\_API** get\_move\_settings ( **device\_t** id, **move\_settings\_t** \* move\_settings )

Read command setup movement (speed, acceleration, threshold and etc).

Parameters

|     |                      |  |
|-----|----------------------|--|
|     | <i>id</i>            | an identifier of device  |
| out | <i>move_settings</i> | structure contains move settings: speed, acceleration, deceleration etc. |

5.1.4.52 **result\_t XIMC\_API** get\_pid\_settings ( **device\_t** id, **pid\_settings\_t** \* pid\_settings )

Read PID settings.

This function fill structure with set of motor PID settings stored in controller's memory. These settings specify behaviour of PID routine for voltage. These factors are slightly different for different positioners. All boards are supplied with standart set of PID setting on controller's flash memory.

See also

[set\\_pid\\_settings](#)

Parameters

|     |                     |                         |
|-----|---------------------|-------------------------|
|     | <i>id</i>           | an identifier of device |
| out | <i>pid_settings</i> | pid settings            |

5.1.4.53 **result\_t XIMC\_API** get\_position ( **device\_t** id, **get\_position\_t** \* the\_get\_position )

Reads the value position in steps and micro for stepper motor and encoder steps all engines.

Parameters

|     |                 |  |
|-----|-----------------|--|
|     | <i>id</i>       | an identifier of device  |
| out | <i>position</i> | structure contains move settings: speed, acceleration, deceleration etc. |

5.1.4.54 **result\_t XIMC\_API** get\_power\_settings ( **device\_t** id, **power\_settings\_t** \* power\_settings )

Read settings of step motor power control.

Used with stepper motor only.

Parameters

|     |                       |   |
|-----|-----------------------|---|
|     | <i>id</i>             | an identifier of device                                 |
| out | <i>power_settings</i> | structure contains settings of step motor power control |

5.1.4.55 **result\_t XIMC\_API** get\_secure\_settings ( **device\_t** id, **secure\_settings\_t** \* secure\_settings )

Read protection settings.

Parameters

|     |                        |   |
|-----|------------------------|---|
|     | <i>id</i>              | an identifier of device                             |
| out | <i>secure_settings</i> | critical parameter settings to protect the hardware |

See also

`status_t::flags`

5.1.4.56 **result\_t XIMC\_API** `get_serial_number ( device_t id, unsigned int * SerialNumber )`

Read device serial number.

Parameters

|     |               |                         |
|-----|---------------|-------------------------|
|     | <i>id</i>     | an identifier of device |
| out | <i>serial</i> | serial number           |

5.1.4.57 **result\_t XIMC\_API** `get_stage_information ( device_t id, stage_information_t * stage_information )`

Read stage information from EEPROM.

Parameters

|     |                          |                                      |
|-----|--------------------------|--------------------------------------|
|     | <i>id</i>                | an identifier of device              |
| out | <i>stage-information</i> | structure contains stage information |

5.1.4.58 **result\_t XIMC\_API** `get_stage_name ( device_t id, stage_name_t * stage_name )`

Read user stage name from EEPROM.

Parameters

|     |                   |   |
|-----|-------------------|---|
|     | <i>id</i>         | an identifier of device                           |
| out | <i>stage_name</i> | structure contains previously set user stage name |

5.1.4.59 **result\_t XIMC\_API** `get_stage_settings ( device_t id, stage_settings_t * stage_settings )`

Read stage settings from EEPROM.

Parameters

|     |                       |                                   |
|-----|-----------------------|-----------------------------------|
|     | <i>id</i>             | an identifier of device           |
| out | <i>stage_settings</i> | structure contains stage settings |

5.1.4.60 **result\_t XIMC\_API** `get_status ( device_t id, status_t * status )`

Return device state.

Parameters

|     |               |   |
|-----|---------------|---|
|     | <i>id</i>     | an identifier of device   |
| out | <i>status</i> | structure with snapshot of controller status Device state. Useful structure that contains current controller status, including speed, position and boolean flags. |



See also

[get\\_status](#)

5.1.4.61 **result\_t XIMC\_API** `get_status_calb ( device_t id, status_calb_t * status, const calibration_t * calibration )`

Calibrated device state.

Useful structure that contains current controller status, including speed, position and boolean flags.

See also

[get\\_status](#)

5.1.4.62 **result\_t XIMC\_API** `get_sync_in_settings ( device_t id, sync_in_settings_t * sync_in_settings )`

Read input synchronization settings.

This function fill structure with set of input synchronization settings, modes, periods and flags, that specify behaviour of input synchronization. All boards are supplied with standart set of these settings.

See also

[set\\_sync\\_in\\_settings](#)

Parameters

|     |                         |                          |
|-----|-------------------------|--------------------------|
|     | <i>id</i>               | an identifier of device  |
| out | <i>sync_in_settings</i> | synchronization settings |

5.1.4.63 **result\_t XIMC\_API** `get_sync_out_settings ( device_t id, sync_out_settings_t * sync_out_settings )`

Read output synchronization settings.

This function fill structure with set of output synchronization settings, modes, periods and flags, that specify behaviour of output synchronization. All boards are supplied with standart set of these settings.

See also

[set\\_sync\\_out\\_settings](#)

Parameters

|     |                          |                          |
|-----|--------------------------|--------------------------|
|     | <i>id</i>                | an identifier of device  |
| out | <i>sync_out_settings</i> | synchronization settings |

5.1.4.64 **result\_t XIMC\_API** `get_uart_settings ( device_t id, uart_settings_t * uart_settings )`

Read UART settings.

This function fill structure with UART settings.

See also

[uart\\_settings.t](#)

Parameters

|     |                      |               |
|-----|----------------------|---------------|
|     | <i>Speed</i>         | UART speed    |
| out | <i>uart_settings</i> | UART settings |

5.1.4.65 **result\_t XIMC\_API** goto\_firmware ( **device\_t** id, uint8\_t \* ret )

Reboot to firmware.

Parameters

|     |            |   |
|-----|------------|---|
|     | <i>id</i>  | an identifier of device   |
| out | <i>ret</i> | RESULT_OK, if reboot to firmware is possible. Reboot is done after reply to this command. RESULT_NO_FIRMWARE, if firmware is not found. RESULT_ALR-EADY_IN_FIRMWARE, if this command was sent when controller is already in firmware. |

5.1.4.66 **result\_t XIMC\_API** has\_firmware ( const char \* name, uint8\_t \* ret )

Check for firmware on device.

Parameters

|     |             |                              |
|-----|-------------|------------------------------|
|     | <i>name</i> | a name of device             |
| out | <i>ret</i>  | non-zero if firmware existed |

5.1.4.67 **void XIMC\_API** logging\_callback\_stderr\_narrow ( int loglevel, const wchar\_t \* message )

Simple callback for logging to stderr in narrow (single byte) chars.

Parameters

|                 |            |
|-----------------|------------|
| <i>loglevel</i> | a loglevel |
| <i>message</i>  | a message  |

5.1.4.68 **void XIMC\_API** logging\_callback\_stderr\_wide ( int loglevel, const wchar\_t \* message )

Simple callback for logging to stderr in wide chars.

Parameters

|                 |            |
|-----------------|------------|
| <i>loglevel</i> | a loglevel |
| <i>message</i>  | a message  |

5.1.4.69 **void XIMC\_API** msec\_sleep ( unsigned int msec )

Sleeps for a specified amount of time.

## Parameters

|             |                      |
|-------------|----------------------|
| <i>msec</i> | time in milliseconds |
|-------------|----------------------|

5.1.4.70 **device\_t XIMC\_API** open\_device ( const char \* name )

Open a device with OS name *name* and return identifier of the device which can be used in calls.

## Parameters

|    |             |  |
|----|-------------|--|
| in | <i>name</i> | - a device name - e.g. COM3 or /dev/tty.s123 |
|----|-------------|--|

5.1.4.71 **result\_t XIMC\_API** probe\_device ( const char \* name )

Check if a device with OS name *name* is XIMC device.

Be carefully with this call because it sends some data to the device.

## Parameters

|    |             |                 |
|----|-------------|-----------------|
| in | <i>name</i> | - a device name |
|----|-------------|-----------------|

5.1.4.72 **result\_t XIMC\_API** service\_command\_updf ( **device\_t** id )

Command puts the controller to update the firmware.

After receiving this command, the firmware board sets a flag (for loader), sends echo reply and restarts the controller.

5.1.4.73 **result\_t XIMC\_API** set\_accessories\_settings ( **device\_t** id, const **accessories\_settings\_t** \* accessories\_settings )

Set additional accessories information to EEPROM.

Can be used by manufacturer only.

## Parameters

|    |                             |   |
|----|-----------------------------|---|
|    | <i>id</i>                   | an identifier of device                                     |
| in | <i>accessories_settings</i> | structure contains information about additional accessories |

5.1.4.74 **result\_t XIMC\_API** set\_add\_sync\_in\_action ( **device\_t** id, const **add\_sync\_in\_action\_t** \* add\_sync\_in\_action )

This command adds one element of the FIFO commands that are executed when input clock pulse.

Each pulse synchronization or perform that action, which is described in SSNI, if the buffer is empty, or the oldest loaded into the buffer action to temporarily replace the speed and coordinate in SSNI. In the latter case this action is erased from the buffer. The number of remaining empty buffer elements can be found in the structure of GETS.

## Parameters

|  |           |                         |
|--|-----------|-------------------------|
|  | <i>id</i> | an identifier of device |
|--|-----------|-------------------------|

5.1.4.75 **result\_t XIMC\_API** set\_brake\_settings ( **device\_t** id, const **brake\_settings\_t** \* brake\_settings )

Set settings of brake control.

Parameters

|    |                       |  |
|----|-----------------------|--|
|    | <i>id</i>             | an identifier of device                      |
| in | <i>brake_settings</i> | structure contains settings of brake control |

5.1.4.76 **result\_t XIMC\_API** set\_control\_settings ( **device\_t** id, const **control\_settings\_t** \* control\_settings )

Set settings of motor control.

When choosing CTL\_MODE = 1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i = 0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL\_MODE = 2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout [i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i + 1] to acceleration, as usual.

Parameters

|    |                         |  |
|----|-------------------------|--|
|    | <i>id</i>               | an identifier of device  |
| in | <i>control_settings</i> | structure contains settings motor control by joystick or buttons left/right. |

5.1.4.77 **result\_t XIMC\_API** set\_controller\_name ( **device\_t** id, const **controller\_name\_t** \* controller\_name )

Write user controller name and flags of setting from FRAM.

Parameters

|    |                        |  |
|----|------------------------|--|
|    | <i>id</i>              | an identifier of device                                |
| in | <i>controller_name</i> | structure contains previously set user controller name |

5.1.4.78 **result\_t XIMC\_API** set\_ctp\_settings ( **device\_t** id, const **ctp\_settings\_t** \* ctp\_settings )

Set settings of control position(is only used with stepper motor).

When controlling the step motor with encoder (CTP\_BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP\_ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is greater CTPMinError, a flag STATE\_CTP\_ERROR. When controlling the step motor with speed sensor (CTP\_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE\_CTP\_ERROR.

Parameters

|    |                     |   |
|----|---------------------|---|
|    | <i>id</i>           | an identifier of device                         |
| in | <i>ctp_settings</i> | structure contains settings of control position |

5.1.4.79 **result\_t XIMC\_API** set\_edges\_settings ( **device\_t** id, const **edges\_settings\_t** \* edges\_settings )

Set border and limit switches settings.

See also

[set\\_edges\\_settings](#)

Parameters

|    |                       |  |
|----|-----------------------|--|
|    | <i>id</i>             | an identifier of device  |
| in | <i>edges_settings</i> | edges settings, specify types of borders, motor behaviour and electrical behaviour of limit switches |

5.1.4.80 **result\_t XIMC\_API** set\_encoder\_information ( **device\_t** id, const **encoder\_information\_t** \* encoder\_information )

Set encoder information to EEPROM.

Can be used by manufacturer only.

Parameters

|    |                            |  |
|----|----------------------------|--|
|    | <i>id</i>                  | an identifier of device                      |
| in | <i>encoder_information</i> | structure contains information about encoder |

5.1.4.81 **result\_t XIMC\_API** set\_encoder\_settings ( **device\_t** id, const **encoder\_settings\_t** \* encoder\_settings )

Set encoder settings to EEPROM.

Can be used by manufacturer only.

Parameters

|    |                         |                                     |
|----|-------------------------|-------------------------------------|
|    | <i>id</i>               | an identifier of device             |
| in | <i>encoder_settings</i> | structure contains encoder settings |

5.1.4.82 **result\_t XIMC\_API** set\_engine\_settings ( **device\_t** id, const **engine\_settings\_t** \* engine\_settings )

Set engine settings.

This function send structure with set of engine settings to controller's memory. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics. Use it when you change motor, encoder, positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See also

[get\\_engine\\_settings](#)

Parameters

|    |                        |                         |
|----|------------------------|-------------------------|
|    | <i>id</i>              | an identifier of device |
| in | <i>engine_settings</i> | engine settings         |

5.1.4.83 **result\_t XIMC\_API** set\_entype\_settings ( **device\_t** id, const **entype\_settings\_t** \* entype\_settings )

Set engine type and driver type.

## Parameters

|    |                   |                         |
|----|-------------------|-------------------------|
|    | <i>id</i>         | an identifier of device |
| in | <i>EngineType</i> | engine type             |
| in | <i>DriverType</i> | driver type             |

5.1.4.84 **result\_t XIMC\_API** set\_extio\_settings ( **device\_t** id, const **extio\_settings\_t** \* extio\_settings )

Set EXTIO settings.

This function writes a structure with a set of EXTIO settings to controller's memory. By default input event are signalled through rising front and output states are signalled by high logic state.

See also

[get\\_extio\\_settings](#)

## Parameters

|    |                       |                         |
|----|-----------------------|-------------------------|
|    | <i>id</i>             | an identifier of device |
| in | <i>extio_settings</i> | EXTIO settings          |

5.1.4.85 **result\_t XIMC\_API** set\_feedback\_settings ( **device\_t** id, const **feedback\_settings\_t** \* feedback\_settings )

Set feedback settings.

## Parameters

|    |                      |  |
|----|----------------------|--|
|    | <i>id</i>            | an identifier of device  |
| in | <i>IPS</i>           | number of encoder pulses per shaft revolution. Range: 1..65535 |
| in | <i>FeedbackType</i>  | type of feedback   |
| in | <i>FeedbackFlags</i> | flags of feedback  |

5.1.4.86 **result\_t XIMC\_API** set\_gear\_information ( **device\_t** id, const **gear\_information\_t** \* gear\_information )

Set gear information to EEPROM.

Can be used by manufacturer only.

## Parameters

|    |                         |  |
|----|-------------------------|--|
|    | <i>id</i>               | an identifier of device                            |
| in | <i>gear_information</i> | structure contains information about step gearhead |

5.1.4.87 **result\_t XIMC\_API** set\_gear\_settings ( **device\_t** id, const **gear\_settings\_t** \* gear\_settings )

Set gear settings to EEPROM.

Can be used by manufacturer only.

## Parameters

|    |                      |   |
|----|----------------------|---|
|    | <i>id</i>            | an identifier of device                   |
| in | <i>gear_settings</i> | structure contains step gearhead settings |

5.1.4.88 **result\_t XIMC\_API** set\_hallsensor\_information ( **device\_t** id, const **hallsensor\_information\_t** \* hallsensor\_information )

Set hall sensor information to EEPROM.

Can be used by manufacturer only.

## Parameters

|    |                               |  |
|----|-------------------------------|--|
|    | <i>id</i>                     | an identifier of device                          |
| in | <i>hallsensor_information</i> | structure contains information about hall sensor |

5.1.4.89 **result\_t XIMC\_API** set\_hallsensor\_settings ( **device\_t** id, const **hallsensor\_settings\_t** \* hallsensor\_settings )

Set hall sensor settings to EEPROM.

Can be used by manufacturer only.

## Parameters

|    |                            |   |
|----|----------------------------|---|
|    | <i>id</i>                  | an identifier of device                 |
| in | <i>hallsensor_settings</i> | structure contains hall sensor settings |

5.1.4.90 **result\_t XIMC\_API** set\_home\_settings ( **device\_t** id, const **home\_settings\_t** \* home\_settings )

Set home settings.

This function send structure with calibrating position settings to controller's memory.

See also

[home\\_settings\\_t](#)

## Parameters

|    |                      |                               |
|----|----------------------|-------------------------------|
|    | <i>id</i>            | an identifier of device       |
| in | <i>home_settings</i> | calibrating position settings |

5.1.4.91 **result\_t XIMC\_API** set\_joystick\_settings ( **device\_t** id, const **joystick\_settings\_t** \* joystick\_settings )

Set settings of joystick.

If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next

speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The DeadZone ranges are illustrated on the following picture. [!/attachments/download/5563/range25p.png!](#) The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy. The following picture illustrates this: [!/attachments/download/3092/ExpJoystick.png!](#) The nonlinearity parameter is adjustable. Setting it to zero makes deviation/speed relation linear.

Parameters

|           |                          |                                      |
|-----------|--------------------------|--------------------------------------|
|           | <i>id</i>                | an identifier of device              |
| <i>in</i> | <i>joystick_settings</i> | structure contains joystick settings |

5.1.4.92 void **XIMC\_API** set\_logging\_callback ( **logging\_callback\_t** logging\_callback )

Sets a logging callback.

Call resets a callback to default (stderr, syslog) if NULL passed.

Parameters

|                         |                             |
|-------------------------|-----------------------------|
| <i>logging_callback</i> | a callback for log messages |
|-------------------------|-----------------------------|

5.1.4.93 **result\_t XIMC\_API** set\_motor\_information ( **device\_t** id, const **motor\_information\_t** \* motor\_information )

Set motor information to EEPROM.

Can be used by manufacturer only.

Parameters

|           |                          |                                      |
|-----------|--------------------------|--------------------------------------|
|           | <i>id</i>                | an identifier of device              |
| <i>in</i> | <i>motor_information</i> | structure contains motor information |

5.1.4.94 **result\_t XIMC\_API** set\_motor\_settings ( **device\_t** id, const **motor\_settings\_t** \* motor\_settings )

Set motor settings to EEPROM.

Can be used by manufacturer only.

Parameters

|           |                       |                                      |
|-----------|-----------------------|--------------------------------------|
|           | <i>id</i>             | an identifier of device              |
| <i>in</i> | <i>motor_settings</i> | structure contains motor information |

5.1.4.95 **result\_t XIMC\_API** set\_move\_settings ( **device\_t** id, const **move\_settings\_t** \* move\_settings )

Set command setup movement (speed, acceleration, threshold and etc).

Parameters

|           |                      |  |
|-----------|----------------------|--|
|           | <i>id</i>            | an identifier of device  |
| <i>in</i> | <i>move_settings</i> | structure contains move settings: speed, acceleration, deceleration etc. |



5.1.4.96 **result\_t XIMC\_API** set\_pid\_settings ( **device\_t** id, const **pid\_settings\_t** \* pid\_settings )

Set PID settings.

This function send structure with set of PID factors to controller's memory. These settings specify behaviour of PID routine for voltage. These factors are slightly different for different positioners. All boards are supplied with standart set of PID setting on controller's flash memory. Please use it for loading new PID settings when you change positioner. Please note that wrong PID settings lead to device malfunction.

See also

[get\\_pid\\_settings](#)

Parameters

|    |                     |                         |
|----|---------------------|-------------------------|
|    | <i>id</i>           | an identifier of device |
| in | <i>pid_settings</i> | pid settings            |

5.1.4.97 **result\_t XIMC\_API** set\_position ( **device\_t** id, const **set\_position\_t** \* the\_set\_position )

Sets any position value in steps and micro for stepper motor and encoder steps of all engines.

It means, that changing main indicator of position.

Parameters

|     |                 |  |
|-----|-----------------|--|
|     | <i>id</i>       | an identifier of device  |
| out | <i>position</i> | structure contains move settings: speed, acceleration, deceleration etc. |

5.1.4.98 **result\_t XIMC\_API** set\_power\_settings ( **device\_t** id, const **power\_settings\_t** \* power\_settings )

Set settings of step motor power control.

Used with stepper motor only.

Parameters

|    |                       |   |
|----|-----------------------|---|
|    | <i>id</i>             | an identifier of device                                 |
| in | <i>power_settings</i> | structure contains settings of step motor power control |

5.1.4.99 **result\_t XIMC\_API** set\_secure\_settings ( **device\_t** id, const **secure\_settings\_t** \* secure\_settings )

Set protection settings.

Parameters

|  |                        |                            |
|--|------------------------|----------------------------|
|  | <i>id</i>              | an identifier of device    |
|  | <i>secure_settings</i> | structure with secure data |

See also

`status_t::flags`

5.1.4.100 **result.t XIMC\_API** set\_serial\_number ( **device.t** id, const **serial\_number.t** \* serial\_number )

Write device serial number to controller's flash memory.

Along with the new serial number a "Key" is transmitted. The SN is changed and saved when keys match. Can be used by manufacturer only.

Parameters

|    |               |   |
|----|---------------|---|
|    | <i>id</i>     | an identifier of device                                     |
| in | <i>serial</i> | number structure contains new serial number and secret key. |

5.1.4.101 **result.t XIMC\_API** set\_stage\_information ( **device.t** id, const **stage\_information.t** \* stage\_information )

Set stage information to EEPROM.

Can be used by manufacturer only.

Parameters

|    |                          |                                      |
|----|--------------------------|--------------------------------------|
|    | <i>id</i>                | an identifier of device              |
| in | <i>stage-information</i> | structure contains stage information |

5.1.4.102 **result.t XIMC\_API** set\_stage\_name ( **device.t** id, const **stage\_name.t** \* stage\_name )

Write user stage name from EEPROM.

Parameters

|    |                   |   |
|----|-------------------|---|
|    | <i>id</i>         | an identifier of device                           |
| in | <i>stage_name</i> | structure contains previously set user stage name |

5.1.4.103 **result.t XIMC\_API** set\_stage\_settings ( **device.t** id, const **stage\_settings.t** \* stage\_settings )

Set stage settings to EEPROM.

Can be used by manufacturer only

Parameters

|    |                       |                                   |
|----|-----------------------|-----------------------------------|
|    | <i>id</i>             | an identifier of device           |
| in | <i>stage_settings</i> | structure contains stage settings |

5.1.4.104 **result.t XIMC\_API** set\_sync\_in\_settings ( **device.t** id, const **sync.in\_settings.t** \* sync.in\_settings )

Set input synchronization settings.

This function send structure with set of input synchronization settings, that specify behaviour of input synchronization, to controller's memory. All boards are supplied with standart set of these settings.

See also

[get\\_sync\\_in\\_settings](#)

Parameters

|           |                         |                          |
|-----------|-------------------------|--------------------------|
|           | <i>id</i>               | an identifier of device  |
| <i>in</i> | <i>sync_in_settings</i> | synchronization settings |

5.1.4.105 **result\_t XIMC\_API** set\_sync\_out\_settings ( **device\_t** id, const **sync\_out\_settings\_t** \* sync\_out\_settings )

Set output synchronization settings.

This function send structure with set of output synchronization settings, that specify behaviour of output synchronization, to controller's memory. All boards are supplied with standart set of these settings.

See also

[get\\_sync\\_out\\_settings](#)

Parameters

|           |                          |                          |
|-----------|--------------------------|--------------------------|
|           | <i>id</i>                | an identifier of device  |
| <i>in</i> | <i>sync_out_settings</i> | synchronization settings |

5.1.4.106 **result\_t XIMC\_API** set\_uart\_settings ( **device\_t** id, const **uart\_settings\_t** \* uart\_settings )

Set UART settings.

This function send structure with UART settings to controller's memory.

See also

[uart\\_settings\\_t](#)

Parameters

|           |                      |               |
|-----------|----------------------|---------------|
|           | <i>Speed</i>         | UART speed    |
| <i>in</i> | <i>uart_settings</i> | UART settings |

5.1.4.107 **result\_t XIMC\_API** write\_key ( const char \* name, uint8\_t \* key )

Write controller key.

Can be used by manufacturer only

Parameters

|           |             |                                      |
|-----------|-------------|--------------------------------------|
|           | <i>name</i> | a name of device                     |
| <i>in</i> | <i>key</i>  | protection key. Range: 0..4294967295 |

5.1.4.108 **result\_t XIMC\_API** ximc\_fix\_usbser\_sys ( const char \* device\_name )

Fix for errors in Windows USB driver stack.

Resets a driver if a device exists and in a hanged state.

5.1.4.109 void **XIMC\_API** ximc\_version ( char \* version )

Returns a library version.

Parameters

|                |   |
|----------------|---|
| <i>version</i> | a buffer to hold a version string, 32 bytes is enough |
|----------------|---|

# Index

Accel  
    move\_settings\_t, 35  
accessories\_settings\_t, 7  
    MBRatedCurrent, 8  
    MBRatedVoltage, 8  
    MBTorque, 8  
    TSGrad, 8  
Accuracy  
    sync\_out\_settings\_t, 48  
add\_sync\_in\_action\_calb\_t, 8  
add\_sync\_in\_action\_t, 8  
    Speed, 9  
    uPosition, 9  
    uSpeed, 9  
analog\_data\_t, 9  
Antiplay  
    engine\_settings\_calb\_t, 20  
    engine\_settings\_t, 21  
AntiplaySpeed  
    move\_settings\_t, 35  
  
brake\_settings\_t, 11  
    t1, 11  
    t2, 11  
    t3, 11  
    t4, 11  
  
CTPMinError  
    ctp\_settings\_t, 16  
calibration\_t, 12  
chart\_data\_t, 12  
close\_device  
    ximc.h, 71  
ClutterTime  
    sync\_in\_settings\_calb\_t, 45  
    sync\_in\_settings\_t, 46  
command\_clear\_fram  
    ximc.h, 72  
command\_eeread\_settings  
    ximc.h, 72  
command\_eesave\_settings  
    ximc.h, 72  
command\_home  
    ximc.h, 72  
command\_left  
    ximc.h, 73  
command\_loft  
    ximc.h, 73  
command\_move  
    ximc.h, 73  
command\_movr  
    ximc.h, 73  
command\_power\_off  
    ximc.h, 73  
command\_read\_settings  
    ximc.h, 74  
command\_reset  
    ximc.h, 74  
command\_right  
    ximc.h, 74  
command\_save\_settings  
    ximc.h, 74  
command\_sstp  
    ximc.h, 74  
command\_stop  
    ximc.h, 75  
command\_update\_firmware  
    ximc.h, 75  
command\_zero  
    ximc.h, 75  
control\_settings\_calb\_t, 13  
    MaxClickTime, 13  
    Timeout, 13  
control\_settings\_t, 13  
    MaxClickTime, 14  
    MaxSpeed, 14  
    Timeout, 14  
    uDeltaPosition, 14  
    uMaxSpeed, 14  
controller\_name\_t, 14  
    ControllerName, 15  
ControllerName  
    controller\_name\_t, 15  
Criticalpwr  
    secure\_settings\_t, 38  
Criticalusb  
    secure\_settings\_t, 38  
CriticalT  
    secure\_settings\_t, 38  
CriticalUpwr  
    secure\_settings\_t, 38  
CriticalUusb  
    secure\_settings\_t, 38  
ctp\_settings\_t, 15  
    CTPMinError, 16  
CurrReductDelay  
    power\_settings\_t, 37  
CurrentSetTime  
    power\_settings\_t, 37

- debug\_read.t, 16
- Decel
  - move\_settings.t, 35
- DetentTorque
  - motor\_settings.t, 32
- device\_information.t, 16
- ENGINE\_ACCEL\_ON
  - ximc.h, 69
- ENGINE\_ANTIPLAY
  - ximc.h, 69
- ENGINE\_MAX\_SPEED
  - ximc.h, 70
- ENGINE\_REVERSE
  - ximc.h, 70
- ENGINE\_TYPE\_TEST
  - ximc.h, 70
- ENUMERATE\_PROBE
  - ximc.h, 70
- EXTIO\_SETUP\_INVERT
  - ximc.h, 70
- edges\_settings\_calb.t, 17
- edges\_settings.t, 17
  - LeftBorder, 17
  - RightBorder, 17
  - uLeftBorder, 18
  - uRightBorder, 18
- Efficiency
  - gear\_settings.t, 25
- encoder\_information.t, 18
  - Manufacturer, 18
  - PartNumber, 18
- encoder\_settings.t, 19
  - MaxCurrentConsumption, 19
  - MaxOperatingFrequency, 19
  - SupplyVoltageMax, 19
  - SupplyVoltageMin, 19
- engine\_settings\_calb.t, 20
  - Antiplay, 20
  - NomCurrent, 20
  - NomSpeed, 20
  - NomVoltage, 20
  - StepsPerRev, 20
- engine\_settings.t, 21
  - Antiplay, 21
  - NomCurrent, 21
  - NomSpeed, 21
  - NomVoltage, 22
  - StepsPerRev, 22
  - uNomSpeed, 22
- entype\_settings.t, 22
- enumerate\_devices
  - ximc.h, 75
- extio\_settings.t, 22
- FastHome
  - home\_settings.t, 29
- feedback\_settings.t, 23
- free\_enumerate\_devices
  - ximc.h, 75
- gear\_information.t, 23
  - Manufacturer, 24
  - PartNumber, 24
- gear\_settings.t, 24
  - Efficiency, 25
  - InputInertia, 25
  - MaxOutputBacklash, 25
  - RatedInputSpeed, 25
  - RatedInputTorque, 25
  - ReductionIn, 25
  - ReductionOut, 25
- get\_accessories\_settings
  - ximc.h, 76
- get\_analog\_data
  - ximc.h, 76
- get\_bootloader\_version
  - ximc.h, 76
- get\_brake\_settings
  - ximc.h, 76
- get\_chart\_data
  - ximc.h, 76
- get\_control\_settings
  - ximc.h, 77
- get\_controller\_name
  - ximc.h, 77
- get\_ctp\_settings
  - ximc.h, 77
- get\_debug\_read
  - ximc.h, 77
- get\_device\_count
  - ximc.h, 78
- get\_device\_information
  - ximc.h, 78
- get\_device\_name
  - ximc.h, 78
- get\_edges\_settings
  - ximc.h, 78
- get\_encoder\_information
  - ximc.h, 79
- get\_encoder\_settings
  - ximc.h, 79
- get\_engine\_settings
  - ximc.h, 79
- get\_entype\_settings
  - ximc.h, 79
- get\_enumerate\_device\_information
  - ximc.h, 79
- get\_enumerate\_device\_serial
  - ximc.h, 80
- get\_extio\_settings
  - ximc.h, 80
- get\_feedback\_settings
  - ximc.h, 80
- get\_firmware\_version
  - ximc.h, 80
- get\_gear\_information
  - ximc.h, 81

- get\_gear\_settings
  - ximc.h, [81](#)
- get\_hallsensor\_information
  - ximc.h, [81](#)
- get\_hallsensor\_settings
  - ximc.h, [81](#)
- get\_home\_settings
  - ximc.h, [81](#)
- get\_joystick\_settings
  - ximc.h, [82](#)
- get\_motor\_information
  - ximc.h, [82](#)
- get\_motor\_settings
  - ximc.h, [82](#)
- get\_move\_settings
  - ximc.h, [82](#)
- get\_pid\_settings
  - ximc.h, [83](#)
- get\_position
  - ximc.h, [83](#)
- get\_position\_calb\_t, [26](#)
- get\_position\_t, [26](#)
- get\_power\_settings
  - ximc.h, [83](#)
- get\_secure\_settings
  - ximc.h, [83](#)
- get\_serial\_number
  - ximc.h, [84](#)
- get\_stage\_information
  - ximc.h, [84](#)
- get\_stage\_name
  - ximc.h, [84](#)
- get\_stage\_settings
  - ximc.h, [84](#)
- get\_status
  - ximc.h, [84](#)
- get\_status\_calb
  - ximc.h, [85](#)
- get\_sync\_in\_settings
  - ximc.h, [85](#)
- get\_sync\_out\_settings
  - ximc.h, [85](#)
- get\_uart\_settings
  - ximc.h, [85](#)
- goto\_firmware
  - ximc.h, [86](#)
- HOME\_DIR\_FIRST
  - ximc.h, [70](#)
- HOME\_DIR\_SECOND
  - ximc.h, [70](#)
- hallsensor\_information\_t, [26](#)
  - Manufacturer, [27](#)
  - PartNumber, [27](#)
- hallsensor\_settings\_t, [27](#)
  - MaxCurrentConsumption, [27](#)
  - MaxOperatingFrequency, [27](#)
  - SupplyVoltageMax, [27](#)
  - SupplyVoltageMin, [28](#)
- has\_firmware
  - ximc.h, [86](#)
- HoldCurrent
  - power\_settings\_t, [37](#)
- home\_settings\_calb\_t, [28](#)
- home\_settings\_t, [28](#)
  - FastHome, [29](#)
  - HomeDelta, [29](#)
  - SlowHome, [29](#)
  - uFastHome, [29](#)
  - uHomeDelta, [29](#)
  - uSlowHome, [29](#)
- HomeDelta
  - home\_settings\_t, [29](#)
- HorizontalLoadCapacity
  - stage\_settings\_t, [42](#)
- InputInertia
  - gear\_settings\_t, [25](#)
- JOY\_REVERSE
  - ximc.h, [70](#)
- joystick\_settings\_t, [29](#)
- LeadScrewPitch
  - stage\_settings\_t, [42](#)
- LeftBorder
  - edges\_settings\_t, [17](#)
- logging\_callback\_stderr\_narrow
  - ximc.h, [86](#)
- logging\_callback\_stderr\_wide
  - ximc.h, [86](#)
- logging\_callback\_t
  - ximc.h, [71](#)
- LowUpwrOff
  - secure\_settings\_t, [38](#)
- MBRatedCurrent
  - accessories\_settings\_t, [8](#)
- MBRatedVoltage
  - accessories\_settings\_t, [8](#)
- MBTorque
  - accessories\_settings\_t, [8](#)
- MVCMD\_ERROR
  - ximc.h, [70](#)
- Manufacturer
  - encoder\_information\_t, [18](#)
  - gear\_information\_t, [24](#)
  - hallsensor\_information\_t, [27](#)
  - motor\_information\_t, [31](#)
  - stage\_information\_t, [40](#)
- MaxClickTime
  - control\_settings\_calb\_t, [13](#)
  - control\_settings\_t, [14](#)
- MaxCurrent
  - motor\_settings\_t, [32](#)
- MaxCurrentConsumption
  - encoder\_settings\_t, [19](#)
  - hallsensor\_settings\_t, [27](#)

- stage\_settings.t, [42](#)
- MaxCurrentTime
  - motor\_settings.t, [32](#)
- MaxOperatingFrequency
  - encoder\_settings.t, [19](#)
  - hallsensor\_settings.t, [27](#)
- MaxOutputBacklash
  - gear\_settings.t, [25](#)
- MaxSpeed
  - control\_settings.t, [14](#)
  - motor\_settings.t, [32](#)
  - stage\_settings.t, [42](#)
- MechanicalTimeConstant
  - motor\_settings.t, [32](#)
- MinimumUusb
  - secure\_settings.t, [39](#)
- motor\_information.t, [30](#)
  - Manufacturer, [31](#)
  - PartNumber, [31](#)
- motor\_settings.t, [31](#)
  - DetentTorque, [32](#)
  - MaxCurrent, [32](#)
  - MaxCurrentTime, [32](#)
  - MaxSpeed, [32](#)
  - MechanicalTimeConstant, [32](#)
  - NoLoadCurrent, [33](#)
  - NoLoadSpeed, [33](#)
  - NominalCurrent, [33](#)
  - NominalPower, [33](#)
  - NominalSpeed, [33](#)
  - NominalTorque, [33](#)
  - NominalVoltage, [33](#)
  - RotorInertia, [33](#)
  - SpeedConstant, [33](#)
  - SpeedTorqueGradient, [34](#)
  - StallTorque, [34](#)
  - TorqueConstant, [34](#)
  - WindingInductance, [34](#)
  - WindingResistance, [34](#)
- move\_settings\_calb.t, [34](#)
- move\_settings.t, [35](#)
  - Accel, [35](#)
  - AntiplaySpeed, [35](#)
  - Decel, [35](#)
  - Speed, [35](#)
  - uAntiplaySpeed, [35](#)
  - uSpeed, [36](#)
- msec\_sleep
  - ximc.h, [86](#)
- NoLoadCurrent
  - motor\_settings.t, [33](#)
- NoLoadSpeed
  - motor\_settings.t, [33](#)
- NomCurrent
  - engine\_settings\_calb.t, [20](#)
  - engine\_settings.t, [21](#)
- NomSpeed
  - engine\_settings\_calb.t, [20](#)
- engine\_settings.t, [21](#)
- NomVoltage
  - engine\_settings\_calb.t, [20](#)
  - engine\_settings.t, [22](#)
- NominalCurrent
  - motor\_settings.t, [33](#)
- NominalPower
  - motor\_settings.t, [33](#)
- NominalSpeed
  - motor\_settings.t, [33](#)
- NominalTorque
  - motor\_settings.t, [33](#)
- NominalVoltage
  - motor\_settings.t, [33](#)
- open\_device
  - ximc.h, [87](#)
- PartNumber
  - encoder\_information.t, [18](#)
  - gear\_information.t, [24](#)
  - hallsensor\_information.t, [27](#)
  - motor\_information.t, [31](#)
  - stage\_information.t, [40](#)
- pid\_settings.t, [36](#)
- PositionerName
  - stage\_name.t, [41](#)
- power\_settings.t, [36](#)
  - CurrReductDelay, [37](#)
  - CurrentSetTime, [37](#)
  - HoldCurrent, [37](#)
  - PowerOffDelay, [37](#)
- PowerOffDelay
  - power\_settings.t, [37](#)
- probe\_device
  - ximc.h, [87](#)
- REV\_SENS\_INV
  - ximc.h, [71](#)
- RatedInputSpeed
  - gear\_settings.t, [25](#)
- RatedInputTorque
  - gear\_settings.t, [25](#)
- ReductionIn
  - gear\_settings.t, [25](#)
- ReductionOut
  - gear\_settings.t, [25](#)
- RightBorder
  - edges\_settings.t, [17](#)
- RotorInertia
  - motor\_settings.t, [33](#)
- STATE\_ALARM
  - ximc.h, [71](#)
- SYNCIN\_GOTOPOSITION
  - ximc.h, [71](#)
- SYNCOUT\_ENABLED
  - ximc.h, [71](#)
- secure\_settings.t, [37](#)



- Criticalpwr, [38](#)
- Criticalusb, [38](#)
- CriticalT, [38](#)
- CriticalUpwr, [38](#)
- CriticalUusb, [38](#)
- LowUpwrOff, [38](#)
- MinimumUusb, [39](#)
- serial\_number\_t, [39](#)
- service\_command\_updf
  - ximc.h, [87](#)
- set\_accessories\_settings
  - ximc.h, [87](#)
- set\_add\_sync\_in\_action
  - ximc.h, [87](#)
- set\_brake\_settings
  - ximc.h, [87](#)
- set\_control\_settings
  - ximc.h, [88](#)
- set\_controller\_name
  - ximc.h, [88](#)
- set\_ctp\_settings
  - ximc.h, [88](#)
- set\_edges\_settings
  - ximc.h, [88](#)
- set\_encoder\_information
  - ximc.h, [89](#)
- set\_encoder\_settings
  - ximc.h, [89](#)
- set\_engine\_settings
  - ximc.h, [89](#)
- set\_entype\_settings
  - ximc.h, [89](#)
- set\_extio\_settings
  - ximc.h, [90](#)
- set\_feedback\_settings
  - ximc.h, [90](#)
- set\_gear\_information
  - ximc.h, [90](#)
- set\_gear\_settings
  - ximc.h, [90](#)
- set\_hallsensor\_information
  - ximc.h, [91](#)
- set\_hallsensor\_settings
  - ximc.h, [91](#)
- set\_home\_settings
  - ximc.h, [91](#)
- set\_joystick\_settings
  - ximc.h, [91](#)
- set\_logging\_callback
  - ximc.h, [92](#)
- set\_motor\_information
  - ximc.h, [92](#)
- set\_motor\_settings
  - ximc.h, [92](#)
- set\_move\_settings
  - ximc.h, [92](#)
- set\_pid\_settings
  - ximc.h, [92](#)
- set\_position
  - ximc.h, [93](#)
- set\_position\_calb\_t, [39](#)
- set\_position\_t, [39](#)
- set\_power\_settings
  - ximc.h, [93](#)
- set\_secure\_settings
  - ximc.h, [93](#)
- set\_serial\_number
  - ximc.h, [93](#)
- set\_stage\_information
  - ximc.h, [94](#)
- set\_stage\_name
  - ximc.h, [94](#)
- set\_stage\_settings
  - ximc.h, [94](#)
- set\_sync\_in\_settings
  - ximc.h, [94](#)
- set\_sync\_out\_settings
  - ximc.h, [95](#)
- set\_uart\_settings
  - ximc.h, [95](#)
- SlowHome
  - home\_settings\_t, [29](#)
- Speed
  - add\_sync\_in\_action\_t, [9](#)
  - move\_settings\_t, [35](#)
  - sync\_in\_settings\_t, [46](#)
- SpeedConstant
  - motor\_settings\_t, [33](#)
- SpeedTorqueGradient
  - motor\_settings\_t, [34](#)
- stage\_information\_t, [40](#)
  - Manufacturer, [40](#)
  - PartNumber, [40](#)
- stage\_name\_t, [41](#)
  - PositionerName, [41](#)
- stage\_settings\_t, [41](#)
  - HorizontalLoadCapacity, [42](#)
  - LeadScrewPitch, [42](#)
  - MaxCurrentConsumption, [42](#)
  - MaxSpeed, [42](#)
  - SupplyVoltageMax, [42](#)
  - SupplyVoltageMin, [42](#)
  - TravelRange, [42](#)
  - Units, [43](#)
  - VerticalLoadCapacity, [43](#)
- StallTorque
  - motor\_settings\_t, [34](#)
- status\_calb\_t, [43](#)
- status\_t, [44](#)
  - uCurPosition, [45](#)
  - uCurSpeed, [45](#)
- StepsPerRev
  - engine\_settings\_calb\_t, [20](#)
  - engine\_settings\_t, [22](#)
- SupplyVoltageMax
  - encoder\_settings\_t, [19](#)

- hallsensor\_settings.t, [27](#)
- stage\_settings.t, [42](#)
- SupplyVoltageMin
  - encoder\_settings.t, [19](#)
  - hallsensor\_settings.t, [28](#)
  - stage\_settings.t, [42](#)
- sync\_in\_settings\_calb.t, [45](#)
  - ClutterTime, [45](#)
- sync\_in\_settings.t, [45](#)
  - ClutterTime, [46](#)
  - Speed, [46](#)
  - uPosition, [46](#)
  - uSpeed, [46](#)
- sync\_out\_settings\_calb.t, [46](#)
  - SyncOutPeriod, [47](#)
  - SyncOutPulseSteps, [47](#)
- sync\_out\_settings.t, [47](#)
  - Accuracy, [48](#)
  - SyncOutPeriod, [48](#)
  - SyncOutPulseSteps, [48](#)
  - uAccuracy, [48](#)
- SyncOutPeriod
  - sync\_out\_settings\_calb.t, [47](#)
  - sync\_out\_settings.t, [48](#)
- SyncOutPulseSteps
  - sync\_out\_settings\_calb.t, [47](#)
  - sync\_out\_settings.t, [48](#)
- t1
  - brake\_settings.t, [11](#)
- t2
  - brake\_settings.t, [11](#)
- t3
  - brake\_settings.t, [11](#)
- t4
  - brake\_settings.t, [11](#)
- TSGrad
  - accessories\_settings.t, [8](#)
- Timeout
  - control\_settings\_calb.t, [13](#)
  - control\_settings.t, [14](#)
- TorqueConstant
  - motor\_settings.t, [34](#)
- TravelRange
  - stage\_settings.t, [42](#)
- uAccuracy
  - sync\_out\_settings.t, [48](#)
- uAntiplaySpeed
  - move\_settings.t, [35](#)
- uCurPosition
  - status.t, [45](#)
- uCurSpeed
  - status.t, [45](#)
- uDeltaPosition
  - control\_settings.t, [14](#)
- uFastHome
  - home\_settings.t, [29](#)
- uHomeDelta
  - home\_settings.t, [29](#)
- uLeftBorder
  - edges\_settings.t, [18](#)
- uMaxSpeed
  - control\_settings.t, [14](#)
- uNomSpeed
  - engine\_settings.t, [22](#)
- uPosition
  - add\_sync\_in\_action.t, [9](#)
  - sync\_in\_settings.t, [46](#)
- uRightBorder
  - edges\_settings.t, [18](#)
- uSlowHome
  - home\_settings.t, [29](#)
- uSpeed
  - add\_sync\_in\_action.t, [9](#)
  - move\_settings.t, [36](#)
  - sync\_in\_settings.t, [46](#)
- uart\_settings.t, [48](#)
- Units
  - stage\_settings.t, [43](#)
- VerticalLoadCapacity
  - stage\_settings.t, [43](#)
- WindingInductance
  - motor\_settings.t, [34](#)
- WindingResistance
  - motor\_settings.t, [34](#)
- write\_key
  - ximc.h, [95](#)
- XIMC\_API
  - ximc.h, [71](#)
- ximc.h, [49](#)
  - close\_device, [71](#)
  - command\_clear\_fram, [72](#)
  - command\_eeread\_settings, [72](#)
  - command\_eesave\_settings, [72](#)
  - command\_home, [72](#)
  - command\_left, [73](#)
  - command\_loft, [73](#)
  - command\_move, [73](#)
  - command\_movr, [73](#)
  - command\_power\_off, [73](#)
  - command\_read\_settings, [74](#)
  - command\_reset, [74](#)
  - command\_right, [74](#)
  - command\_save\_settings, [74](#)
  - command\_sstp, [74](#)
  - command\_stop, [75](#)
  - command\_update\_firmware, [75](#)
  - command\_zero, [75](#)
  - ENGINE\_ACCEL\_ON, [69](#)
  - ENGINE\_ANTIPLAY, [69](#)
  - ENGINE\_MAX\_SPEED, [70](#)
  - ENGINE\_REVERSE, [70](#)
  - ENGINE\_TYPE\_TEST, [70](#)
  - ENUMERATE\_PROBE, [70](#)

EXTIO\_SETUP\_INVERT, 70  
enumerate\_devices, 75  
free\_enumerate\_devices, 75  
get\_accessories\_settings, 76  
get\_analog\_data, 76  
get\_bootloader\_version, 76  
get\_brake\_settings, 76  
get\_chart\_data, 76  
get\_control\_settings, 77  
get\_controller\_name, 77  
get\_ctp\_settings, 77  
get\_debug\_read, 77  
get\_device\_count, 78  
get\_device\_information, 78  
get\_device\_name, 78  
get\_edges\_settings, 78  
get\_encoder\_information, 79  
get\_encoder\_settings, 79  
get\_engine\_settings, 79  
get\_entype\_settings, 79  
get\_enumerate\_device\_information, 79  
get\_enumerate\_device\_serial, 80  
get\_extio\_settings, 80  
get\_feedback\_settings, 80  
get\_firmware\_version, 80  
get\_gear\_information, 81  
get\_gear\_settings, 81  
get\_hallsensor\_information, 81  
get\_hallsensor\_settings, 81  
get\_home\_settings, 81  
get\_joystick\_settings, 82  
get\_motor\_information, 82  
get\_motor\_settings, 82  
get\_move\_settings, 82  
get\_pid\_settings, 83  
get\_position, 83  
get\_power\_settings, 83  
get\_secure\_settings, 83  
get\_serial\_number, 84  
get\_stage\_information, 84  
get\_stage\_name, 84  
get\_stage\_settings, 84  
get\_status, 84  
get\_status\_calb, 85  
get\_sync\_in\_settings, 85  
get\_sync\_out\_settings, 85  
get\_uart\_settings, 85  
goto\_firmware, 86  
HOME\_DIR\_FIRST, 70  
HOME\_DIR\_SECOND, 70  
has\_firmware, 86  
JOY\_REVERSE, 70  
logging\_callback\_stderr\_narrow, 86  
logging\_callback\_stderr\_wide, 86  
logging\_callback\_t, 71  
MVCMD\_ERROR, 70  
msec\_sleep, 86  
open\_device, 87  
probe\_device, 87  
REV\_SENS\_INV, 71  
STATE\_ALARM, 71  
SYNCIN\_GOTOPOSITION, 71  
SYNCOUT\_ENABLED, 71  
service\_command\_updf, 87  
set\_accessories\_settings, 87  
set\_add\_sync\_in\_action, 87  
set\_brake\_settings, 87  
set\_control\_settings, 88  
set\_controller\_name, 88  
set\_ctp\_settings, 88  
set\_edges\_settings, 88  
set\_encoder\_information, 89  
set\_encoder\_settings, 89  
set\_engine\_settings, 89  
set\_entype\_settings, 89  
set\_extio\_settings, 90  
set\_feedback\_settings, 90  
set\_gear\_information, 90  
set\_gear\_settings, 90  
set\_hallsensor\_information, 91  
set\_hallsensor\_settings, 91  
set\_home\_settings, 91  
set\_joystick\_settings, 91  
set\_logging\_callback, 92  
set\_motor\_information, 92  
set\_motor\_settings, 92  
set\_move\_settings, 92  
set\_pid\_settings, 92  
set\_position, 93  
set\_power\_settings, 93  
set\_secure\_settings, 93  
set\_serial\_number, 93  
set\_stage\_information, 94  
set\_stage\_name, 94  
set\_stage\_settings, 94  
set\_sync\_in\_settings, 94  
set\_sync\_out\_settings, 95  
set\_uart\_settings, 95  
write\_key, 95  
XIMC\_API, 71  
ximc\_fix\_usbser\_sys, 95  
ximc\_version, 96  
ximc\_fix\_usbser\_sys  
    ximc.h, 95  
ximc\_version  
    ximc.h, 96